


6/23/2021 10:25:09 AM R:\Projects\2021\121173 - Anamosa DOC Bldg RE-14 Stairs\Central Files\21173.rvt Above low limits the use of this document (drawing/data) to this specific project only, and duplication whole or in part for use on other than this project is prohibited. COPYRIGHT PROTECTION UNDER FEDERAL LAW TITLE 17, U.S. CODE.

# ANAMOSA PENITENTIARY

## STAIR REPLACEMENT

### ANAMOSA, IA



ISOMETRIC STAIR VIEW

| SHEET INDEX  |          |                               |
|--------------|----------|-------------------------------|
| SHEET NUMBER | REV. NO. | SHEET TITLE                   |
| G000         | A        | TITLE SHEET                   |
| G001         | A        | GENERAL NOTES                 |
| F100         | A        | FOUNDATION PLAN AND DETAILS   |
| S100         | A        | STAIR FRAMING PLAN & SECTIONS |
| S500         | A        | STRUCTURAL DETAILS            |
| S501         | A        | STAIR DETAILS                 |

**PRELIMINARY**  
NOT FOR CONSTRUCTION

|     |                   |          |
|-----|-------------------|----------|
|     |                   |          |
|     |                   |          |
|     |                   |          |
| A   | ISSUED FOR REVIEW | 06/23/21 |
| NO. | REVISION          | DATE     |



Shoemaker  
Haaland  
www.shoemaker-haaland.com

OWNER  
ANAMOSA  
PENITENTIARY

PROJECT  
STAIR REPLACEMENT

SHEET TITLE  
TITLE SHEET

PROJECT NUMBER  
21173

DATE 06/23/21  
DRAWN CBL  
CHKD RAH  
APPROV. REK

SHEET NUMBER  
G000



6/23/2021 10:25:09 AM R:\Projects\2021\21173 - Anamosa DOC Bldg RE-14 Stairs\Central Files\21173.rvt

Above the limits the use of this document (drawing/data) to this specific project only, and duplication whole or in part for use on other than this project is prohibited. COPYRIGHT PROTECTION UNDER FEDERAL LAW TITLE 17, U.S. CODE.

GENERAL NOTES:

CODES, STANDARDS, AND SPECIFICATIONS

- 1. DESIGN AND CONSTRUCTION OF THIS PROJECT SHALL CONFORM TO THE REQUIREMENTS OF THE 2015 EDITION OF THE INTERNATIONAL BUILDING CODE (IBC) AND ANY APPLICABLE AMENDMENTS, AS ADOPTED BY THE AUTHORITY HAVING JURISDICTION
- 2. DESIGN REQUIREMENTS FOR THE MATERIALS OF CONSTRUCTION BASED ON THE REFERENCED STANDARDS IN CHAPTER 35 OF THE IBC
- 3. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA) 29 CFR 1910 - STANDARDS FOR GENERAL INDUSTRY AND CFR 1926 - SAFETY AND HEALTH REGULATIONS FOR CONSTRUCTION HAVE BEEN REFERENCED FOR REQUIREMENTS RELATED TO WORKPLACE SAFETY

STRUCTURAL DESIGN INFORMATION

- 1. DESIGN LIVE LOADS  
STAIRS, CORRIDORS 100 PSF

GENERAL STRUCTURAL NOTES

- 1. ALL WORK SHALL CONFORM TO ALL APPLICABLE BUILDING CODES, ORDINANCES, AND REGULATIONS AS ADOPTED BY LOCAL AUTHORITIES HAVING JURISDICTIONS
- 2. ENGINEER SHALL NOT HAVE CONTROL OR CHARGE OF, AND SHALL NOT BE RESPONSIBLE FOR: CONSTRUCTION MEANS, METHODS, TECHNIQUES, SEQUENCES, OR PROCEDURES, FOR SAFETY PRECAUTIONS AND PROGRAMS IN CONNECTION WITH THE WORK, FOR THE ACTS OR OMISSION OF THE CONTRACTOR, SUBCONTRACTOR, OR ANY OTHER PERSONS PERFORMING ANY OF THE WORK, OR FOR THE FAILURE OF ANY OF THEM TO CARRY OUT THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS
- 3. THE CONTRACTOR SHALL VERIFY ALL CONDITIONS, DIMENSIONS, AND ELEVATIONS AT THE SITE. IF ACTUAL CONDITIONS DIFFER FROM THOSE SHOWN ON CONTRACT DOCUMENTS, CONSTRUCTION OF ANY AFFECTED ELEMENTS SHALL NOT COMMENCE WITHOUT APPROVAL OF DESIGN ENGINEER
- 4. THE LOCATION OF ANY EXISTING UTILITIES SHOWN ON THE DRAWINGS ARE TAKEN FROM EXISTING RECORDS. ADDITIONAL UTILITIES MAY BE ENCOUNTERED DURING CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING ALL UTILITIES WHICH COME IN CONFLICT WITH THE PROPOSED CONSTRUCTION
- 5. THE CONTRACTOR SHALL SUBMIT A WRITTEN REQUEST TO THE DESIGN ENGINEER FOR APPROVAL BEFORE PROCEEDING WITH ANY CHANGES, MODIFICATIONS OR SUBSTITUTIONS DIFFERING FROM CONTRACT DOCUMENTS
- 6. THE CONTRACTOR SHALL PROVIDE ADEQUATE TEMPORARY SHORING AND BRACING FOR ALL STRUCTURAL ELEMENTS UNTIL THE ENTIRE STRUCTURAL SYSTEM IS PLUMB AND SECURED
- 7. THE CONTRACTOR SHALL VERIFY THE POSITION, ELEVATION, AND ORIENTATION OF PROCESS EQUIPMENT PRIOR TO FABRICATION. THIS INCLUDES ANCHOR BOLT SIZES AND LOCATIONS, FLOOR PENETRATIONS, AND REQUIRED CLEARANCES TO ADJACENT WALLS, FRAMING, AND OTHER OBSTRUCTIONS
- 8. WHERE NEW CONSTRUCTION INTERFACES WITH EXISTING, FIELD VERIFY EXISTING DIMENSIONS, MEMBER SIZES, AND ELEVATIONS SHOWN ON THE DRAWINGS PRIOR TO STARTING CONSTRUCTION. ALL DISCREPANCIES SHALL BE IMMEDIATELY BROUGHT TO THE ATTENTION OF THE DESIGN ENGINEER.
- 9. DO NOT SCALE DIMENSIONS FROM DRAWINGS. INTERPRETATION OF PLANS, DETAILS, DIMENSIONS, OR OTHER ITEMS PROVIDED IN THE CONTRACT DOCUMENTS ARE TO BE COMPLETED BY THE DESIGN ENGINEER
- 10. DETAILED SHOP DRAWINGS SHALL BE SUBMITTED FOR APPROVAL, BY THE OWNER AND DESIGN ENGINEER, PRIOR TO FABRICATION FOR ALL STRUCTURAL ITEMS INCLUDING: CONCRETE AND MASONRY REINFORCEMENT, EMBEDDED STEEL ITEMS, STRUCTURAL STEEL, STEEL STACKS, STEEL JOISTS, STEEL DECKING, METAL GRATING, GUARDRAILS AND STAIRS
- 11. ALL OPEN EXCAVATIONS SHALL CONFORM TO OSHA STANDARDS FOR THE CONSTRUCTION INDUSTRY
- 12. WHERE APPLICATION IS MADE TO THE BUILDING OFFICIAL FOR CONSTRUCTION, THE OWNER SHALL EMPLOY A SPECIAL INSPECTOR TO PROVIDE INSPECTIONS AND TESTS PER THE REQUIREMENTS OF CHAPTER 17 OF THE IBC UNLESS WAIVED BY THE BUILDING OFFICIAL
- 13. PERIODIC SITE OBSERVATION BY THE ENGINEER IS SOLELY FOR THE PURPOSE OF DETERMINING IF WORK IS PROCEEDING IN ACCORDANCE WITH STRUCTURAL CONTRACT DOCUMENTS. THIS LIMITED SITE OBSERVATION SHOULD NOT BE CONSTRUED AS EXHAUSTIVE OR CONTINUOUS TO CHECK THE QUALITY OF WORK, BUT RATHER AS PERIODIC IN AN EFFORT TO REVIEW THE PROGRESS OF THE CONTRACTOR

STRUCTURAL STEEL

- 1. MATERIALS:  
WIDE FLANGE (W AND WT) - ASTM A992  
ANGLES (L), CHANNELS (C AND MC), BEAMS (S AND M) - ASTM A36  
PLATES (PL) AND BARS - ASTM A36  
HP SHAPES (HP) - ASTM A572 GR. 50  
SQUARE/RECTANGULAR HSS - ASTM A500 GR. C  
ROUND HOLLOW STRUCTURAL SECTIONS - ASTM A500 GR. C  
STANDARD STEEL PIPE - ASTM A53 GR. B  
RAISED-PATTERN FLOOR PLATE - ASTM A786 COMMERCIAL GRADE  
STEEL CONNECTION BOLTS - ASTM F3125 GR. A325 (TYP.) OR GR. A490  
WELD MATERIAL - AWS A5.1 E70XX  
ANCHOR BOLTS - ASTM F1554 GR. 36  
STAINLESS STEEL SHAPES - ASTM A276 TYPE 304 Fy = 30 KSI  
HEADED WELDED STEEL STUDS - ASTM A108, TYPE B  
HEAVY HEX NUTS - ASTM A563  
WASHERS - ASTM F436
- 2. FABRICATION AND ERECTION TO BE IN ACCORDANCE WITH AISC 360 SPECIFICATIONS
- 3. BEAM CONNECTIONS ARE TO BE EQUAL TO OR GREATER THAN ONE HALF THE UNIFORM LOAD CAPACITY OF THE BEAM. THE LENGTH OF CONNECTION ANGLES SHALL NOT BE LESS THAN HALF THE "T" DISTANCE OF THE BEAM WEB. ALL MAJOR BOLTED CONNECTIONS ARE TO BE BEARING TYPE CONNECTIONS USING DOUBLE CLIP ANGLES AND 3/4"Ø A325N BOLTS AND NUTS UNLESS NOTED OTHERWISE.
- 4. FIELD CUTTING OR OTHER FIELD MODIFICATIONS TO STRUCTURAL STEEL SHALL NOT BE MADE WITHOUT SPECIFIC PRIOR WRITTEN APPROVAL OF THE ENGINEER
- 5. ALL STRUCTURAL STEEL PLAN DIMENSIONS ARE TO CENTER LINE OF BEAMS AND COLUMNS AND TO THE BACK OF CHANNELS AND ANGLES, U.N.O. FOR HORIZONTAL BRACING, ELEVATIONS ARE GIVEN TO THE TOP OF THE STRUCTURAL MEMBER
- 6. THE CENTER OF GRAVITY OF BRACES AND SUPPORT MEMBERS ARE TO INTERSECT IN A MANNER TO AVOID ECCENTRICITY WHERE PRACTICAL; OTHERWISE FASTENERS AND SUPPORT MEMBERS ARE TO ACCOMMODATE STRESS DUE TO ECCENTRICITY, INCLUDING PRYING ACTION IN FRAMING ANGLES OR FLANGED GUSSETS
- 7. CAPACITY OF CONNECTIONS FOR BRACING MEMBERS TO BE CAPABLE OF DEVELOPING THE NET SECTION STRENGTH OF THE MEMBERS IN COMPRESSION, U.N.O.
- 8. ALL WELDING AND TESTING OF WELDS SHALL BE IN ACCORDANCE WITH THE LATEST AWS CODES AND RECOMMENDATIONS AND SHALL BE COMPLETED BY AWS QUALIFIED WELDERS WITH CURRENT AWS CERTIFICATION
- 9. WELDING ELECTRODES SHALL BE IN ACCORDANCE WITH AWS D1.1 AWS A5.1 OR A5.5; E70XX ARE GENERALLY REQUIRED FOR SHIELDED-METAL ARC WELDING; AWS A5.17 OR AWS A5.23, F7X-EXXX FOR SUBMERGED ARC WELDING; AWS A5.18, ER70S-X FOR GAS METAL ARC WELDING; AND AWS A5.0 E7XT-X FOR FLUX-CORED ARC WELDING
- 10. FABRICATION AND ERECTION WELDING TECHNIQUES SHALL CONFORM TO AWS D1.1; WELDERS SHALL BE QUALIFIED AND CERTIFIED TO PERFORM THE WORK REQUIRED IN ACCORDANCE WITH AWS D1.1 OR SIMILAR REQUIREMENTS
- 11. UNLESS NOTED OTHERWISE, ALL WELDS SHALL BE CONTINUOUS 3/16" FILLET WELDS
- 12. ALL BASE PLATES SUPPORTING STEEL COLUMNS SHALL BE GROUTED SOLID WITH HIGH STRENGTH (8,000 PSI MIN.), NON-SHRINK GROUT IMMEDIATELY AFTER STRUCTURAL STEEL IS IN PLACE AND PLUMB AND PRIOR TO PLACING ANY CONCRETE FOR THE ELEVATED FLOORS SUPPORTED BY THE RESPECTIVE COLUMNS
- 13. DAMAGE TO ANY GALVANIZED MATERIAL SHALL BE TOUCHED UP AS REQUIRED WITH A ZINC RICH PAINT
- 14. STRUCTURAL STEEL TO BE HOT DIPPED GALVANIZED FINISH

CAST-IN-PLACE CONCRETE

- 1. MATERIALS:  
CONCRETE - MINIMUM 28 DAY COMPRESSIVE STRENGTH  
4,500 PSI (5% - 7% AIR) = CONCRETE EXPOSED TO FREEZE THAW CYCLES  
4,000 PSI = ALL OTHER CONCRETE  
CEMENT - ASTM C150  
AGGREGATE - ASTM C33  
STEEL REINFORCING BARS - ASTM A615 GR. 60  
STEEL REINFORCING WELDABLE - ASTM A706 GR. 60  
WELDED WIRE FABRIC - ASTM A185  
GROUT - ASTM C827  
ANCHOR BOLTS - ASTM F1554 GR. 36
- 2. CONSTRUCTION SHALL BE IN ACCORDANCE WITH ACI 318 AND ACI 301 AND ALL LOCAL BUILDING CODES. REFER TO THE FOLLOWING CODE SECTIONS FOR SPECIFIC REQUIREMENTS:  
MIX PROPORTIONS - ACI 211.1  
HOT WEATHER CONCRETE - ACI 305R  
COLD WEATHER CONCRETE - ACI 306.1  
CONCRETE CURING - ACI 308  
CONCRETE CONSOLIDATION - ACI 309  
REBAR DETAILING AND PLACEMENT - ACI 315  
ENVIRONMENTAL STRUCTURES - ACI 350
- 3. CLEAR COVER FROM FACE OF CONCRETE TO OUTERMOST REINFORCING, UNLESS NOTED OTHERWISE:  
WALLS, PIERS - 2"  
COLUMNS (EDGE TIES) - 1-1/2"  
FOOTINGS - 3"  
SLABS EXPOSED TO EARTH AND WEATHER - 1-1/2"  
SLABS NOT EXPOSED TO EARTH AND WEATHER - 3/4"  
GRADE BEAMS - (EDGE OF STIRRUPS) - 1-1/2" TOP, 3" BOT., 3" SIDES
- 4. WATER REDUCING ADMIXTURES MAY BE INCORPORATED IN THE MIX DESIGN WITH THE APPROVAL OF THE ENGINEER. ADMIXTURE SHALL CONFORM TO ASTM C494 AND USED PER MANUFACTURER'S RECOMMENDATIONS. CHLORIDE CONTAINING ADMIXTURES SHALL NOT BE USED
- 5. AIR-ENTRAINING AGENTS SHALL CONFORM TO ASTM C260 WITH AMOUNTS IN ACCORDANCE WITH ACI 318. ENTRAINED AIR SHALL BE MEASURED IN THE FIELD AT THE DISCHARGE FROM THE TRUCK
- 6. ALL EXPOSED CONCRETE EDGES TO HAVE 3/4" CHAMFER, U.N.O.
- 7. BAR LAP SPLICES SHALL BE BASED UPON THE REQUIREMENTS OF ACI 318 OR CRSI UNLESS NOTED OTHERWISE. LAP WELD WIRE FABRIC SHEETS 8 INCHES MINIMUM. LAP SPLICES SHALL BE STAGGERED

PRELIMINARY  
NOT FOR CONSTRUCTION

|     |                   |          |
|-----|-------------------|----------|
|     |                   |          |
|     |                   |          |
|     |                   |          |
| A   | ISSUED FOR REVIEW | 06/23/21 |
| NO. | REVISION          | DATE     |



www.shoemaker-haaland.com

OWNER  
ANAMOSA  
PENITENTIARY

PROJECT  
STAIR REPLACEMENT

SHEET TITLE  
GENERAL NOTES





PROJECT NUMBER  
21173

DATE 06/23/21  
DRAWN CBL  
CHKD RAH  
APROV. REK

SHEET NUMBER

G001





**NOTE:**  
CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS  
AND ELEVATIONS PRIOR TO FABRICATION.  
CONTRACTOR TO VERIFY UNDERGROUND UTILITIES  
LOCATIONS

**PRELIMINARY**  
**NOT FOR CONSTRUCTION**

|     |                   |          |
|-----|-------------------|----------|
|     |                   |          |
|     |                   |          |
|     |                   |          |
| A   | ISSUED FOR REVIEW | 06/23/21 |
| NO. | REVISION          | DATE     |



Shoemaker  
Haaland

[www.shoemaker-haaland.com](http://www.shoemaker-haaland.com)

OWNER  
ANAMOSA  
PENITENTIARY

PROJECT  
STAIR REPLACEMENT


SHEET TITLE  
FOUNDATION PLAN AND DETAILS


PROJECT NUMBER  
**21173**

|         |          |
|---------|----------|
| DATE    | 06/23/21 |
| DRAWN   | CBL      |
| CHKD    | RAH      |
| APPROV. | REK      |

SHEET NUMBER  
**F100**







SIDE VIEW


FRONT VIEW

BOLTED BEAM CONNECTION SCHEDULE


| BEAM SIZE | CLIP ANGLE        | CLIP ANGLE LENGTH | BOLT QTY | BOLT DIA |
|-----------|-------------------|-------------------|----------|----------|
| W10 / C10 | L4 X 3 1/2 X 5/16 | 5 1/2"            | 2        | 3/4"     |
| W8 / C8   | L4 X 3 1/2 X 5/16 | 5 1/2"            | 2        | 3/4"     |
| C7        | L4 X 3 1/2 X 5/16 | 4 1/2"            | 2        | 3/4"     |

NOTE:  
1. UNLESS LOADS ARE GIVEN ON DRAWINGS, USE BOLT QUANTITIES SHOWN ON THIS TABLE FOR BEAM END CONNECTIONS.  
2. REFER TO GENERAL NOTES FOR ALL OTHER CONNECTIONS (UNO)


1 DOUBLE CLIP ANGLE BOLTED CONNECTION  
1" = 1'-0"




2 ANGLE BRACING BOLTED CONNECTION  
1" = 1'-0"




3 HORIZONTAL ANGLE BRACE AT INTERSECTING BEAMS  
3/4" = 1'-0"




4 CONNECTION PLATE DETAIL  
1 1/2" = 1'-0"



5 BEAM TO TUBE COLUMN SHEAR PLATE CONNECTION  
1" = 1'-0"



6 BEAM TO BEAM SHEAR TAB CONNECTION  
1" = 1'-0"



7 TYPICAL HSS BASE PLATE DETAIL  
1 1/2" = 1'-0"

PRELIMINARY  
NOT FOR CONSTRUCTION

|     |                   |          |
|-----|-------------------|----------|
|     |                   |          |
|     |                   |          |
|     |                   |          |
| A   | ISSUED FOR REVIEW | 06/23/21 |
| NO. | REVISION          | DATE     |

Shoemaker  
Haalan  
www.shoemaker-haaland.com

OWNER  
ANAMOSA  
PENITENTIARY

PROJECT  
STAIR REPLACEMENT

SHEET TITLE  
STRUCTURAL DETAILS

PROJECT NUMBER  
21173  
DATE 06/23/21  
DRAWN CBL  
CHKD RAH  
APPROV. REK

SHEET NUMBER

S500



Above low limits the use of this document (drawing/data) to this specific project only, and duplication whole or in part for use on other than this project is prohibited.



**HANDRAIL NOTE:**  
HANDRAILS SHALL RETURN TO A WALL, GUARDRAIL, OR WALKING SURFACE, OR BE CONTINUOUS TO HANDRAIL OF ADJACENT FLIGHT OF STAIRS. GUARDRAIL EXTENSIONS ARE NOT REQUIRED UNLESS HANDRAILS ARE RETURNED TO GUARDRAIL. SEE TOP & BOTTOM STAIR STRINGER CONNECTION DETAILS FOR HANDRAIL CONTINUITY AT ADJACENT FLIGHTS OF STAIRS.

**1** **TYPICAL STAIR DETAIL**  
3/4" = 1'-0"




**2 TYPICAL GUARDRAIL DETAIL**  
3/4" = 1'-0"




**4 TYPICAL BOLTED TOP MOUNT GUARDRAIL ON STEEL**  
3/4" = 1'-0"



NOTE:  
ALTERNATE TO BOLTING, WELD BENT  
PLATE ON (3) SIDES WITHOUT LEG



**3 TOP STAIR STRINGER DETAIL**  
3/4" = 1'-0"



**5** **BOTTOM STAIR STRINGER DETAIL**  
3/4" = 1'-0"

|     |                   |          |
|-----|-------------------|----------|
|     |                   |          |
|     |                   |          |
|     |                   |          |
| A   | ISSUED FOR REVIEW | 06/23/21 |
| NO. | REVISION          | DATE     |



|                |          |
|----------------|----------|
| PROJECT NUMBER |          |
| 21173          |          |
| DATE           | 06/23/21 |
| DRAWN          | CBL      |
| CHKD           | RAH      |
| APROV.         | REK      |

SHEET NUMBER

S501

