

**WORKMASTER 50 / 60 / 70**  
**US PRICE LIST**

## Standard Equipment

Changes contained in 10/1/2019 pages

The following high-take-rate options have been made standard equipment

- 337444 (Loader Ready)

The following low-take-rake options have been discontinued as FIO options

- 337985 (2 Rear Remotes)  
2 rear remotes remains available as a Dealer Installed Accessory 718259012
- 337891 (Vertical Exhaust)  
Vertical exhaust remains available as a Dealer Installed Accessory 718278012 (w/o Ldr) or 718279012 (w/Ldr)
- 337898 (540/540E RPM PTO)

-----  
**WORKMASTER# 50**

- 53 Engine hp @ 2600
- 45 PTO hp @ 2600

**WORKMASTER# 60**

- 60 Engine hp @ 2600
- 51 PTO hp @ 2600

**WORKMASTER# 70**

- 70 Engine hp @ 2600
- 62 PTO hp @ 2600

**ALL MODELS**

- 3 Cylinder Turbocharged Engine
- Tier 4b Final Emission Compliant
- 136.0 cu in (2.2 L) Displacement
- Mechanical Fuel Injection Pump
- Electric Engine Shutoff
- Hand and Foot Throttle Controls
- Quick Glow Plug Starting Aid
- Air Cleaner with dual dry elements
- Under Hood Muffler / Exhaust
- Fuel Sediment Filter
- Pivoting Engine Hood
- SMV Emblem
- B7 Biodiesel compatible
- 17.2 Gallon Fuel Tank (65 L)

**TRANSMISSION**

- 8 x 8 Transmission with Synchronized Left Hand Shuttle
- (4) Synchronized gears
- (2) Non-synchronized ranges
- 11 inch Traction Clutch

**FRONT AXLE - 2WD**

- Adjustable Front Axle
- Adjustable Rear Rims

**FRONT AXLE - 4WD**

- Mechanical FWD Engagement
- Front Drive Shaft Shield
- Adjustable Front & Rear Rims

**REAR AXLE**

- Flange Type Axle
- In-board Planetary Design
- Rear Diff Lock - Mechanical Engagement

**BRAKES**

- Mechanical Wet Brakes
- Park Brake - Hand Engagement

**STANDARD TIRES: WM 50**

- Tires - 2wd - R1
- Front: 7.5 X 16 6PR (F2)
- Rear: 13.6 X 28 6PR (R1)
- Tires - 4wd - R1
- Front: 8.3 X 24 6PR (R1)
- Rear: 13.6 X 28 6PR (R1)

**STANDARD TIRES: WM 50/70**

- Tires - 2wd - R1
- Front: 7.5 X 16 6PR (F2)
- Rear: 14.9 X 28 6PR (R1)
- Tires - 4wd - R1
- Front: 9.5 X 24 6PR (R1)
- Rear: 14.9 X 28 6PR (R1)

NOTE: All 4wd equipped units have a single gear box ratio allowing (AG), (R4) and (R3) tires to be swapped in the field without the need to change ratios.

**WORKMASTER 50 / 60 / 70**  
**US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM

Hydrostatic Power Steering  
Open Center System  
(1) Lever Controlled Rear Remote Valve  
(Float & Detent)  
Dual Gear Pumps  
Implement Pump: 11.9 gpm (45 L/M)  
Steering Pump: 5.5 gpm (21 L/M)

### LOADER READY

Includes Mid-Mount Valve & Joystick,  
Loader Mounts, Hose Kit & Grill Guard

### 3-POINT LIFT SYSTEM

Single Lever Position Control  
Lift Capacity @ Ball ends:  
3307 lbs. (1500 kg)  
Lift Capacity @ 24" behind ball ends:  
2701 lbs. (1125 kg)  
Combined Ball ends Cat I / Cat II  
Telescoping Stabilizers  
Flexible Link Ends  
Draft Control

### PTO

11 inch PTO Clutch  
Independent, 540 rpm PTO  
Single Lever, Mechanical Engagement  
Flip-up PTO Shaft Guard

### DRAWBAR

Flat Swinging Drawbar

### OPERATOR'S STATION

Straddle Deck Configuration  
2-post Foldable ROPS  
Contoured Cushion Seat  
- Fore / Aft Adjustment  
- Retractable Seat Belt  
- Operator's Presence Sensor  
Cupholder  
Toolbox

### INSTRUMENT PANEL

Digital / Analog Instrument Panel with  
warning lights, engine temperature,  
fuel level gauges, tachometer and hour  
meter

### ELECTRICAL

(1) 12-volt, 720 CCA Battery  
Alternator = 75 amp  
7 Pin Outllet - For trailer/implement  
lighting

### LIGHTING

(2) Halogen Headlights  
(2) Halogen Corner Work Lights  
Tail lights / Brake lights  
Turn Signals, Flashing warning lights

### WARRANTY

New Holland Standard Warranty Applies



**WORKMASTER 50 / 60 / 70  
US PRICE LIST**

**Models**

COMMERCIAL MODEL	TRACTION	Weight	Factory Data	List Price
WORKMASTER 50	2WD	4,442 LB		\$28,973.00
WORKMASTER 50	MFD	5,059 LB		\$32,496.00
WORKMASTER 60	2WD	4,442 LB		\$30,312.00
WORKMASTER 60	MFD	5,059 LB		\$33,835.00
WORKMASTER 70	2WD	4,442 LB		\$32,615.00
WORKMASTER 70	MFD	5,059 LB		\$36,138.00

**WORKMASTER 50 / 60 / 70  
US PRICE LIST**

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### FAST PICK CONFIGURATION

#### SD\_T9981 CONFIGURATION

	XT9981X	Less Fast Pick Config			No Charge
	X0274XX	WRKMSTR 60 Fast Pick <b>FAST PICK PKG PRICE = 2% SAVINGS OVER ALA-CART ORDER</b> <b>Fast Pick WORKMASTER 60 ROPS</b> <b>Package Contains:</b> <b>WORKMASTER 60 (FWD, 8x8 w/Mechanical Suttle)</b> <b>- 337444 (Loader Ready)</b> <b>- R1 AG Tires</b> <b>- 8270601 (Front 9.5x24)</b> <b>- 8980280 (Rear 14.9x28)</b>  <b>Fast-Pick Implement Packages are available.</b> <b>Consider ordering the following with your WORKMASTER 60:</b> <b>- Loader (611TL SSL/NSL Fast-Pick for Loader Ready)</b>			(\$678.00)

### TIRES AND WHEELS

#### FRONT AND REAR WHEELS AND TIRES

#### SD\_T4940 FRONT WHEELS AND TIRES

2wd					
	8199101	Front Shipping Wheels-2wd <b>Less tire option. Front shipping wheels for all 2WD models</b> <b>Order with 8399905</b>			(\$325.00)
	8299905	Front Shipping Wheels-4WD <b>Less tire option. Front shipping wheels for all 4WD models</b> <b>Order with 8399905</b>			(\$325.00)
	8812461	FR-R4-RYRE 11Lx15F3 - 2WD <b>F3 Industrial Front Tires for all 2WD models. Order with 8940301</b>			\$270.00
	8270600	Front Wheel - 7.5 x 16 - 2WD <b>(F2)</b>			No Charge
4wd					
	8812451	FR-R4 TYRE 12.4x20 <b>R4 Industrial Front Tires for all 4WD models. Order with 8940301</b>			\$372.00
	8812471	FR-R-3TYRE-9.5X24 - 4WD <b>R3 Turf Front tires of all 4WD models. Order with 8912481</b>			\$372.00

**WORKMASTER 50 / 60 / 70**  
**US PRICE LIST**

		8270605	Front Wheel - 8.3 X 24 - 4WD <b>Standard R1 Ag Tire for WM50 4wd</b>			No Charge
		8270601	Front Wheel - 9.5 X 24 - 4WD <b>Standard R1 Ag Tire for WM60 &amp; WM70 4wd</b>			No Charge

## SD T4950 REAR WHEELS AND TIRES

		8980270	Rear Wheel - 13.6x28 <b>Standard R1 Ag Tire for WM50 2wd or 4wd</b>			No Charge
		8980280	Rear Wheel - 14.9x28 <b>Standard R1 Ag Tire for WM60 &amp; WM70 2wd or 4wd</b>			No Charge
		8940301	Rear - R4 - 18.4 x 24 <b>R4 Industrial Rear tires for all 4wd models. Order with 8812451</b>			\$526.00
		8399905	Shipping Wheels-Rear <b>Less tire option. Rear shipping wheel for 2WD or 4WD</b>			(\$541.00)
		8912481	RR-R3-16.9x24 <b>R3 Turf Rear Tires for all 4WD models. Order with 8812471</b>			\$526.00

**FACTORY SUPPLIED OPTIONS**

## OPERATOR'S MANUAL

## SD T9800 OPERATORS MANUAL

		337952	French Manual			No Charge
--	--	--------	---------------	--	--	-----------

**WORKMASTER 55, 65, 75 CAB**  
**US PRICE LIST**

## Standard Equipment

Workmaster 55  
54 Gross Engine hp  
40 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

Workmaster 65  
64 Gross Engine hp  
50 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

**REAR AXLE**

Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard

**4WD power shuttle:**

-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

**WORKMASTER 55, 65, 75 CAB**  
**US PRICE LIST**

## Standard Equipment

### ELECTRICAL:

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

### CAB LIGHTING:

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach

#### 555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach

**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$49,886.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$52,457.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$55,028.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**OPERATOR PLATFORM**

## SD\_T9200 OPERATOR STRUCTURE #1

		333606	CAB FIX SCREEN OPEN <b>Cab with openable high visibility panel</b>			\$375.00
--	--	--------	---	--	--	----------

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

		8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
		8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>			\$670.00

## REAR

## SD\_T4950 REAR WHEELS AND TIRES

		8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
		8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>			\$309.00



**WORKMASTER 55, 65, 75 CAB**  
**US PRICE LIST**
**HYDRAULICS**

## REAR REMOTES

## SD T8270 REAR REMOTES

		335640	3 REMOTE VALVE 3 rear remote valves  Float, Detent and kickout on 2nd and 3rd remotes			\$803.00
--	--	--------	--	--	--	----------

**LOADER**

## LOADER

## SD T8110 LOADER BRACKETS

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00
		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST****3-POINT HITCH**

## REAR 3 POINT HITCH

## SD T8200 HITCH

		332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>			\$455.00
--	--	--------	---	--	--	----------

**WEIGHTS**

## REAR

## SD T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>			\$611.00
--	--	--------	---	--	--	----------

**OPERATOR'S MANUALS**

## SD T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

## SD T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 75 ROPS  
US PRICE LIST**

## Standard Equipment

The Workmaster Utility tractors from New Holland are the perfect combination of basic value, comfort, and features with the visibility to ensure you are productive in all your chores.

**Key Features:**

Flat deck platform

**Value Utility Target Customers:**

**Lifestyler / Weekender**

**Who are they?**

Small land-owners, who are owner-operators engaged in farming as a lifestyle

Ergonomic right hand console

**Why do they buy?**

- Comfortable operator area
- Simple, easy to operate
- Low price tag

**Mixed Beef / Cow/Calf**

**Who are they?**

Owner-operator farmers engaged in mixed farming (haying or grain farming with a Beef or Cow/Calf herd) for income

Factory Installed Loader

**Why do they buy?**

- Comfortable operator area
- Low cost of ownership
- Good visibility

**Small Livestock**

**Who are they?**

Owner-operator farmers engaged in raising livestock herds for additional income

ROPS, 4WD, power shuttle configuration

**Why do they buy?**

- Comfortable operator area
- Low cost of ownership
- Reliability

**WORKMASTER 75 ROPS  
US PRICE LIST**

## Standard Equipment

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

**REAR AXLE**

Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard  
4WD power shuttle:  
-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**WORKMASTER 75 ROPS  
US PRICE LIST**

## Standard Equipment

### INSTRUMENTATION:

Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake  
Gauges for fuel level, engine temperature and tachometer  
Digital Readout for PTO speed, ground speed, battery & hours

### ROPS LIGHTING:

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### ROPS MODELS

2-Post Foldable ROPS with ISO-mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension, operator's presence sensor, retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 550LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45 deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach

#### 555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @ pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45 deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach

**WORKMASTER 75 ROPS  
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB		\$47,048.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**TIRES**

## FRONT

## SD T4940 FRONT WHEELS AND TIRES

		8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
		8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>			\$670.00

## REAR

## SD T4950 REAR WHEELS AND TIRES

		8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
		8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>			\$309.00

**HYDRAULICS**

## REAR REMOTES

## SD T8270 REAR REMOTES

		335640	3 REMOTE VALVE <b>3 rear remote valves</b>  <b>Float, Detent and kickout on 2nd and 3rd remotes</b>			\$803.00
--	--	--------	--	--	--	----------

**WORKMASTER 75 ROPS  
US PRICE LIST**
**LOADER**

## LOADER

## SD T8110 LOADER BRACKETS

		344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344743	LOADER-NSL-2F-EU-WGG <b>550LU</b> Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344738	LOADER-MSL.2F.SSLWGG <b>555LU</b> Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00
		344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

**3-POINT HITCH**

## REAR 3 POINT HITCH

## SD T8200 HITCH

		332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>			\$455.00
--	--	--------	---	--	--	----------



**WORKMASTER 75 ROPS  
US PRICE LIST**

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>			\$611.00
--	--	--------	---	--	--	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------





**WORKMASTER 55, 65, 75 SPECIAL ORDER  
US PRICE LIST**

## Standard Equipment

### Special Custom Order Options

Requires YSR, YRT or YGR order codes.

Please place an order in the system with the configuration as close as possible to your desired configuration and then contact Dealer Sales Support with the following information to get the order configuration changed:

1. Vehicle Number(s)
2. Order Code(s) desired for each vehicle number

The orders will then be sent to have the order configurations changed to include your desired order code(s).

## Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

### OPERATOR PLATFORM

#### SD T8520 INSTRUCTIONAL SEAT

		390865	Less Instructional Seat <b>Removes instructor seat option from Cab Models</b>  <b>Instructor seat CANNOT be installed as a Dealer Installed Accessory</b>			(\$536.00)
--	--	--------	--	--	--	------------



**WORKMASTER 55, 65, 75 SPECIAL ORDER  
US PRICE LIST**

**LOADER**

**LOADER**

**SD T8110 LOADER BRACKETS**

		391489	Less Loader Bracket <b>No Loader</b>  Removes mid mount valve, loader & bucket			(\$7,669.00)
--	--	--------	---	--	--	--------------

**WEIGHTS**

**FRONT**

**SD T2150 FRONT BALLAST**

		330183	FRONT WEIGHT 8X30KG Front weight carrier (42 lbs) + 8 front weights (66 lbs) = 572 lbs  <b>NOT COMPATIBLE with front loader</b>			\$1,050.00
--	--	--------	--	--	--	------------