

**POWERSTAR 75 STANDARD FAST PICK  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- 12x12 Transmission
- Hydraulic shuttle lever
- Full-size instructor seat
- Hi Visibility Panel
- Lift-O-Matic Plus
- Tier 4B EPA emissions compliant
- Factory Installed Loader

### DIESEL ENGINE

PowerStar 75  
74 Gross Engine hp  
65 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS

US EPA Tier 4B Emissions Compliant  
Bosch Fuel Injection Pump  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Air Cleaner: Dry Type with Safety Element  
Under Hood Muffler  
Vertical Exhaust  
Fuel Sediment Filter with Water Sensor  
23.8 gal Fuel Tank w/ Protection Shield  
Parking brake

### TRANSMISSION

Wet Clutch  
LH side steering column mounted shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
Forward Reverse Power Shuttle  
FWD - 25 mph (40 kph)  
Speed varies with tire selection

### AXLES

#### FWD FRONT AXLE

Electro-Hydraulic engagement standard  
Adjustable Tread Width from 60.8 in. to 76.6 in.  
Limited Slip Differential Lock  
Standard FAS Ready

#### REAR AXLE

Flange Type  
Adjustable Tread Width 52.2 in. to 76.0 in.  
Rear Differential Lock - FWD mechanically engaged.

### HYDRAULIC SYSTEM

Open Center System  
(2) Open Center Valves with detent  
2 Function mid mount valve and joystick  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.5 L)  
Steering Pump: 7.3 gpm (27.5 L)  
Total Flow: 19.8 gpm (75 L)

### PTO

540 rpm Hydraulic PTO  
(1-3/8 in. 6 splines)  
Fully Independent, wet clutch  
Hydraulic engagement  
Flip-up PTO Shaft Guard

**POWERSTAR 75 STANDARD FAST PICK  
US PRICE LIST**

## Standard Equipment

### HITCH

3-point Category II with flex lower links  
and telescoping stabilizers  
Lift-O-Matic Plus rear hitch control  
3664 lbs. Lift Capacity (SAE)  
Swinging Drawbar  
Mechanical Draft Control  
Upper Link Draft Sensing  
3-Point Hitch Ground Control

### STEERING/BRAKES

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

### INSTRUMENTATION

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake, digital  
speed readout, gauges for fuel level,  
engine temperature, tachometer and  
hour meter

### ELECTRICAL

(1) 800 cca Heavy-duty Battery  
Alternator: 120 amp  
7-pin Outlet for trailer/implement lighting  
and signals  
4-pin Power Outlet (30 amp)  
8 amp single pole  
2 Auxiliary power sockets  
(cigarette lighter)

### LIGHTING

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE

ROPS protected, flat deck platform with  
heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper and washer,  
two doors with locks, two external  
mirrors, openable side windows,  
hinged rear window (fully opens)  
High Visibility Panel  
Steering Wheel - adjustable tilt  
Seat - Cloth covered with air  
suspension and 10 degrees of swivel,  
operator's presence sensor, retractable  
seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS

Pivoting Engine Hood  
SMV Emblem  
Rear wheel weights  
Toolbox

### WARRANTY

New Holland Standard Warranty Applies

**POWERSTAR 75 STANDARD FAST PICK  
US PRICE LIST**

## **Standard Equipment**

**LOADER:**

**655TL/710LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

**Lift Capacity**

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer style bucket attach

**655TL/715LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

**Lift Capacity**

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

**POWERSTAR 75 STANDARD FAST PICK  
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price
POWERSTAR 75	Cab	75 HP	7,996 LB		\$69,012.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**PACKAGE SELECTION**

## SD\_T9980 PACKAGING

		X99803X	STANDARD PACKAGING <b>Standard Package and Pricing Includes:</b> 84 inch bucket 4 x 110 lb Rear Wheel Weights  <b>Requires one selection for each of the following:</b> <b>Mid mount valve and joystick:</b> 2 Function mid mount valve and joystick or 2 Function mid mount valve and joystick + 3rd function diverter <b>Loader:</b> 655TL loader (select one)			(\$1,703.00)
--	--	---------	--	--	--	--------------

**HYDRAULICS**

## MID-MOUNT

## SD\_T8280 MID-MOUNT VALVES

		762166	MID+JOY+3FNCTN+NEW 2 function mid-mount valve and joystick.			No Charge
		762167	MID+JOY+3FNC+DIV+NEW 2 function mid-mount valve and joystick with 3rd function diverter. Requires a 655TL Loader. Bucket with Grapple NOT AVAILABLE as Factory Installed.			\$750.00



**POWERSTAR 75 STANDARD FAST PICK  
US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA <b>655TL/710LU</b> <b>Non Self Leveling with Skid Steer Attachment</b>			No Charge
		336734	Mech Self Leveling Ldr +SSQA <b>655TL/715LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b>			\$1,119.00

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS			No Charge
		334257	USA Spanish Configuration			No Charge

**POWERSTAR 75 A LA CARTE  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- 12x12 Transmission
- Mechanical or hydraulic shuttle lever
- Full-size instructor seat option
- Hi Visibility Panel Option
- Tier 4B EPA emissions compliant
- Factory Installed Loader

### DIESEL ENGINE

PowerStar 75  
74 Gross Engine hp  
65 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS

US EPA Tier 4B Emissions Compliant  
Bosch Fuel Injection Pump  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Air Cleaner: Dry Type with Safety Element  
Under Hood Muffler  
Vertical Exhaust  
Fuel Sediment Filter with Water Sensor  
23.8 gal Fuel Tank w/ Protection Shield  
Parking brake

### TRANSMISSION

Wet Clutch  
LH side steering column mounted shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
Forward Reverse Power Shuttle  
FWD - 25 mph (40 kph)  
Speed varies with tire selection

### AXLES

2WD HD FRONT AXLE - PowerStar 75  
Inverted U-section type  
Adjustable Tread Width from 57.0 in. to 79.7 in.

### FWD FRONT AXLE

Electro-Hydraulic engagement standard  
Adjustable Tread Width from 60.8 in. to 76.6 in.  
Limited Slip Differential Lock

### REAR AXLE

Flange Type  
Adjustable Tread Width 52.2 in. to 76.0 in.  
Rear Differential Lock - 2WD and FWD mechanically engaged.

### HYDRAULIC SYSTEM

Open Center System  
(2) Open Center Valves with detent  
2 Function mid mount valve and joystick  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.5 L)  
Steering Pump: 7.3 gpm (27.5 L)  
Total Flow: 19.8 gpm (75 L)

### PTO

540 rpm Mechanical PTO  
(1-3/8 in. 6 splines)  
Fully Independent, wet clutch  
Hydraulic Engagement  
Flip-up PTO Shaft Guard

**POWERSTAR 75 A LA CARTE  
US PRICE LIST**

## Standard Equipment

### HITCH

3-point Category II with flex lower links  
and telescoping stabilizers  
3664 lbs. Lift Capacity (SAE)  
Lift-O-Matic Plus  
3-Point Hitch Ground Control  
Swinging Drawbar  
Mechanical Draft Control  
Upper Link Draft Sensing

### STEERING/BRAKES

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

### INSTRUMENTATION

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake, digital  
speed readout  
Gauges for fuel level, engine  
temperature, tachometer and hour  
meter

### ELECTRICAL

(1) 800 cca Heavy-duty Battery  
Alternator: 120 amp  
7-pin Outlet for trailer/implement lighting  
and signals  
4-pin Power Outlet (30 amp)  
8 amp single pole  
Auxiliary power socket (cigarette lighter)

### LIGHTING

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE

ROPS protected, flat deck platform with  
heat and air conditioning, tinted  
windshield, retractable sun screen,  
front wiper and washer, two doors  
with locks, two external mirrors,  
openable side windows, hinged rear  
window (fully opens)  
High Visibility Pane  
Steering Wheel - adjustable tilt  
Seat - Cloth covered with air  
suspension and 10 degrees of swivel,  
operator's presence sensor, retractable  
seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS

Pivoting Engine Hood  
SMV Emblem  
Toolbox  
Toolbox on ROPS unit located in fenders

### WARRANTY

New Holland Standard Warranty Applies

**POWERSTAR 75 A LA CARTE  
US PRICE LIST**

## **Standard Equipment**

**LOADER:**

**655TL/710LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

**Lift Capacity**

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach

**655TL/715LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 127.2"

Dump Clearance: 94.4"

Digging Depth: 6.4"

**Lift Capacity**

Max Height @ 800mm: 3,179 LBS

59" high @ 800mm: 4,665 LBS

Breakout Force @ 800mm: 3,860 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style bucket attach



**POWERSTAR 75 A LA CARTE  
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	ENGINE POWER	Weight	Factory Data	List Price
POWERSTAR 75	Cab	75 HP	7,996 LB		\$69,012.00
Includes the following Equipment					
11.2R24 R1W (8232404) \$1,161.00					
16.9R30 R1W (8355404) \$2,530.00					

**Factory Supplied Options**

Order Code	Description	Weight	List Price
------------	-------------	--------	------------

**PACKAGE SELECTION**

## SD\_T9980 PACKAGING

	X99801X	Custom Configuration		No Charge
--	---------	----------------------	--	-----------

**POWER TRAIN**

## AXLES

## SD\_T4010 FRONT AXLE

	336858	2WD Standard Axle Heavy Duty <b>Requires 20 MPH (30 KPH)</b> <b>Compatible with 655TL</b> <b>Requires rear wheel weights (330470) ONLY when ordered with 655TL</b>  <b>PowerStar 75 ONLY</b>			(\$1,105.00)
	744580	4WD Electro Hyd Limited Slip <b>Electro-hydraulic 4WD engagement</b>			No Charge

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

2WD Front Tires					
	8125801	7.50-16 8 PLY HD			\$473.00
	8126601	9.5L15 4 RIB 8 PLY			\$619.00

**POWERSTAR 75 A LA CARTE  
US PRICE LIST**

4WD Radial Tires				
	8232404	11.2R24 R1W		\$1,161.00
4WD Specialty Tires				
	8290904	12.5/80-18 10PR R4		\$1,662.00
4WD Front Shipping Wheels				
	8299801	Non-Return Ship Wheels - 4WD		\$95.00

REAR				
------	--	--	--	--

## SD\_T4950 REAR WHEELS AND TIRES

Radial Tires				
	8355404	16.9R30 R1W <b>4WD Front Tire - 11.2R24 (8232404)</b> <b>2WD Front Tire - 9.5L15 4 Rib (8126601) or 7.5-16 (8125801)</b>		\$2,530.00
Specialty Tires				
	8391904	19.5L-24 10 PR R4 <b>4WD Front Tire - 12.5/80-18 (8290904)</b>		\$2,573.00
Rear Shipping Wheels				
	8399801	Non-Returnable Shipping Wheel		\$568.00

<b>HYDRAULICS</b>				
-------------------	--	--	--	--

MID-MOUNT				
-----------	--	--	--	--

## SD\_T8280 MID-MOUNT VALVES

	762166	MID+JOY+3FNCTN+NEW <b>2 function mid-mount valve and joystick.</b>		No Charge
	762167	MID+JOY+3FNC+DIV+NEW <b>2 function mid-mount valve and joystick with 3rd function diverter.</b> <b>Requires a 655TL Loader.</b> <b>Bucket with Grapple NOT AVAILABLE as Factory Installed.</b>		\$750.00

<b>LOADER</b>				
---------------	--	--	--	--

LOADER				
--------	--	--	--	--

## SD\_T8110 LOADER BRACKETS

Standard Duty Loader				
	336914	Non Self Leveling Ldr +SSQA <b>655TL/710LU</b> <b>Non Self Leveling with Skid Steer Attachment</b>		No Charge
	336734	Mech Self Leveling Ldr +SSQA <b>655TL/715LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b>		\$1,119.00
	743593	Less Front Loader		(\$6,120.00)



**POWERSTAR 75 A LA CARTE  
US PRICE LIST**

SD\_T8140 BUCKET

		XT8140X	Less Bucket			(\$952.00)
		336750	84" Bucket			No Charge

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights			\$844.00
			<b>Total weight - 661 lbs (300 kg)</b>			
		390215	Less Front Carrier and Weights			No Charge

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights			\$645.00
		XT4961X	Standard less rear ballast			No Charge

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS			No Charge
		334257	USA Spanish Configuration			No Charge

**POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed NSL SSL Loader

#### PowerStar 90

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 100

99 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 110

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 120

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

Tier 4B Emissions Compliant:  
(SCR + CEGR)

Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Constant Engine RPM  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBlue DEF Tank  
Parking brake

### TRANSMISSION:

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
19 mph (30 kph)  
Speed varies with tire selection

### STEERING/BRAKES:

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

### AXLES:

FRONT - 4WD  
Limited Slip  
- PowerStar 90, 100 & 110:  
Electrohydraulic FWD Engagement  
Adjustable Tread Width from  
56.6 in to 76.6 in.  
- PowerStar 120:  
Heavy Duty Electrohydraulic FWD Engagement  
Adjustable Tread Width from  
56.6 in. to 76.6 in.

**POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST**

## Standard Equipment

**AXLES Continued:**
**REAR**

- PowerStar 90, 100 & 110:
  - Flange Type
  - Adjustable Tread Width 55.5 in to 76.2 in.
- PowerStar 120:
  - Heavy Duty Flange Type
  - Adjustable Tread Width 55.5 in. to 76.2 in.
- 4 x 110 lb Rear Wheel Weights

**HYDRAULIC SYSTEM:**

## Open Center System

## Dual Gear Pumps

- Implement Pump: 16.9 gpm (63.9 L)
- Steering Pump: 9.7 gpm (37.0 L)
- Total Flow: 26.6 gpm (100.8 L)
- (2) Open Center Remote Valves with detent
- 2 Function Mid Mount Valve and Joystick

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

- Fully Independent
- Flip-up PTO Shaft Guard
- PowerStar 90, 100 & 110:
  - 540 rpm Hydraulic
- PowerStar 120:
  - 540/1000 rpm Hydraulic
  - Electronic engagement
  - Wet clutch
- 1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

- Right hand console mounted lever control
- Mechanical Draft Control
- Rear 3 Point Hitch Control
- 5,620 Pounds Lift Capacity
- Category II Ends
- Telescopic Stabilizers
- Flexible Lower Link Ends

**ELECTRICAL:**

- (1) 800 cca Heavy-Duty Battery - Cab
- 120 amp Alternator
- 7-pin Outlet for trailer/implement lighting and signals
- 3-pin Power Outlet (30 amp)
- Single Pin (8 amp) Accessory Power outlet
- 12V power socket

**INSTRUMENTATION:**

- Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, digital speed readout
- Gauges for fuel level, engine temperature, tachometer and hour meter

**LIGHTING:**

- Front: (2) Halogen Headlights and (2) cab mounted worklights
- Rear: (2) cab mounted worklights
- Turn Signals/Flashers/Rear Lights

**OPERATOR PROTECTIVE STRUCTURE:**
**CAB MODELS**

- ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front and rear wiper and washer, two doors with locks, two external mirrors, openable side windows, hinged rear window (opens completely)
- Steering Wheel - adjustable tilt
- Seat - Cloth covered with air suspension and 10 degrees of swivel, operator's presence sensor, retractable seat belt and arm rests
- Instructor Seat
- Suspended pedals
- Radio, speakers, and antenna



**POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST**

**Standard Equipment**

MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

655TL/710LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 126"

Dump Clearance: 93.6"

Digging Depth: 8.2"

Lift Capacity

Max Height @ 800mm: 2,478 LBS

59" high @ 800mm: 3,080 LBS

Breakout Force @ 800mm: 3,739 LBS

Reach @ Max Lift Height: 39.5"

Reach @ Ground Level: 90.7"

Bucket Rollback Angle: 45 degrees

Bucket Dump Angle: 60 degrees

Skid Steer Loader bucket attach



**POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	List Price
POWERSTAR 90	Cab	8,157 LB	\$75,065.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 100	Cab	10,031 LB	\$77,525.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 110	Cab	8,157 LB	\$80,196.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 120	Cab	8,158 LB	\$84,157.00
Includes the following Equipment			
4WD+EH Engage+Limited Slip (744581) \$277.00			
Heavy Duty Rear Axle (333411) \$665.00			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
540/1000 RPM PTO (743594) \$560.00			



POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD\_T9980 PACKAGING

	759310	UTILITY PACKAGE <b>UTILITY Package and Pricing Includes:</b> UTILITY package discount 12x12 Power shuttle transmission Deluxe cab with instructor seat 25 mph (40 kph) transmission speed 2 Function mid mount valve and joystick 655TL Non Self Leveling loader with SSL attachment 84" Bucket Rear 3 point hitch ground control  Allows for choice of the following tires: 18.4-30 Rear with 12.4R24 Front R1 Bias ply OR 18.4-34 Rear with 14.9R24 Front R1 Bias ply Radial			\$4,207.00
--	--------	---	--	--	------------

POWER TRAIN

AXLES

SD\_T4010 FRONT AXLE

	744581	4WD+EH Engage+Limited Slip+HD <b>Heavy-Duty Limited Slip</b> Base equipment on PowerStar 120 Requires Heavy-Duty rear axle (333411)			\$277.00
--	--------	--	--	--	----------

SD\_T4810 REAR AXLE

	333411	Heavy Duty Rear Axle <b>Heavy-Duty Rear Axle</b> Base Equipment on PowerStar 120 Required for 34 & 38 inch rear tires <b>NOT compatible with Standard-Duty 4WD</b> front axles (743559 or 744580) <b>NOT compatible with 30 inch or smaller rear tires</b> on PowerStar 90, 100 or 110			\$665.00
--	--------	---	--	--	----------



**POWERSTAR 90-120 PS UTILITY FAST PICK  
US PRICE LIST**

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

## 4WD Bias Front Tires

		8235601	12.4-24 8PR			\$1,075.00
		8240604	14.9-24 8PR R1			\$1,622.00

## REAR

## SD\_T4950 REAR WHEELS AND TIRES

## Bias Rear Tires

		8363801	18.4-30 12PR R1 FLAN <b>4WD Front Tire - 12.4-24 (8235601)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$2,609.00
		8365501	18.4-34 10PR <b>4WD Front Tire - 14.9-24 (8240604)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$2,875.00

**PTO**

## REAR PTO

## SD\_T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

**WEIGHTS**

## REAR

## SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Total weight - 440 lbs (200 kg)</b> <b>NOT compatible with 24" rear tires option</b> <b>Required with 2WD HD front axle</b>			\$639.00
--	--	--------	---	--	--	----------

**OPERATOR'S MANUALS**

## SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
		334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge

**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- High visibility panel for better view of loader when at full height
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader

#### PowerStar 90

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 100

98 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 110

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 120

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

#### Tier 4B Emissions Compliant:

(SCR + CEGR)

#### Electronic Injection Bosch

High-pressure Common Rail System

#### Electric Engine Shutoff

#### Hand and Foot Throttle Controls

#### Grid Heater Starting Aid

#### Dual Element Air Filter

#### Constant Engine RPM

#### Vertical Exhaust

#### 30.3 gal Fuel Tank with Guard

#### 2.8 gal AdBlue DEF Tank

#### Parking brake

### TRANSMISSION:

#### LH side steering column mounted

#### Power Shuttle

#### 12 Forward and 12 Reverse Speeds

#### (4) Synchronized Gears

#### (3) Non-synchronized Ranges

#### Forward Reverse Synchronized Shuttle

#### 25 mph (40 kph)

Speed varies with tire selection

### STEERING/BRAKES:

#### Hydrostatic Power Steering

#### Brakes-

Wet disk brakes

Hydraulically assisted

### AXLES:

#### FRONT - 4WD

#### Limited Slip

#### Heavy Duty Electrohydraulic

FWD Engagement

#### Adjustable Tread Width from

56.6 in. to 76.6 in.

### REAR

#### Heavy Duty Flange Type

#### Adjustable Tread Width 55.5 in.

to 76.2 in.

**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps  
    Implement Pump: 16.9 gpm (63.9 L)  
    Steering Pump: 9.7 gpm (37.0 L)  
    Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with  
    detent  
2 Function Mid Mount Valve and Joystick

### REAR DIFFERENTIAL LOCK:

Mechanically Engaged

### PTO:

Fully Independent  
Flip-up PTO Shaft Guard  
540/1000 rpm Hydraulic  
    -Electronic engagement  
    -Wet clutch  
1-3/8 in. 6 splines

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
    lever control  
Lift-O-Matic Plus single lever control  
3 Point Hitch Ground Control  
Mechanical Draft Control  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
    and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power  
outlet  
(2) - 12V power sockets

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
digital speed readout  
Gauges for fuel level, engine  
temperature, tachometer and hour  
meter

### CAB LIGHTING:

Front: (2) Halogen Headlights and  
    (2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper and washer, two  
doors with locks, two external mirrors,  
openable side windows, hinged rear  
window, high visibility panel  
Steering Wheel - adjustable tilt  
Seat - Cloth covered with air  
suspension and 10 degrees of swivel,  
operator's presence sensor, retractable  
seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

## Standard Equipment

**LOADER:**

**665TL/720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"  
Digging Depth: 7"  
Lift Capacity  
Max Height @ 800mm: 2,632 LBS  
59" high @ 800mm: 3,638 LBS  
Breakout Force @ 800mm: 4,455 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 91"  
Bucket Rollback Angle: 44 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer style Loader bucket attach

**665TL/725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"  
Dump Clearance: 102.2"  
Digging Depth: 6.4"  
Lift Capacity  
Max Height @ 800mm: 3,428 LBS  
59" high @ 800mm: 5,549 LBS  
Breakout Force @ 800mm: 5,661 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 93  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach



**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	List Price
POWERSTAR 90	Cab	8,157 LB	\$75,065.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 100	Cab	10,031 LB	\$77,525.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 110	Cab	8,157 LB	\$80,196.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 120	Cab	8,158 LB	\$84,157.00
Includes the following Equipment			
4WD+EH Engage+Limited Slip (744581) \$277.00			
Heavy Duty Rear Axle (333411) \$665.00			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
540/1000 RPM PTO (743594) \$560.00			



POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD\_T9980 PACKAGING

	X99803X	<b>STANDARD PACKAGING</b> <b>Standard Package and Pricing Includes:</b> 12x12 Power shuttle transmission Deluxe cab with instructor seat and hi-vis panel 25mph (40 kph) speed Heavy Duty 4WD front axle Heavy Duty rear axle 84" Bucket 540/1000 RPM PTO Rear 3 point hitch ground control Lift-O-Matic Plus 4 x 110 lb Rear wheel weights  <b>Requires one selection for each of the following:</b> <b>Mid mount valve and joystick:</b> 2 Function mid mount valve and joystick or 2 Function mid mount valve and joystick + 3rd function diverter <b>Loader:</b> 665TL loader (select one) <b>Tires:</b> 18.4R30 Rear with 12.4R24 Front R1W Radial OR 18.4R34 Rear with 14.9R24 Front R1W Radial			\$8,940.00
--	---------	--	--	--	------------

TIRES

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

4WD Radial Tires				
	8235404	12.4R24 R1W		\$1,436.00
4WD Radial Front Tires				
	8239404	14.9R24 R1W		\$2,162.00



**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

**REAR**

**SD\_T4950 REAR WHEELS AND TIRES**

**Radial Rear Tires**

		8357404	18.4R30 R1W <b>4WD Front Tire - 12.4R24 (8235404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$3,480.00
		8365404	18.4R34 R1W <b>4WD Front Tire - 14.9R24 (8239404)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$3,768.00

**HYDRAULICS**

**MID-MOUNT**

**SD\_T8280 MID-MOUNT VALVES**

		762166	MID+JOY+3FNCTN+NEW <b>2 function mid-mount valve and joystick</b>			No Charge
		762167	MID+JOY+3FNC+DIV+NEW <b>2 function mid-mount valve and joystick with 3rd function diverter</b> <b>Requires a Loader</b> <b>Bucket with Grapple NOT AVAILABLE as Factory Installed</b>			\$765.00

**LOADER**

**LOADER**

**SD\_T8110 LOADER BRACKETS**

**Heavy Duty Loader**

		336740	HD Non Self Leveling Ldr +SSQA <b>665TL/720LU</b> <b>Non Self Leveling with Skid Steer Style Attachment</b>			No Charge
		336744	HD Self Leveling Ldr +SSQA <b>665TL/725LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b>			\$1,147.00
		336746	HD Self Leveling Ldr +Euro <b>665TL/725LU</b> <b>Mechanical Self Leveling with Euro Style Attachment</b>			\$1,147.00

**OPERATOR'S MANUALS**

**SD\_T9840 COUNTRY CONFIGURATION**

		334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
--	--	--------	--	--	--	-----------



**POWERSTAR 90-120 PS STANDARD FAST PICK  
US PRICE LIST**

		334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge
--	--	--------	---	--	--	-----------



**POWERSTAR 90-120 PS KLASIK FAST PICK  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Ten repositionable vents for heating and air conditioning
- High visibility panel for better view of loader when at full height
- Full-size instructor seat
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

#### PowerStar 90

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 100

98 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 110

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 120

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

#### Tier 4B Emissions Compliant:

(SCR + CEGR)

#### Electronic Injection Bosch

High-pressure Common Rail System

#### Electric Engine Shutoff

#### Hand and Foot Throttle Controls

#### Grid Heater Starting Aid

#### Dual Element Air Filter

#### Constant Engine RPM

#### Vertical Exhaust

#### 30.3 gal Fuel Tank with Guard

#### 2.8 gal AdBlue DEF Tank

#### Parking brake

### TRANSMISSION:

#### LH side steering column mounted

#### Power Shuttle

#### 12 Forward and 12 Reverse Speeds

#### (4) Synchronized Gears

#### (3) Non-synchronized Ranges

#### Forward Reverse Synchronized Shuttle

#### 25 ph (40 kph)

Speed varies with tire selection

### STEERING/BRAKES:

#### Hydrostatic Power Steering

#### Brakes-

Wet disk brakes

Hydraulically assisted

### AXLES:

#### FRONT - 4WD

#### Limited Slip

#### Heavy Duty Electrohydraulic

FWD Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

### REAR

#### Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

4 Wheel Weights (2 x 110lb per side)

**POWERSTAR 90-120 PS KLASIK FAST PICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with  
detent

### REAR DIFFERENTIAL LOCK:

Mechanically Engaged

### PTO:

Fully Independent

Flip-up PTO Shaft Guard

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control

Mechanical Draft Control

Rear 3 Point Hitch Control

Lift-O-Matic Plus

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting  
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power  
outlet

(2) - 12V power sockets

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
digital speed readout

Gauges for fuel level, engine  
temperature, tachometer and hour  
meter

### CAB LIGHTING:

Front: (2) Halogen Headlights and  
(2) cab mounted worklights

Rear: (2) cab mounted worklights

Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper and washer, two  
doors with locks, two external mirrors,  
openable side windows, hinged rear  
window, high visibility panel  
Steering Wheel - adjustable tilt  
Seat - Cloth covered with air  
suspension and 10 degrees of swivel,  
operator's presence sensor, retractable  
seat belt and arm rests

Instructor Seat

Suspended pedals

Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

**POWERSTAR 90-120 PS KLASSIC FAST PICK  
US PRICE LIST**

## **Standard Equipment**

**LOADER:**

**665TL/720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**POWERSTAR 90-120 PS KLASSIC FAST PICK  
 US PRICE LIST**
**Models**

COMMERCIAL MODEL	VERSION	Weight	List Price
POWERSTAR 90	Cab	8,157 LB	\$75,065.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 100	Cab	10,031 LB	\$77,525.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 110	Cab	8,157 LB	\$80,196.00
Includes the following Equipment			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
POWERSTAR 120	Cab	8,158 LB	\$84,157.00
Includes the following Equipment			
4WD+EH Engage+Limited Slip (744581) \$277.00			
Heavy Duty Rear Axle (333411) \$665.00			
12.4-24 8PR (8235601) \$1,075.00			
18.4-30 12PR R1 FLAN (8363801) \$2,609.00			
540/1000 RPM PTO (743594) \$560.00			

**POWERSTAR 90-120 PS KLASIK FAST PICK  
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**PACKAGE SELECTION**

## SD\_T9980 PACKAGING

	X99804X	<b>KLASSIC PACKAGING</b> <b>Klassic Package and Pricing Includes:</b> 12x12 Power shuttle transmission Deluxe cab with instructor seat and hi-vis panel 25mph (40 kph) speed Heavy Duty 4WD front axle Heavy Duty rear axle 2 Function mid mount valve and joystick 540/1000 RPM PTO Rear 3 point hitch ground control Lift-O-Matic Plus 4 x 110 lb Rear wheel weights  Allows for choice of the following tires: 18.4-30 Rear with 12.4R24 Front R1 Bias ply OR 16.4R34 Rear with 13.6R24 Front R1W Radial			(\$512.00)
--	---------	--	--	--	------------

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

4WD Bias Front Tires					
	8235601	12.4-24 8PR			\$1,075.00
4WD Radial Front Tires					
	8236404	13.6R24 R1W			\$1,757.00

## REAR

## SD\_T4950 REAR WHEELS AND TIRES

Bias Rear Tires					
	8363801	18.4-30 12PR R1 FLAN 4WD Front Tire - 12.4-24 (8235601) 2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)			\$2,609.00

**POWERSTAR 90-120 PS KLASSIC FAST PICK  
US PRICE LIST**

Radial Rear Tires					
		8302804	16.9R34 R1W <b>4WD Front Tire - 13.6R24 (8236404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>		\$2,505.00

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

Heavy Duty Loader					
		336740	HD Non Self Leveling Ldr +SSQA <b>665TL/720LU</b> <b>Non Self Leveling with Skid Steer Style Attachment</b>		\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro <b>665TL/720LU</b> <b>Non Self Leveling with Euro Style Attachment</b>		\$7,025.00
		743593	Less Front Loader		No Charge

SD\_T8140 BUCKET

		336750	84" Bucket		\$942.00
--	--	--------	------------	--	----------

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights <b>Total weight - 661 lbs (300 kg)</b>		\$819.00
		335215	8 WEIGHTS 40 KG - CA <b>Total weight - 837 lbs (380 kg)</b>		\$1,036.00

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS <b>French operator manual</b>		No Charge
		334257	USA Spanish Configuration <b>Spanish operator manual</b>		No Charge

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel option for better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat option
- Hydraulic shuttle lever
- Creeper transmission option
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

#### PowerStar 90

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 100

98 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 110

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 120

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

#### Tier 4B Emissions Compliant:

(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

### TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

19 mph (30 kph)

Speed varies with tire selection

### HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

## Standard Equipment

### STEERING/BRAKES:

Hydrostatic Power Steering

#### Brakes-

- Wet disk brakes
- Hydraulically assisted

### AXLES:

FRONT - 2WD (19 mph, 30 kph)

Inverted U-section type

Adjustable Tread Width from 57.0 in.  
to 79.7 in.

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:
  - Electrohydraulic FWD Engagement
  - Adjustable Tread Width from  
56.6 in. to 76.6 in.
- PowerStar 120:
  - Heavy Duty Electrohydraulic FWD Engagement
  - Adjustable Tread Width from  
56.6 in. to 76.6 in.

### REAR

- PowerStar 90, 100 & 110:
  - Flange Type
  - Adjustable Tread Width 55.5 in.  
to 76.2 in.
- PowerStar 120:
  - Heavy Duty Flange Type
  - Adjustable Tread Width 55.5 in.  
to 76.2 in.

### REAR DIFFERENTIAL LOCK:

Mechanically Engaged

### PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - Cab

120 amp Alternator

7-pin Outlet for trailer/implement lighting  
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power  
outlet

12V power socket

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
digital speed readout

Gauges for fuel level, engine  
temperature, tachometer and hour  
meter

### LIGHTING:

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper and washer, two  
doors with locks, two external mirrors,  
openable side windows, hinged rear  
window (opens completely)

Steering Wheel - adjustable tilt

Seat - Cloth covered with air

suspension and 10 degrees of swivel,  
operator's presence sensor, retractable  
seat belt and arm rests

Instructor seat

Suspended pedals

Radio, speakers, and antenna



**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

## Standard Equipment

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:**

**655TL/710LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 126"  
Dump Clearance: 93.6"  
Digging Depth: 8.2"  
Lift Capacity  
Max Height @ 800mm: 2,478 LBS  
59" high @ 800mm: 3,080 LBS  
Breakout Force @ 800mm: 3,739 LBS  
Reach @ Max Lift Height: 39.5"  
Reach @ Ground Level: 90.7"  
Bucket Rollback Angle: 45 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro Style Loader  
bucket attach

**655TL/715LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 125"  
Dump Clearance: 93"  
Digging Depth: 8"  
Lift Capacity  
Max Height @ 800mm: 3,179 LBS  
59" high @ 800mm: 4,665 LBS  
Breakout Force @ 800mm: 3,860 LBS  
Reach @ Max Lift Height: 39.4"  
Reach @ Ground Level: 90.5"  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**665TL/720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"  
Digging Depth: 7"  
Lift Capacity  
Max Height @ 800mm: 2,632 LBS  
59" high @ 800mm: 3,638 LBS  
Breakout Force @ 800mm: 4,455 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 91"  
Bucket Rollback Angle: 44 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**665TL/725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"  
Dump Clearance: 102.2"  
Digging Depth: 6.4"  
Lift Capacity  
Max Height @ 800mm: 3,428 LBS  
59" high @ 800mm: 5,549 LBS  
Breakout Force @ 800mm: 5,661 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 93  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**POWERSTAR 90-120 PS A LA CARTE CAB  
 US PRICE LIST**
**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
POWERSTAR 90	Cab	8,157 LB		\$75,065.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Cab	10,031 LB		\$77,525.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Cab	8,157 LB		\$80,196.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Cab	8,158 LB		\$84,157.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**PACKAGE SELECTION**

## SD\_T9980 PACKAGING

	X99801X	Custom Configuration			No Charge
--	---------	----------------------	--	--	-----------

**OPERATOR PLATFORM**

## SD\_T9200 OPERATOR STRUCTURE #1

Cab					
	744588	Deluxe Cab Includes instructor seat, rear wiper and washer, radio & internal mirror			No Charge
	334183	Deluxe Cab w/HiVis Panel Includes high visibility panel, instructor seat, rear wiper and washer, radio & internal mirror			\$557.00

**POWER TRAIN**

## TRANSMISSION

## SD\_T2800 SPEED

	759059	40KPH - REAL ALL TYR 25 MPH (40 KPH) Transmission for 4WD			\$264.00
--	--------	--	--	--	----------

## AXLES

## SD\_T4010 FRONT AXLE

	336858	2WD Standard Axle Heavy Duty Requires 20 MPH (30 KPH) Compatible with 655TL Requires rear wheel weights (330470) ONLY when ordered with 655TL NOT compatible with 665TL			(\$1,105.00)
	744581	4WD+EH Engage+Limited Slip+HD Heavy-Duty Limited Slip Base equipment on PowerStar 120 Requires Heavy-Duty rear axle (333411)			\$277.00

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

## SD\_T4810 REAR AXLE

		333411	Heavy Duty Rear Axle <b>Heavy-Duty Rear Axle</b> <b>Base Equipment on PowerStar 120</b> <b>Required for 34 &amp; 38 inch rear tires</b> <b>NOT compatible with Standard-Duty 4WD</b> <b>front axles (743559 or 744580)</b> <b>NOT compatible with 30 inch or smaller rear tires</b> <b>on PowerStar 90, 100 or 110</b>			\$665.00
--	--	--------	---	--	--	----------

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

2WD Front Tires						
		8126601	9.5L15 4 RIB 8 PLY			\$641.00
		8125801	7.50-16 8 PLY HD			\$489.00
		8125901	10.00-16 8 PLY HD			\$914.00
4WD Bias Front Tires						
		8235601	12.4-24 8PR			\$1,075.00
		8236501	13.6-24 8PR R1 FLANG			\$1,317.00
		8240604	14.9-24 8PR R1			\$1,622.00
4WD Radial Tires						
		8235404	12.4R24 R1W			\$1,436.00
4WD Radial Front Tires						
		8236404	13.6R24 R1W			\$1,757.00
		8239404	14.9R24 R1W			\$2,162.00
4WD Specialty Front Tires						
		8290904	12.5/80-18 10PR R4			\$1,717.00
		8247404	11.2R28 R1W			\$1,484.00
		8873402	360/80R20 TRI 2 HD <b>Municipal tread</b>			\$1,956.00

## REAR

## SD\_T4950 REAR WHEELS AND TIRES

Bias Rear Tires						
		8363801	18.4-30 12PR R1 FLAN <b>4WD Front Tire - 12.4-24 (8235601)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$2,609.00
		8364604	16.9-34 8PR R1 <b>4WD Front Tire - 13.6-24 (8236501)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$1,878.00

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

		8365501	18.4-34 10PR <b>4WD Front Tire - 14.9-24 (8240604)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$2,875.00
Radial Rear Tires						
		8357404	18.4R30 R1W <b>4WD Front Tire - 12.4R24 (8235404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$3,480.00
		8302804	16.9R34 R1W <b>4WD Front Tire - 13.6R24 (8236404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$2,505.00
		8365404	18.4R34 R1W <b>4WD Front Tire - 14.9R24 (8239404)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$3,768.00
Specialty Rear Tires						
		8391904	19.5L-24 10 PR R4 <b>4WD Front Tire - 12.5/80-18 (8290904)</b>			\$2,658.00
		8372404	13.6R38 R1W 8372404 <b>4WD Front Tire - 11.2R28 (8247404)</b> <b>2WD Front Tire - 7.50-16 (8125801)</b>			\$2,338.00
		8906401	440/80 R30 <b>Municipal tread</b> <b>4WD Front Tire - 360/80R20 (8873402)</b>			\$3,644.00

**HYDRAULICS**

MID-MOUNT

SD\_T8280 MID-MOUNT VALVES

		762166	MID+JOY+3FNCTN+NEW <b>2 function mid-mount valve and joystick</b>			\$1,484.00
		762167	MID+JOY+3FNC+DIV+NEW <b>2 function mid-mount valve and joystick with 3rd function diverter</b> <b>Requires a Loader</b> <b>Bucket with Grapple NOT AVAILABLE as Factory Installed</b>			\$2,227.00

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA <b>655TL/710LU</b> <b>Non Self Leveling with Skid Steer Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$6,062.00
--	--	--------	---	--	--	------------

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

		336732	Non Self Leveling Ldr +Euro <b>655TL/710LU</b> <b>Non Self Leveling with Euro Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$6,062.00
		336734	Mech Self Leveling Ldr +SSQA <b>655TL/715LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$7,170.00
		336736	Mech Self Leveling Ldr +Euro <b>655TL/715LU</b> <b>Mechanical Self Leveling with Euro Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$7,170.00
Heavy Duty Loader						
		336740	HD Non Self Leveling Ldr +SSQA <b>665TL/720LU</b> <b>Non Self Leveling with Skid Steer Style Attachment</b>			\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro <b>665TL/720LU</b> <b>Non Self Leveling with Euro Style Attachment</b>			\$7,025.00
		336744	HD Self Leveling Ldr +SSQA <b>665TL/725LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b>			\$8,138.00
		336746	HD Self Leveling Ldr +Euro <b>665TL/725LU</b> <b>Mechanical Self Leveling with Euro Style Attachment</b>			\$8,138.00

## SD\_T8140 BUCKET

		336750	84" Bucket			\$942.00
--	--	--------	------------	--	--	----------

**PTO**

## REAR PTO

## SD\_T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

**HITCH**

## REAR 3 POINT HITCH

## SD\_T8130 3 POINT HITCH CONTROL

		332035	Mech 3 Pt Hitch Ground Control			\$261.00
--	--	--------	--------------------------------	--	--	----------

## SD\_T8200 HITCH

		743595	Lift-O-Matic Plus <b>Lift-O-Matic Plus</b>			\$265.00
--	--	--------	---	--	--	----------

**POWERSTAR 90-120 PS A LA CARTE CAB  
US PRICE LIST**

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights <b>Total weight - 661 lbs (300 kg)</b>			\$819.00
		335215	8 WEIGHTS 40 KG - CA <b>Total weight - 837 lbs (380 kg)</b>			\$1,036.00

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Total weight - 440 lbs (200 kg)</b> <b>NOT compatible with 24" rear tires option</b> <b>Required with 2WD HD front axle</b>			\$639.00
--	--	--------	---	--	--	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
		334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

## Standard Equipment

### KEY SELLING POINTS:

- CommandArc™ ergonomically places most frequently used controls to operator's right
- Hydraulic shuttle lever
- 3.4L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B EPA emissions compliant with Selective Catalytic Reduction (SCR) & Cooled Exhaust Gas Recirculation (CEGR)
- Factory Installed Loader available

#### PowerStar 90

86 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 100

98 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 110

107 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

#### PowerStar 120

117 Gross Engine hp  
100 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

### ALL MODELS:

#### Tier 4B Emissions Compliant:

(SCR + CEGR)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Dual Element Air Filter

Constant Engine RPM

Vertical Exhaust

30.3 gal Fuel Tank with Guard

2.8 gal AdBlue DEF Tank

Parking brake

### TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

Forward Reverse Synchronized Shuttle

19 mph (30 kph)

Speed varies with tire selection

### HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 16.9 gpm (63.9 L)

Steering Pump: 9.7 gpm (37.0 L)

Total Flow: 26.6 gpm (100.8 L)

(2) Open Center Remote Valves with detent

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control

Mechanical Draft Control

5,620 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends



**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

## Standard Equipment

### STEERING/BRAKES:

Hydrostatic Power Steering

#### Brakes-

Wet disk brakes

Hydraulically assisted

### AXLES:

FRONT - 2WD (19 mph, 30 kph)

Inverted U-section type

Adjustable Tread Width from 57.0 in.

to 79.7 in.

FRONT - 4WD

Limited Slip

- PowerStar 90, 100 & 110:

Electrohydraulic FWD Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

- PowerStar 120:

Heavy Duty Electrohydraulic FWD

Engagement

Adjustable Tread Width from

56.6 in. to 76.6 in.

### REAR

- PowerStar 90, 100 & 110:

Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

- PowerStar 120:

Heavy Duty Flange Type

Adjustable Tread Width 55.5 in.

to 76.2 in.

### REAR DIFFERENTIAL LOCK:

Mechanically Engaged

### PTO:

Fully Independent

Flip-up PTO Shaft Guard

PowerStar 90, 100 & 110:

540 rpm Hydraulic

PowerStar 120:

540/1000 rpm Hydraulic

-Electronic engagement

-Wet clutch

1-3/8 in. 6 splines

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery - ROPS

120 amp Alternator

7-pin Outlet for trailer/implement lighting  
and signals

3-pin Power Outlet (30 amp)

Single Pin (8 amp) Accessory Power  
outlet

12V power socket

### INSTRUMENTATION:

Analog Instrumentation with warning

lights for air cleaner service,

alternator, oil pressure, fuel

sediment/water sensor, PTO

engagement, head light high beam,

low fuel and parking brake,

digital speed readout

Gauges for fuel level, engine temp,

tachometer and hour meter

### LIGHTING:

ROPS

Front: (2) Halogen Headlights

Rear: (1) ROPS mounted worklight

Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-

mounted flat deck platform

Steering Wheel - adjustable tilt

Seat - Vinyl covered with mechanical

suspension, operator's presence

sensor, retractable seat belts and

arm rests

Suspended pedals

Locking brake pedals

### MISCELLANEOUS:

Pivoting Engine Hood

SMV Emblem

Toolbox

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

## Standard Equipment

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:**
**LOADER:**
**655TL/710LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 126"  
Dump Clearance: 93.6"  
Digging Depth: 8.2"  
Lift Capacity  
Max Height @ 800mm: 2,478 LBS  
59" high @ 800mm: 3,080 LBS  
Breakout Force @ 800mm: 3,739 LBS  
Reach @ Max Lift Height: 39.5"  
Reach @ Ground Level: 90.7"  
Bucket Rollback Angle: 45 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro Style Loader  
bucket attach

**655TL/715LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 125"  
Dump Clearance: 93"  
Digging Depth: 8"  
Lift Capacity  
Max Height @ 800mm: 3,179 LBS  
59" high @ 800mm: 4,665 LBS  
Breakout Force @ 800mm: 3,860 LBS  
Reach @ Max Lift Height: 39.4"  
Reach @ Ground Level: 90.5"  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**665TL/720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"  
Digging Depth: 7"  
Lift Capacity  
Max Height @ 800mm: 2,632 LBS  
59" high @ 800mm: 3,638 LBS  
Breakout Force @ 800mm: 4,455 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 91"  
Bucket Rollback Angle: 44 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**665TL/725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"  
Dump Clearance: 102.2"  
Digging Depth: 6.4"  
Lift Capacity  
Max Height @ 800mm: 3,428 LBS  
59" high @ 800mm: 5,549 LBS  
Breakout Force @ 800mm: 5,661 LBS  
Reach @ Max Lift Height: 43"  
Reach @ Ground Level: 93"  
Bucket Rollback Angle: 40 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style Loader  
bucket attach

**POWERSTAR 90-120 PS A LA CARTE ROPS  
 US PRICE LIST**
**Models**

COMMERCIAL MODEL	VERSION	Weight		List Price
POWERSTAR 90	Rops	8,157 LB		\$64,161.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 100	Rops	8,157 LB		\$66,621.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 110	Rops	8,157 LB		\$69,292.00
Includes the following Equipment				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
POWERSTAR 120	Rops	8,157 LB		\$73,253.00
Includes the following Equipment				
4WD+EH Engage+Limited Slip (744581) \$277.00				
Heavy Duty Rear Axle (333411) \$665.00				
12.4-24 8PR (8235601) \$1,075.00				
18.4-30 12PR R1 FLAN (8363801) \$2,609.00				
540/1000 RPM PTO (743594) \$560.00				

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**PACKAGE SELECTION**

## SD\_T9980 PACKAGING

		X99801X	Custom Configuration			No Charge
--	--	---------	----------------------	--	--	-----------

**OPERATOR PLATFORM**

## SD\_T9200 OPERATOR STRUCTURE #1

ROPS						
		392315	Platform w/Foldable ROPS <b>Includes tilt column</b>			No Charge
		334190	Deluxe Platform w/FOPS <b>Includes tilt column, FOPS canopy, noise reduction kit and 12V power outlet</b>			\$1,661.00

**POWER TRAIN**

## TRANSMISSION

## SD\_T2800 SPEED

		759059	40KPH - REAL ALL TYR <b>25 MPH (40 KPH) Transmission for 4WD</b>			\$264.00
--	--	--------	---	--	--	----------

## AXLES

## SD\_T4010 FRONT AXLE

		336858	2WD Standard Axle Heavy Duty <b>Requires 20 MPH (30 KPH)</b> <b>Compatible with 655TL</b> <b>Requires rear wheel weights (330470) ONLY when ordered with 655TL</b> <b>NOT compatible with 665TL</b>			(\$1,105.00)
		744581	4WD+EH Engage+Limited Slip+HD <b>Heavy-Duty Limited Slip</b> <b>Base equipment on PowerStar 120</b> <b>Requires Heavy-Duty rear axle (333411)</b>			\$277.00

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

## SD\_T4810 REAR AXLE

		333411	Heavy Duty Rear Axle <b>Heavy-Duty Rear Axle</b> <b>Base Equipment on PowerStar 120</b> <b>Required for 34 &amp; 38 inch rear tires</b> <b>NOT compatible with Standard-Duty 4WD</b> <b>front axles (743559 or 744580)</b> <b>NOT compatible with 30 inch or smaller rear tires</b> <b>on PowerStar 90, 100 or 110</b>			\$665.00
--	--	--------	---	--	--	----------

**TIRES**

## FRONT

## SD\_T4940 FRONT WHEELS AND TIRES

2WD Front Tires						
		8126601	9.5L15 4 RIB 8 PLY			\$641.00
		8125801	7.50-16 8 PLY HD			\$489.00
		8125901	10.00-16 8 PLY HD			\$914.00
4WD Bias Front Tires						
		8235601	12.4-24 8PR			\$1,075.00
		8236501	13.6-24 8PR R1 FLANG			\$1,317.00
		8240604	14.9-24 8PR R1			\$1,622.00
4WD Radial Tires						
		8235404	12.4R24 R1W			\$1,436.00
4WD Radial Front Tires						
		8236404	13.6R24 R1W			\$1,757.00
		8239404	14.9R24 R1W			\$2,162.00
4WD Specialty Front Tires						
		8290904	12.5/80-18 10PR R4			\$1,717.00
		8247404	11.2R28 R1W			\$1,484.00
		8873402	360/80R20 TRI 2 HD <b>Municipal tread</b>			\$1,956.00

## REAR

## SD\_T4950 REAR WHEELS AND TIRES

Bias Rear Tires						
		8363801	18.4-30 12PR R1 FLAN <b>4WD Front Tire - 12.4-24 (8235601)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$2,609.00
		8364604	16.9-34 8PR R1 <b>4WD Front Tire - 13.6-24 (8236501)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$1,878.00

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

		8365501	18.4-34 10PR <b>4WD Front Tire - 14.9-24 (8240604)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$2,875.00
Radial Rear Tires						
		8357404	18.4R30 R1W <b>4WD Front Tire - 12.4R24 (8235404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$3,480.00
		8302804	16.9R34 R1W <b>4WD Front Tire - 13.6R24 (8236404)</b> <b>2WD Front Tire - 7.50-16 (8125801) or 10.00-16 (8125901)</b>			\$2,505.00
		8365404	18.4R34 R1W <b>4WD Front Tire - 14.9R24 (8239404)</b> <b>2WD Front Tire - 10.00-16 (8125901)</b>			\$3,768.00
Specialty Rear Tires						
		8391904	19.5L-24 10 PR R4 <b>4WD Front Tire - 12.5/80-18 (8290904)</b>			\$2,658.00
		8372404	13.6R38 R1W 8372404 <b>4WD Front Tire - 11.2R28 (8247404)</b> <b>2WD Front Tire - 7.50-16 (8125801)</b>			\$2,338.00
		8906401	440/80 R30 <b>Municipal tread</b> <b>4WD Front Tire - 360/80R20 (8873402)</b>			\$3,644.00

**HYDRAULICS**

MID-MOUNT

SD\_T8280 MID-MOUNT VALVES

		762166	MID+JOY+3FNCTN+NEW <b>2 function mid-mount valve and joystick</b>			\$1,484.00
		762167	MID+JOY+3FNC+DIV+NEW <b>2 function mid-mount valve and joystick with 3rd function diverter</b> <b>Requires a Loader</b> <b>Bucket with Grapple NOT AVAILABLE as Factory Installed</b>			\$2,227.00

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

Standard Duty Loader

		336914	Non Self Leveling Ldr +SSQA <b>655TL/710LU</b> <b>Non Self Leveling with Skid Steer Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$6,062.00
--	--	--------	---	--	--	------------

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

		336732	Non Self Leveling Ldr +Euro <b>655TL/710LU</b> <b>Non Self Leveling with Euro Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$6,062.00
		336734	Mech Self Leveling Ldr +SSQA <b>655TL/715LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$7,170.00
		336736	Mech Self Leveling Ldr +Euro <b>655TL/715LU</b> <b>Mechanical Self Leveling with Euro Style Attachment</b> <b>NOT compatible with 38" rear tires</b>			\$7,170.00
Heavy Duty Loader						
		336740	HD Non Self Leveling Ldr +SSQA <b>665TL/720LU</b> <b>Non Self Leveling with Skid Steer Style Attachment</b>			\$7,025.00
		336742	HD Non Self Leveling Ldr +Euro <b>665TL/720LU</b> <b>Non Self Leveling with Euro Style Attachment</b>			\$7,025.00
		336744	HD Self Leveling Ldr +SSQA <b>665TL/725LU</b> <b>Mechanical Self Leveling with Skid Steer Style Attachment</b>			\$8,138.00
		336746	HD Self Leveling Ldr +Euro <b>665TL/725LU</b> <b>Mechanical Self Leveling with Euro Style Attachment</b>			\$8,138.00

## SD\_T8140 BUCKET

		336750	84" Bucket			\$942.00
--	--	--------	------------	--	--	----------

**PTO**

## REAR PTO

## SD\_T8010 PTO

		743594	540/1000 RPM PTO			\$560.00
--	--	--------	------------------	--	--	----------

**HITCH**

## REAR 3 POINT HITCH

## SD\_T8130 3 POINT HITCH CONTROL

		332035	Mech 3 Pt Hitch Ground Control			\$261.00
--	--	--------	--------------------------------	--	--	----------

## SD\_T8200 HITCH

		743595	Lift-O-Matic Plus <b>Lift-O-Matic Plus</b>			\$265.00
--	--	--------	---	--	--	----------

**POWERSTAR 90-120 PS A LA CARTE ROPS  
US PRICE LIST**

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		333215	Front Carrier +6 88 lb Weights <b>Total weight - 661 lbs (300 kg)</b>			\$819.00
		335215	8 WEIGHTS 40 KG - CA <b>Total weight - 837 lbs (380 kg)</b>			\$1,036.00

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Total weight - 440 lbs (200 kg)</b> <b>NOT compatible with 24" rear tires option</b> <b>Required with 2WD HD front axle</b>			\$639.00
--	--	--------	---	--	--	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

		334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
		334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge