

**WORKMASTER 95-120 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines

**WORKMASTER 95-120 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 STANDARD CAB FAST PICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB		\$74,495.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB		\$77,395.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB		\$80,995.00



WORKMASTER 95-120 STANDARD CAB FAST PICK
US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD		No Charge
--	-----	-----	--	-----------

SD_VE VERSION

	CAB	Cab		\$14,630.00
--	-----	-----	--	-------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9911X	Standard Cab Fast Pick Standard Cab Fast Pick pricing includes: Cab with openable Black-Out panel 2 rear remotes 632LA NSL loader with SSL quick attach and 84" bucket Allows for choice of the following: Tires: 18.4-30 R1 rear with 12.4-24 R1 front OR 16.4-34 R1 rear with 13.6-24 R1 front PTO: 540 OR 540/1000 RPM Rear weights: 4 rear wheel weights OR NO rear wheel weights			(\$3,700.00)
--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag				
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires		No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires		\$220.00

**WORKMASTER 95-120 STANDARD CAB FAST PICK
US PRICE LIST****REAR****SD_T4950 REAR WHEELS AND TIRES****Rear tires - Ag**

		8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)

PTO**REAR PTO****SD_T8010 PTO**

		759271	540 RPM W CAP			No Charge
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS**REAR WHEEL WEIGHTS****SD_T4960 WHEEL WEIGHTS**

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
--	--	--------	--	--	--	----------

OPERATOR'S MANUALS**SD_T9805 OPERATOR MANUAL (SE**

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox
4 Rear Wheel Weights

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 DELUXE CAB FAST PICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB		\$74,495.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB		\$77,395.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB		\$80,995.00



WORKMASTER 95-120 DELUXE CAB FAST PICK
US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	CAB	Cab			\$14,630.00
--	-----	-----	--	--	-------------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9912X	Deluxe Cab Fast Pick Deluxe Cab Fast Pick pricing includes: Cab with openable Black-Out panel 3 rear remotes 632LA NSL loader with SSL quick attach and 84" bucket 4 rear wheel weights Allows for choice of the following: Tires: 18.4-30 R1 rear with 12.4-24 R1 front OR 16.4-34 R1 rear with 13.6-24 R1 front PTO: 540/540E OR 540/1000 RPM			(\$2,270.00)
--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00



**WORKMASTER 95-120 DELUXE CAB FAST PICK
US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
		8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)

PTO

REAR PTO

SD_T8010 PTO

		759272	540-540E RPM W CAP			\$455.00
		759273	540-1000 RPM W CAP			\$530.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB		\$74,495.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB		\$77,395.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB		\$80,995.00

**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	CAB	Cab			\$14,630.00
--	-----	-----	--	--	-------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

Cab

	762204	HVAC CAB 2 REMOTE PS Cab with TWO rear remotes includes: <ul style="list-style-type: none">- Blacked out vent panel- 2 rear view mirrors- Air suspension seat- Bluetooth radio- Rear wiper/wwasher- 12x12 powershuttle transmission			No Charge
	762205	HVAC CAB 3 REMOTE PS Cab with THREE rear remotes includes: <ul style="list-style-type: none">- Blacked out vent panel- 2 rear view mirrors- Air suspension seat- Bluetooth radio- Rear wiper/wwasher- 12x12 powershuttle transmission DELAYED OPTION WILL NOT BE AVAILABLE UNTIL MID 2020 AT THE EARLIEST			\$800.00

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag

	8220701	11.2 - 24 Requires 16.9-30 rear tires			(\$60.00)
--	---------	---	--	--	-----------



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

		8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
		8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00
4WD Front Tires - Ind						
		8230503	FRONT 12.5 - 18 Requires 19.5L-24 rear tires			\$700.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
		8930602	REAR 16.9 - 30 Requires 11.2-24 4WD front or 7.50-16 2WD front			\$300.00
		8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)
Rear tires - Ind						
		8930603	REAR 19.5 - 24 Requires 12.5/80-18 4WD front tires			\$625.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		345324	L/ LOADER FOR MMV Mid Mount Valve and Joystick ONLY.			(\$6,500.00)
		343422	LOADER READY 343422 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard			(\$1,480.00)
		762057	TL632 FULL NS762057 632TL Non self leveling loader with 84" SSL Bucket			No Charge

PTO

REAR PTO

SD_T8010 PTO

		759271	540 RPM W CAP			No Charge
		759272	540-540E RPM W CAP			\$455.00
		759273	540-1000 RPM W CAP			\$530.00



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

		342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			\$1,250.00
		342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			\$1,000.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
		759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires			\$1,260.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 STANDARD ROPS FASTPICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 STANDARD ROPS FASTPICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 STANDARD ROPS FASTPICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00



WORKMASTER 95-120 STANDARD ROPS FASTPICK
US PRICE LIST

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	ROPS	Rops			No Charge
--	------	------	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9913X	Standard ROPS Fast Pick ROPS Standard Fast Pick pricing includes: 2 rear remotes 632LA NSL loader with SSL quick attach and 84" bucket Allows for choice of the following: Tires: 18.4-30 R1 rear with 12.4-24 R1 front OR 16.4-34 R1 rear with 13.6-24 R1 front PTO: 540 OR 540/1000 RPM Rear weights: 4 rear wheel weights OR NO rear wheel weights			(\$3,700.00)
--	---------	--	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00



**WORKMASTER 95-120 STANDARD ROPS FASTPICK
US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
		8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)

PTO

REAR PTO

SD_T8010 PTO

		759271	540 RPM W CAP			No Charge
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
--	--	--------	--	--	--	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick
18.4X30 rear and 12.4X24 front tires

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in..

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox
4 Rear Wheel Weights

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear
OR
11.2-24 Front
16.9x30 Rear

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 DELUXE ROPS FAST PICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00

**WORKMASTER 95-120 DELUXE ROPS FAST PICK
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	ROPS	Rops			No Charge
--	------	------	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9914X	Deluxe ROPS Fast Pick Deluxe ROPS Fast Pick pricing includes: 3 rear remotes 632LA NSL loader with SSL quick attach and 84" bucket 4 rear wheel weights Allows for choice of the following: Tires: 18.4-30 R1 rear with 12.4-24 R1 front OR 16.4-34 R1 rear with 13.6-24 R1 front PTO: 540/540E OR 540/1000 RPM			(\$2,270.00)
--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge



**WORKMASTER 95-120 DELUXE ROPS FAST PICK
US PRICE LIST**

		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)
--	--	---------	--	--	--	------------

PTO

REAR PTO

SD_T8010 PTO

		759272	540-540E RPM W CAP			\$455.00
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

		342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			\$1,250.00
		342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			\$1,000.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 71.6 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS
2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear
OR
11.2-24 Front
16.9x30 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00

**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	ROPS	Rops			No Charge
--	------	------	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9917X	Low Profile All Purpose Fast P Low Profile All Purpose Fast Pick Allows for choice of the following: Tires: 16.9-30 R1 rear with 11.2-24 R1 front OR 19.5L27 R4 rear with 12.5-80/18 R4 front OR 500/60-22.5 R1 rear with 11.5/80-15.3 R1 front Rear Remotes: 2 or 3 remotes PTO: 540 OR 540/1000 RPM Rear weights: 4 rear wheel weights OR NO rear wheel weights Front weights: 8, 10 OR NO front weights Mid mount valve / loader: NO mid mount valve or loader OR Mid mount valve with NO brackets & NO Loader OR Complete loader ready (mid mount valve, hoses and brackets)			(\$3,700.00)
--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8220701	11.2 - 24 Requires 16.9-30 rear tires			(\$60.00)



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

		8811501	11.5/80-15.3 Requires 500/60-22.5 rear tires (ROPS ONLY)			\$700.00
4WD Front Tires - Ind						
		8230503	FRONT 12.5 - 18 Requires 19.5L-24 rear tires			\$700.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
		8930602	REAR 16.9 - 30 Requires 11.2-24 4WD front or 7.50-16 2WD front			\$300.00
		8310501	500/60-22.5 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)			\$625.00
Rear tires - Ind						
		8930603	REAR 19.5 - 24 Requires 12.5/80-18 4WD front tires			\$625.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

		762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
		762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2			\$800.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		343422	LOADER READY 343422 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard			(\$1,480.00)
		762057	TL632 FULL NS762057 632TL Non self leveling loader with 84" SSL Bucket			No Charge



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

PTO

REAR PTO

SD_T8010 PTO

		759271	540 RPM W CAP			No Charge
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

		342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			\$1,250.00
		342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			\$1,000.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
--	--	--------	--	--	--	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Engine Reversing Fan
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 68.5 in.

REAR AXLE

Flange Type
Tread Width: 64.8 in. to 72.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS
2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING
Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	ROPS	Rops			No Charge
--	------	------	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9915X	<p>Poultry NSL Loader Fast Pick</p> <p>Poultry NSL Loader Fast Pick pricing includes:</p> <p>Reversing engine fan</p> <p>632LA NSL loader with SSL quick attach and 84" bucket</p> <p>Allows for choice of the following:</p> <p>Tires:</p> <p>19.5L27 R4 rear with 12.5-80/18 R4 front OR</p> <p>500/60-22.5 R1 rear with 11.5/80-15.3 R1 front</p> <p>Rear Remotes:</p> <p>2 or 3 remotes</p> <p>PTO:</p> <p>540 OR 540/1000 RPM</p> <p>Rear weights:</p> <p>4 rear wheel weights OR NO rear wheel weights</p>			(\$550.00)
	XF9916X	<p>Poultry NO Loader Fast Pick</p> <p>Poultry NSL Loader Fast Pick pricing includes:</p> <p>Reversing engine fan</p> <p>Less loader and mid mount valve</p> <p>Allows for choice of the following:</p> <p>Tires:</p> <p>19.5L27 R4 rear with 12.5-80/18 R4 front OR</p> <p>500/60-22.5 R1 rear with 11.5/80-15.3 R1 front</p> <p>Rear Remotes:</p> <p>2 or 3 remotes</p> <p>PTO:</p> <p>540 OR 540/1000 RPM</p> <p>Rear weights:</p> <p>4 rear wheel weights OR NO rear wheel weights</p>			(\$8,530.00)

**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST****TIRES**

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag

		8811501	11.5/80-15.3 Requires 500/60-22.5 rear tires (ROPS ONLY)			\$700.00
--	--	---------	--	--	--	----------

4WD Front Tires - Ind

		8230503	FRONT 12.5 - 18 Requires 19.5L-24 rear tires			\$700.00
--	--	---------	--	--	--	----------

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag

		8310501	500/60-22.5 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)			\$625.00
--	--	---------	---	--	--	----------

Rear tires - Ind

		8930603	REAR 19.5 - 24 Requires 12.5/80-18 4WD front tires			\$625.00
--	--	---------	--	--	--	----------

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

		762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
		762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2			\$800.00

PTO

REAR PTO

SD_T8010 PTO

		759271	540 RPM W CAP			No Charge
		759273	540-1000 RPM W CAP			\$530.00



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

WEIGHTS

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
--	--	--------	--	--	--	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00

**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST****Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD			No Charge
--	-----	-----	--	--	-----------

SD_VE VERSION

	ROPS	Rops			No Charge
--	------	------	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	XF9918X	ROPS Mowing Fast Pick ROPS Mowing Fast Pick 3 rear remotes NO mid mount valve or loader Allows for choice of the following: Tires: 18.4-30 R1 rear with 12.4-24 R1 front OR 16.4-34 R1 rear with 13.6-24 R1 front PTO: 540 OR 540/1000 RPM Rear weights: 4, 8 OR NO rear wheel weights Front weights: 8, 10 OR NO front weights Mid mount valve / loader: NO mid mount valve or loader OR Mid mount valve with NO brackets & NO Loader OR Complete loader ready (mid mount valve, hoses and brackets)			(\$10,880.00)
--	---------	---	--	--	---------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00

**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST****REAR****SD_T4950 REAR WHEELS AND TIRES****Rear tires - Ag**

		8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
		8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)

LOADER**LOADER****SD_T8110 LOADER BRACKETS**

		345324	L/ LOADER FOR MMV Mid Mount Valve and Joystick ONLY.			\$1,480.00
		343422	LOADER READY 343422 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard			\$6,500.00

PTO**REAR PTO****SD_T8010 PTO**

		759271	540 RPM W CAP			No Charge
		759272	540-540E RPM W CAP			\$455.00
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS**FRONT WEIGHTS****SD_T2151 WEIGHT PACK**

		342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			\$1,250.00
		342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			\$1,000.00



**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
		759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires			\$1,260.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	7,451 LB		\$59,865.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB		\$62,765.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB		\$66,365.00



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_TR TRACTION

	4WD	MFD		No Charge
--	-----	-----	--	-----------

SD_VE VERSION

	ROPS	Rops		No Charge
--	------	------	--	-----------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag

	8220701	11.2 - 24 Requires 16.9-30 rear tires			(\$60.00)
	8230506	FRONT 12.4 - 24 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 Requires 16.9-34 rear tires			\$220.00
	8811501	11.5/80-15.3 Requires 500/60-22.5 rear tires (ROPS ONLY)			\$700.00

4WD Front Tires - Ind

	8230503	FRONT 12.5 - 18 Requires 19.5L-24 rear tires			\$700.00
--	---------	--	--	--	----------

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag

	8930602	REAR 16.9 - 30 Requires 11.2-24 4WD front or 7.50-16 2WD front			\$300.00
	8930605	REAR 18.4 - 30 Requires 12.4-24 4WD front or 10.0-16 2WD front			No Charge
	8930601	REAR 16.9 - 34 Requires 13.6-24 4WD front or 10.0-16 2WD front			(\$140.00)
	8310501	500/60-22.5 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)			\$625.00

Rear tires - Ind

	8930603	REAR 19.5 - 24 Requires 12.5/80-18 4WD front tires			\$625.00
--	---------	--	--	--	----------

**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST****HYDRAULICS**

REAR REMOTES

SD_T8270 REAR REMOTES

		762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
		762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2			\$800.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		345324	L/ LOADER FOR MMV Mid Mount Valve and Joystick ONLY.			(\$6,500.00)
		343422	LOADER READY 343422 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard			(\$1,480.00)
		762057	TL632 FULL NS762057 632TL Non self leveling loader with 84" SSL Bucket			No Charge

PTO

REAR PTO

SD_T8010 PTO

		759271	540 RPM W CAP			No Charge
		759272	540-540E RPM W CAP			\$455.00
		759273	540-1000 RPM W CAP			\$530.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

		342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs			\$1,250.00
--	--	--------	---	--	--	------------



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

		342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs			\$1,000.00
--	--	--------	---	--	--	------------

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

		762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires			\$630.00
		759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires			\$1,260.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

		342076	French (Canada)			No Charge
		342077	Spanish			No Charge

**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines

**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket

**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

	CAB	Cab		No Charge
--	-----	-----	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X0590XX	Standard Cab Fast Pick Standard Cab Fast Pick pricing includes: Cab with openable Black-Out panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights			(\$2,600.00)
--	---------	--	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
--	---------	--	--	--	-----------

**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST**

		8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00
--	--	---------	--	--	--	----------

REAR

SD_T4950 REAR WHEELS AND TIRES

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total			\$611.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

WORKMASTER 55-75 STD CAB H1VIS FAST PIC
US PRICE LIST

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines

**WORKMASTER 55-75 STD CAB HIVIS FAST PIC
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, high visibility
panel, front wiper and washer, rear
wiper and washer, two doors with
locks, two external mirrors, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket

**WORKMASTER 55-75 STD CAB HIVIS FAST PIC
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

	CAB	Cab			No Charge
--	-----	-----	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X0592XX	Standard Cab HiVis Fast Pick Standard Cab HiVis Fast Pick pricing includes: Cab with openable Clear HiVis panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights			(\$2,225.00)
--	---------	--	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
	8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00



**WORKMASTER 55-75 STD CAB HIVIS FAST PIC
US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total			\$611.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

	CAB	Cab		No Charge
--	-----	-----	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X0591XX	Deluxe Cab Fast Pick Deluxe Cab Fast Pick pricing includes: Cab with openable Black-Out panel 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket			(\$1,186.00)
--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
	8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00

**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST****REAR****SD_T4950 REAR WHEELS AND TIRES**

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

LOADER**LOADER****SD_T8110 LOADER BRACKETS**

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

OPERATOR'S MANUALS**SD_T9802 OPERATORS MANUAL**

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with
Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, high visibility
panel, front wiper and washer, rear
wiper and washer, two doors with
locks, two external mirrors, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket

**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

	CAB	Cab			No Charge
--	-----	-----	--	--	-----------

PACKAGE SELECTION

SD_T9980 PACKAGING

	X0593XX	Deluxe Cab HiVis Fast Pick Deluxe Cab HiVis Fast Pick pricing includes: Cab with openable Clear HiVis panel 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket			(\$811.00)
--	---------	---	--	--	------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
	8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00

**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST****REAR****SD_T4950 REAR WHEELS AND TIRES**

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

LOADER**LOADER****SD_T8110 LOADER BRACKETS**

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

OPERATOR'S MANUALS**SD_T9802 OPERATORS MANUAL**

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75
74 Gross Engine hp
60 PTO hp @ 2300 rpm
3 Cyl Turbocharged Engine
179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
21.6 gal Fuel Tank
2 function mid mount valve & joystick
16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 25 mph (40 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type
Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.7 L)
Steering Pump: 7.6 gpm (28.7 L)
Total Flow: 20.1 gpm (76.4 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:
Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
4WD power shuttle:
-540 RPM hydraulic wet clutch
-Hydraulic engagement
-Wet clutch
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends



**WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket

**WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB		\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

		ROPS	Rops				(\$7,980.00)
--	--	------	------	--	--	--	--------------

PACKAGE SELECTION

SD_T9980 PACKAGING

		X0588XX	Standard ROPS Fast Pick Standard ROPS Fast Pick pricing includes: 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights				(\$2,600.00)
--	--	---------	---	--	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

		8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)				No Charge
		8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)				\$670.00



WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST

REAR

SD_T4950 REAR WHEELS AND TIRES

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total			\$611.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

Total Flow: 20.1 gpm (76.4 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted

lever control

Mechanical Draft Control

3,500 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket

**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB		\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

		ROPS	Rops			(\$7,980.00)
--	--	------	------	--	--	--------------

PACKAGE SELECTION

SD_T9980 PACKAGING

		X0589XX	Deluxe ROPS Fast Pick Deluxe ROPS Fast Pick pricing includes: 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket			(\$1,186.00)
--	--	---------	---	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

		8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
		8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00

**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST****REAR****SD_T4950 REAR WHEELS AND TIRES**

		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

LOADER**LOADER****SD_T8110 LOADER BRACKETS**

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

OPERATOR'S MANUALS**SD_T9802 OPERATORS MANUAL**

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab & ROPS platform
- 12x12 power shuttle transmission
- Lift-O-Matic
- 1 Auxiliary lift ram (4,000 lbs)
- 8 Front weights
- 3 Rear remotes

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines

**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
4,000 Pounds Lift Capacity with
1 Auxiliary Lift Ram
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00
WORKMASTER 75 T4A	Rops	6,239 LB		\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

	CAB	Cab			No Charge
	ROPS	Rops			(\$7,980.00)

PACKAGE SELECTION

SD_T9980 PACKAGING

	X0596XX	West Coast Less Loader West Coast Less Loader Fast Pick pricing includes: 3 rear remotes Less loader and mid mount valve 8 front weights Auxiliary lift ram Cab Models: Cab with openable Black-Out panel Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR Front and rear shipping wheels Rear weights: 4 rear wheel weights OR NO rear wheel weights			(\$7,961.00)
--	---------	---	--	--	--------------



**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

		8299801	Non-Return Ship Wheels - 4WD			(\$763.00)
		8232304	11.2 x 24 6PR R1			No Charge
			Matching rear tires = 16.9-30 (8355304)			

REAR

SD_T4950 REAR WHEELS AND TIRES

		8399801	Non-Returnable Shipping Wheel			(\$1,477.00)
		8355304	16.9-30 6PR R1			No Charge
			Matching front tires = 11.2-24 (8232304)			

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights			\$611.00
			Two weights per side (110 lbs each) = 440 lbs total			

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with
Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)

Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB		\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB		\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB		\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

		CAB	Cab			No Charge
--	--	-----	-----	--	--	-----------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

		333606	CAB FIX SCREEN OPEN Cab with openable high visibility panel			\$375.00
--	--	--------	---	--	--	----------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

		8299801	Non-Return Ship Wheels - 4WD			(\$763.00)
		8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
		8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

		8399801	Non-Returnable Shipping Wheel			(\$1,477.00)
		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

		335413	2 Rem. Valve (1 S/D 2 rear remote valves Float, Detent and kickout on 2nd remote			No Charge
		335640	3 REMOTE VALVE 3 rear remote valves Float, Detent and kickout on 2nd and 3rd remotes			\$803.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00
--	--	--------	---	--	--	------------

3-POINT HITCH

REAR 3 POINT HITCH

SD_T8200 HITCH

		332785	MDC Hitch aux lift ram 1 Auxiliary lift ram = 4,000 lbs total lift capacity			\$455.00
--	--	--------	---	--	--	----------

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total			\$611.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------

**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System

Dual Gear Pumps

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

Total Flow: 20.1 gpm (76.4 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted

lever control

Mechanical Draft Control

3,500 Pounds Lift Capacity

Category II Ends

Telescopic Stabilizers

Flexible Lower Link Ends

**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket

**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST****Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB		\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

SD_VE VERSION

		ROPS	Rops			(\$7,980.00)
--	--	------	------	--	--	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

		8299801	Non-Return Ship Wheels - 4WD			(\$763.00)
		8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
		8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)			\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

		8399801	Non-Returnable Shipping Wheel			(\$1,477.00)
		8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
		8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)			\$309.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

		335413	2 Rem. Valve (1 S/D) 2 rear remote valves Float, Detent and kickout on 2nd remote			No Charge
--	--	--------	---	--	--	-----------



**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

		335640	3 REMOTE VALVE 3 rear remote valves Float, Detent and kickout on 2nd and 3rd remotes			\$803.00
--	--	--------	--	--	--	----------

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
		344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00
		344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			\$1,098.00

3-POINT HITCH

REAR 3 POINT HITCH

SD_T8200 HITCH

		332785	MDC Hitch aux lift ram 1 Auxiliary lift ram = 4,000 lbs total lift capacity			\$455.00
--	--	--------	---	--	--	----------



**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

WEIGHTS

REAR

SD_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total			\$611.00
--	--	--------	---	--	--	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 SPECIAL ORDER
US PRICE LIST**

Standard Equipment

Special Custom Order Options

Requires YSR, YRT or YGR order codes.

Please place an order in the system with the configuration as close as possible to your desired configuration and then contact Dealer Sales Support with the following information to get the order configuration changed:

1. Vehicle Number(s)
2. Order Code(s) desired for each vehicle number

The orders will then be sent to have the order configurations changed to include your desired order code(s).

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR PLATFORM

SD_T8520 INSTRUCTIONAL SEAT

		390865	Less Instructional Seat Removes instructor seat option from Cab Models			(\$536.00)
--	--	--------	--	--	--	------------



WORKMASTER 55, 65, 75 SPECIAL ORDER
US PRICE LIST

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		391489	Less Loader Bracket No Loader Removes mid mount valve, loader & bucket			(\$7,669.00)
--	--	--------	---	--	--	--------------

WEIGHTS

FRONT

SD_T2150 FRONT BALLAST

		330183	FRONT WEIGHT 8X30KG Front weight carrier (42 lbs) + 8 front weights (66 lbs) = 572 lbs NOT COMPATIBLE with front loader			\$1,050.00
--	--	--------	--	--	--	------------