



Current Date 03Jan2020

## 204L FOUR WHEEL DRIVE LOADER

## 204L Standard Equipment

## ENGINE:

Yanmar 4TNV98

61 SAE Net Horsepower (45 kW)

Isolation Mounted

Meets EPA Final Tier 4 and EU Stage IIIB

Emissions

Engine Coolant -34 Degree F

(-37 Degree C)

Air Intake Pre Heater

Coolant Recovery Tank

Belt Driven Cooling Fan

Spin-On Engine Oil and Fuel Filters

Oil-to-Water Engine Oil Cooler

Dual Safety Element Dry-Type

Air Cleaner with Dust

Evacuator Valve and

Muffler, Under Hood, with Angled exhaust Stack and Diffuser

Enclosed Safety Fan Guard (Conforms to SAE J1308)

## ELECTRICAL:

12 Volt System

80 Amp Sealed Alternator

(1) Battery

850 CCA, 80 Minutes

Rated Reserve Capacity

Master Electrical Disconnect Switch

Blade-Type Multi-Fused

Circuits battery load center bolt down main fuses

Sealed External Electrical Connections

Electrical Load Center In Operator Station

Positive Terminal Battery Cover

Lights (Conforms to SAE

Hydraulic Test Ports

## AXLES:

Heavy-Duty Outboard Planetary

Final Drives

Limited Slip Differential

45% Front Differential and 45% Rear Standard Differential

## BRAKES:

Service Brakes; Hydraulically

Actuated, Self-Adjusting internal Wet Disc Brake and Driveline Drum Brake

Park Brake; Automatic

Spring-Applied,

Hydraulic-Released

internal Wet Disc Brake

## STEERING:

Hydraulic Power Steer:

40 Degrees Articulation

## HYDRAULIC SYSTEM:

18 GPM (70 L/Min) Engine

Mounted Gear Pump - Open Center control valve

Combined

Hydrostatic/Hydraulic

Oil Reservoir Sight Glass

## OPERATOR'S STATION:

Modular Design ROPS/FOPS Canopy/Cab,

Isolation Mounted (Conforms

to SAE J1040, J231, ISO 3471, ISO 3449)

Steel Roof

Left Side Access

Slip-Resistant Steps and Ergonomically Located

Handholds (Conforms to SAE J185)

Tilt Steering Console (Cab option Only)

Steering Wheel with Spinner

Engine Coolant

Engine Air Filter

Temperature

Hydraulic Oil Temperature

Oil Temperature

Fuel Gauge (Fuel Gauge Only - No Audible Alarm)

Hourmeter

Indicator Lights:

Park Brake Actuated

Forward-Reverse Travel

I or II Speed Range

Turn Signal and Hazard Lights

High Beam Indicator

Battery Voltage

Floormat

Horn, Electric (Conforms to SAE J994, J1446)

Key Start Switch with Electric

Fuel Shut-Off

Power Port

Interior Mounted Rearview

Convex Mirror (Conforms to SAE J985)

(2) Exterior Convex Mirrors (Conforms to SAE J985)

Built-In Operators Manual

Storage Compartment

Pre-wired for Beacon

Cab includes Radio Speakers

and Antenna

## LOADER:

Hydraulic powered

Attachment Coupler

Z-Bar Linkage

Boom Float

Return to Dig Feature (visual indicator)

Loader Boom Service Lock (Conforms to SAE J38)

## OVERALL VEHICLE:

Articulation Locking Pin

J99):	Seat, Deluxe Deep Foam,	(Conforms to SAE J276)
(2) Driving/(2) Front	Fabric,(Cab Option)	Oscillating Frame Articulation
Working Halogen Lights	Mechanical	
(2) Front and (2) Rear	Suspension for Weight/	System
Turn/Flashing	Height, Fore-Aft	Front and Rear Fenders
(2) Rear Stop Lights	Adjustment, Backrest Tilts	Integral Loader Frame Lift
(2) Rear Reflectors	and Adjustable Arm Rests	and
TRANSMISSION:	Seat, Deluxe Deep Foam,	Engine Frame Lift Eyes and
Joystick FNR (Forward	Vinyl,(Canopy Option)	Tie Down Eyes
Neutral	Mechanical	Full Counterweight
Reverse) Control with	Suspension for Weight/	Drawbar with Pin
Electrohydraulic Third	Height, Fore-Aft	Rear Bottom Guard
Function Control on Joystick	Adjustment, Backrest Tilts	Environmental Fluid Drains
Hydrostatic Transmission	and Adjustable Arm Rests	Vandal Protection Locking
with	2 In. (51 mm) Seat Belt with	for:
2 Speed ranges:		Engine Enclosure (Fuel Fill
Infinite Speed Control	Retractor (Conforms to	inside Engine Compartment)
Inching Pedal	SAE J386)	Operator Enclosure
Vertical Element, HST	Electronic Monitor System	Rear Engine Access Door
Charge Pressure Filter	with	13.2 Gallon (50 L) Fuel Tank
with Bypass to Reservoir	Audible and Visual Warning:	
Oil-to-Air Cooler for	Engine Oil Pressure	Reverse Warning Alarm
Transmission		(Conforms to SAE J994,
		J1446)

Required - *You must select one from each category*

▼ BASE MACHINE

F.O.B. Baltimore, Maryland

Description	Code	Price
204L FOUR WHEEL DRIVE LOADER	OADOT	\$78,811.00

▼ OPERATOR'S STATION

Description	Code	Price
Canopy	8419	No Added Cost

Includes fixed steering column, floormat, locking storage compartment, two front and two rear work lights, vinyl mechanical suspension seat with 2 in. (51mm) seat belt with retractors (conforms to SAE J386), one interior rear view convex mirror, two exterior convex mirrors.

Cab with Heater & Air Conditioner	8422	\$11,945.00
-----------------------------------	------	-------------

Fresh air heater, defroster, and pressurizer  
Headliner, floor mat, and insulated floor  
Tinted safety glass, front and rear  
Intermittent front and rear wipers and washers  
Fabric mechanical suspension seat with 2 in. (51mm) seat belt with retractors (conforms to SAE J386)  
One interior rear view convex mirror  
Two exterior convex mirrors  
Integral front sun visor

▼ ENGINE

Description	Code	Price
Engine	0924	\$3,976.00
John Deere PowerTech E 4.5 L		

▼ RIDE CONTROL

Description	Code	Price
Less Ride Control	3000	No Added Cost
Ride Control	3010	\$2,040.00

▼ WHEELS AND TIRES

Description	Code	Price
405/70R18 Firestone Duraforce	4020	\$1,219.00

This tire option gives total machine height of 8 ft 1 inch (2468 mm) for cab option and total machine height of 8 ft (2444 mm) for the canopy option.

Mitas EM01	4025	No Added Cost
------------	------	---------------

365/70R18

This tire option gives total machine height of 8 ft (2445 mm) for cab option and total machine height of 7 ft 11 inches (2421 mm) for the canopy option.

400/70R20 Michelin XMCL	4030	\$2,227.00
-------------------------	------	------------

This tire option gives total machine height of 8 ft 2 inches (2488 mm) for cab option and total machine height of 8 ft 1 inch (2464 mm) for the canopy option.

▼ WORK LIGHTS

Description	Code	Price
Halogen Work Lights	7110	No Added Cost

Canopy  
2x Front, 2x Rear Halogen WorkLights

Halogen Work Lights - Cab	7120	No Added Cost
---------------------------	------	---------------

2x Front, 2x Rear Halogen WorkLights

▼ BUCKETS AND COUPLERS

Description	Code	Price
Less Coupler / Coupler Ready	8545	No Added Cost

Dealer must order and install AT412608 Integrated Skid Steer Compatible Quik Tatch Coupler or ISO Integrated Coupler. Must also order a bucket if desired.

Optional - *Select as desired*

▼ SPEED CONTROL

Description	Code	Price
Creep/Speed Control	9300	\$2,148.00

Only available with Cab Option Code 8422



## DEALER-INSTALLED KITS

Description	Code	Price
<u><a href="#">Buckets &amp; Pallet Forks</a></u>		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler	AT316647	\$1,957.00
* 74.8 in. (1.90 m) overall width * Includes 2 built-in lift loops		
1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for ISO Coupler	AT316646	\$2,930.00
* 86.6 in. (2.2 m) overall width * Includes 2 built-in lift loops		
Pallet Forks for ISO Coupler	BYT11466	\$2,258.00
Class ITA 2B fork frame Frame width 49 in. (1.2m) Tires, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)		
Replace kit AT321215		
<u><a href="#">Buckets Couplers &amp; Forks</a></u>		
1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch		
74.8 in. (1.90 m) overall width Includes 2 built-in lift loops		