

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

AF66 AG FORKS
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

<i>F.O.B. Dubuque, Iowa</i>				
9360T		AF66 AG FORKS <i>For use on the following models:</i> 312-318G SS 313-320 SS 318D-320D SS 318E-320E SS 317 CTL CT315 CTL		1,263.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

AF78 AG FORKS
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

<i>F.O.B. Dubuque, Iowa</i>				
9340T		AF78 AG FORKS <i>For use on the following models:</i> 317-328 SS 318D-328D SS 318E-328E SS CT322 CTL 317G CTL 319D-323D CTLs 319E-323E CTLs		1,550.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AT14 Angle-Tatch

Equipment for Base Machine

The Angle-Tatch attaches to the Quik-Tatch coupler and allows attachments to tilt up to 14 degrees to the left and right of level. The Angle-Tatch allows buckets, blades, and other non-hydraulic attachments to rotate for more precise grading and leveling.

(46.8)
Overall Height cm/(in) 46.99 (18.5)
Overall Depth cm/(in) 10.67 (4.2)
Cylinder Bore cm/(in) 6.35 (2.5)
Rod Diameter cm/(in) 3.30 (1.3)
Tilt Angle (degree) 14
Lift Capacity kg/(lb.) 1905.08 (4,200)

Weight kg/(lb.) 191.41 (422)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03D0T	AT14 Angle-Tatch <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTL 319E-333E CTL 204K-324K Wheel Loader with Skid Steer Style Coupler.	3,336.00
-------	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

PA15B PLANETARY DRIVE AUGER

Equipment for Base Machine

Planetary Drive:
Heavy Duty, All Gear Design
Sealed Drive Unit
Reverse Rotation Feature

Forged Alloy Steel
Heat-Treated Bolt-On Teeth
Reinforced Boring Head

Auger Bits:
Double-Wrap Flighting

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Ia.

03V1T	PA15B PLANETARY DRIVE AUGER <i>For use on the following models: 312G-314G SS 17-27 CE</i>	2,248.00
-------	--	----------

BACKHOE PLANETARY DRIVE AUGER QUICK CONNECTION

1006	PA15B PLANETARY AUGER FOR SKID STEER <i>Includes Skid Steer Mounting Bracket Bit is NOT included</i>	400.00
1007	PA15B PLANETARY AUGER FOR COMPACT EXCAVATOR LESS MOUNTING BRACKET <i>NOTE: * Requires Interface Adapter (9800, 9801) * Interface Adapter NOT included * For 17 and 27 CE * Bit is NOT included</i>	No Added Cost

INTERFACE ADAPTERS

9800	Interface Adapter for 17 ZTS and 17G	585.00
9801	Interface Adapter for 26G - 35G CE and 110 TLB	703.00

AUGER BITS

9000	4 in. Heavy Duty Bit	239.00
9001	6 in. Heavy Duty Bit	263.00
9002	8 in. Heavy Duty Bit	376.00
9003	9 in. Heavy Duty Bit	383.00
9004	10 in. Heavy Duty Bit	438.00
9005	12 in. Heavy Duty Bit	445.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

PA15B PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		AUGER BITS Continued...		
9006		15 in. Heavy Duty Bit		579.00
9007		18 in. Heavy Duty Bit		729.00
9008		24 in. Heavy Duty Bit		886.00
9011		18 in. Tree and Shrub Bit		670.00
9012		24 in. Tree and Shrub Bit		694.00
9015		9 in. Rock Bit		1,030.00
9016		12 in. Rock Bit		1,142.00
9017		9 in. HD Difficult Ground Bit		583.00
9018		12 in. HD Difficult Ground Bit		623.00
9019		15 in. HD Difficult Ground Bit		787.00
9020		18 in. HD Difficult Ground Bit		923.00
9021		24 in. HD Difficult Ground Bit		1,351.00
		DEALER-INSTALLED KITS		
		Adapters & Mounting Frames		
	AT431624	PA15/PA30 Skid Steer Mounting Kit		563.00
		Auger Bits		
	KV15765	10 in. Heavy Duty Bit		438.00
	AT379607	12 in. HD Difficult Ground Bit		623.00
	KV15766	12 in. Heavy Duty Bit		445.00
	AT379608	15 in. HD Difficult Ground Bit		787.00
	KV15767	15 in. Heavy Duty Bit		579.00
	AT379609	18 in. HD Difficult Ground Bit		923.00
	KV15768	18 in. Heavy Duty Bit		729.00
	KV15772	18 in. Tree and Shrub Bit		670.00
	AT379610	24 in. HD Difficult Ground Bit		1,351.00
	KV15769	24 in. Heavy Duty Bit		886.00
	KV15773	24 in. Tree and Shrub Bit		694.00
	KV15761	4 in. Heavy Duty Bit		239.00
	KV15762	6 in. Heavy Duty Bit		263.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

3

PA15B PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	KV15763	8 in. Heavy Duty Bit		376.00
	AT379606	9 in. HD Difficult Ground Bit		583.00
	KV15764	9 in. Heavy Duty Bit		383.00
	KV15776	9 in. Rock Bit		1,030.00
		Extensions & Adapters		
	KV15779	12 in. Hex Drive Extension		180.00
	KV15781	2 in. Hex to 2-9/16 in. Round Adaptor		219.00
	KV15782	2-9/16 in. Round to 2 in. Hex		143.00
	KV15780	24 in. Hex Drive Extension		209.00
		Interface Adapters For Compact Excavators		
	AT306925	Interface Adapter for 17 ZTS		585.00
	AT306924	Interface Adapter for 27-35 CE and 110 TLB		703.00
		Kits & Accessories		
	KV15777	12 in. Rock Bit		1,142.00
	AT357576	ISO Adapter to Quik Tatch Coupler <i>Adapter for Standard Coupler to use Skid Steer Attachments</i>		1,584.00
		Miscellaneous		
	AT306926	Interface Adapter for 50-60 CE		719.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PA30B PLANETARY DRIVE AUGER

Equipment for Base Machine

Planetary Drive:
Heavy Duty, All Gear Design
Sealed Drive Unit
Reverse Rotation Feature

Forged Alloy Steel
Heat-Treated Bolt-On Teeth
Reinforced Boring Head

Auger Bits:
Double-Wrap Flighting

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Ia.

03N1T	PA30B PLANETARY DRIVE AUGER <i>For use on the following models:</i> 316G-332G SS 318E-332E SS 317G-333G CTL 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB 35-60 CE * With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required. AT428072 hydraulic quick coupler adapter kit is available to adapt all HIGH FLOW E series SSL and CTL machines to standard flow attachment couplers.	2,428.00
-------	--	----------

BACKHOE PLANETARY DRIVE AUGER QUICK CONNECTION

1008	PA30B PLANETARY AUGER FOR SKID STEERS, CTLs, AND CWL <i>Includes Skid Steer Mounting Bracket</i> <i>Bit is NOT included</i>	440.00
1009	PA30B PLANETARY AUGER FOR COMPACT EXCAVATOR LESS MOUNTING BRACKET <i>Requires Interface Adapter (9801, 9803)</i> <i>Interface Adapter NOT included</i> <i>Bit is NOT included</i> <i>If Compact Excavator is equipped with Long Arm (7120), also requires 2 hydraulic hoses (AT321209) from Parts.</i>	No Added Cost

INTERFACE ADAPTERS

9801	Interface Adapter for 26G - 35G CE and 110 TLB	703.00
9803	Interface Adapter for 50G - 60G CE	719.00

AUGER BITS

9000	4 in. Heavy Duty Bit	239.00
------	----------------------	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

PA30B PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
AUGER BITS Continued...				
9001		6 in. Heavy Duty Bit		263.00
9002		8 in. Heavy Duty Bit		376.00
9003		9 in. Heavy Duty Bit		383.00
9004		10 in. Heavy Duty Bit		438.00
9005		12 in. Heavy Duty Bit		445.00
9006		15 in. Heavy Duty Bit		579.00
9007		18 in. Heavy Duty Bit		729.00
9008		24 in. Heavy Duty Bit		886.00
9009		30 in. Heavy Duty Bit		1,187.00
9010		36 in. Heavy Duty Bit		1,351.00
9011		18 in. Tree and Shrub Bit		670.00
9012		24 in. Tree and Shrub Bit		694.00
9013		30 in. Tree and Shrub Bit		1,010.00
9014		36 in. Tree and Shrub Bit		1,198.00
9015		9 in. Rock Bit		1,030.00
9016		12 in. Rock Bit		1,142.00
9017		9 in. HD Difficult Ground Bit		583.00
9018		12 in. HD Difficult Ground Bit		623.00
9019		15 in. HD Difficult Ground Bit		787.00
9020		18 in. HD Difficult Ground Bit		923.00
9021		24 in. HD Difficult Ground Bit		1,351.00
DEALER-INSTALLED KITS				
		Adapters & Mounting Frames		
	AT431624	PA15/PA30 Skid Steer Mounting Kit		563.00
		Auger Bits		
	KV15765	10 in. Heavy Duty Bit		438.00
	AT379607	12 in. HD Difficult Ground Bit		623.00
	KV15766	12 in. Heavy Duty Bit		445.00
	AT379608	15 in. HD Difficult Ground Bit		787.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

3

PA30B PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	KV15767	15 in. Heavy Duty Bit		579.00
	AT379609	18 in. HD Difficult Ground Bit		923.00
	KV15768	18 in. Heavy Duty Bit		729.00
	KV15772	18 in. Tree and Shrub Bit		670.00
	AT379610	24 in. HD Difficult Ground Bit		1,351.00
	KV15769	24 in. Heavy Duty Bit		886.00
	KV15773	24 in. Tree and Shrub Bit		694.00
	KV15770	30 in. Heavy Duty Bit		1,187.00
	KV15774	30 in. Tree and Shrub Bit		1,010.00
	KV15771	36 in. Heavy Duty Bit		1,351.00
	KV15775	36 in. Tree and Shrub Bit		1,198.00
	KV15761	4 in. Heavy Duty Bit		239.00
	KV15762	6 in. Heavy Duty Bit		263.00
	KV15763	8 in. Heavy Duty Bit		376.00
	AT379606	9 in. HD Difficult Ground Bit		583.00
	KV15764	9 in. Heavy Duty Bit		383.00
	KV15776	9 in. Rock Bit		1,030.00
		Extensions & Adapters		
	KV15779	12 in. Hex Drive Extension		180.00
	KV15781	2 in. Hex to 2-9/16 in. Round Adaptor		219.00
	KV15782	2-9/16 in. Round to 2 in. Hex		143.00
	KV15780	24 in. Hex Drive Extension		209.00
		Interface Adapters For Compact Excavators		
	AT306925	Interface Adapter for 17 ZTS		585.00
	AT306924	Interface Adapter for 27-35 CE and 110 TLB		703.00
		Kits & Accessories		
	KV15777	12 in. Rock Bit		1,142.00
	AT357576	ISO Adapter to Quik Tatch Coupler <i>Adapter for Standard Coupler to use Skid Steer Attachments</i>		1,584.00
		Miscellaneous		
	AT306926	Interface Adapter for 50-60 CE		719.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

4

PA30B PLANETARY DRIVE AUGER

Continued

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

PA40 PLANETARY DRIVE AUGER
Equipment for Base Machine

PA40 Planetary Drive Auger
Standard Equipment
PA40 Base Machine Performance:
Flow Requirements: 28 - 42 GPM
(106 - 159 lpm)
Operating Pressure: 3625 psi
Overall Attachment:

Maximum auger diameter: 48 in
(1219mm)
Output shaft: 2 in (51mm)
Hexagon
3/4 in. Couplers and Hoses

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Ia.

9965T	PA40 PLANETARY DRIVE AUGER <i>For use on the following models: 330G, 332G, 331G & 333G with High Flow.</i> <i>Includes Skid Steer Mounting Bracket.</i>	5,397.00
-------	---	----------

AUGER BITS

9000	4 in. Heavy Duty Bit	239.00
9001	6 in. Heavy Duty Bit	263.00
9002	8 in. Heavy Duty Bit	376.00
9003	9 in. Heavy Duty Bit	383.00
9004	10 in. Heavy Duty Bit	438.00
9005	12 in. Heavy Duty Bit	445.00
9006	15 in. Heavy Duty Bit	579.00
9007	18 in. Heavy Duty Bit	729.00
9008	24 in. Heavy Duty Bit	886.00
9009	30 in. Heavy Duty Bit	1,187.00
9010	36 in. Heavy Duty Bit	1,351.00
9011	18 in. Tree and Shrub Bit	670.00
9012	24 in. Tree and Shrub Bit	694.00
9013	30 in. Tree and Shrub Bit	1,010.00
9014	36 in. Tree and Shrub Bit	1,198.00
9015	9 in. Rock Bit	1,030.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

PA40 PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
AUGER BITS Continued...				
9016		12 in. Rock Bit		1,142.00
9017		9 in. HD Difficult Ground Bit		583.00
9018		12 in. HD Difficult Ground Bit		623.00
9019		15 in. HD Difficult Ground Bit		787.00
9020		18 in. HD Difficult Ground Bit		923.00
9021		24 in. HD Difficult Ground Bit		1,351.00
DEALER-INSTALLED KITS				
Auger Bits				
	KV15765	10 in. Heavy Duty Bit		438.00
	AT379607	12 in. HD Difficult Ground Bit		623.00
	KV15766	12 in. Heavy Duty Bit		445.00
	AT379608	15 in. HD Difficult Ground Bit		787.00
	KV15767	15 in. Heavy Duty Bit		579.00
	AT379609	18 in. HD Difficult Ground Bit		923.00
	KV15768	18 in. Heavy Duty Bit		729.00
	KV15772	18 in. Tree and Shrub Bit		670.00
	AT379610	24 in. HD Difficult Ground Bit		1,351.00
	KV15769	24 in. Heavy Duty Bit		886.00
	KV15773	24 in. Tree and Shrub Bit		694.00
	KV15770	30 in. Heavy Duty Bit		1,187.00
	KV15774	30 in. Tree and Shrub Bit		1,010.00
	KV15771	36 in. Heavy Duty Bit		1,351.00
	KV15775	36 in. Tree and Shrub Bit		1,198.00
	KV15761	4 in. Heavy Duty Bit		239.00
	KV15762	6 in. Heavy Duty Bit		263.00
	KV15763	8 in. Heavy Duty Bit		376.00
	AT379606	9 in. HD Difficult Ground Bit		583.00
	KV15764	9 in. Heavy Duty Bit		383.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

3

PA40 PLANETARY DRIVE AUGER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	KV15776	9 in. Rock Bit		1,030.00
		Extensions & Adapters		
	KV15779	12 in. Hex Drive Extension		180.00
	KV15781	2 in. Hex to 2-9/16 in. Round Adaptor		219.00
	KV15782	2-9/16 in. Round to 2 in. Hex		143.00
	KV15780	24 in. Hex Drive Extension		209.00
		Interface Adapters For Compact Excavators		
	AT306925	Interface Adapter for 17 ZTS		585.00
	AT306924	Interface Adapter for 27-35 CE and 110 TLB		703.00
		Kits & Accessories		
	KV15777	12 in. Rock Bit		1,142.00
	AT357576	ISO Adapter to Quik Tatch Coupler <i>Adapter for Standard Coupler to use Skid Steer Attachments</i>		1,584.00
		Miscellaneous		
	AT306926	Interface Adapter for 50-60 CE		719.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BH9B BACKHOE

Equipment for Base Machine

Product Features:
Cushioned cylinders provide smooth operation and limit shock loads
Low-profile console maximizes visibility
Boom-lock and swing-lock levers are provided for secure transport
Two-lever control of boom / swing (left) and dipperstick / bucket (right) allow precise control
Swing speed control and 180° swing range maximizes efficiency in confined areas
Heavy-duty buckets feature an easy clean-out design and three linkage options to maximize curl, reach, or breakout force
Machine ingress / egress is easy due to a convenient grab handle

and open design. Standard tilt-away seat allows easy access to skid steer / CTL cab. Seat includes height and fore / aft adjustment to ensure comfortable operation.
Dual lock arms quickly and easily latch to the SSL / CTL mainframe
Ideal for light duty Ag or utility work

Specifications:
Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers
1025 lb. [465 kg] overall weight, without mounting bracket
110 in. [2795 mm] maximum dig depth
88 in. [2235 mm] dip depth for 8 ft. flat bottom

Bucket widths of 18 in. [455 mm], 24 in. [610 mm], or 36 in. [915 mm]

Hydraulic Specifications:
9 12 gpm [34 45 l/min] hydraulic flow range
2750 psi [19000 kPa] system relief pressure
3895 lb. [1765 kg] maximum breakout force

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

50A1T	BH9B BACKHOE <i>For use on the following models:</i> SSL: 312GR - 318G CTL: 317G <i>Machine must be equipped with Power Quick-Tatch. Rear counterweight may improve machine stability while operating.</i>	10,138.00
-------	--	-----------

MOUNTING KITS

1001	Mounting Kit - Small Frame SSL/CTL	2,631.00
------	------------------------------------	----------

BUCKETS

2001	18 in. (457 mm) Bucket	613.00
2002	24 in. (610 mm) Bucket	674.00
2003	36 in. (914 mm) Bucket	1,173.00

DEALER-INSTALLED KITS

	Buckets	
BYT11398	18 in. (457 mm) Bucket	613.00
BYT11399	24 in. (610 mm) Bucket	674.00
BYT11400	36 in. (914 mm) Bucket	1,173.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

BH9B BACKHOE

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
		Kits & Accessories		
	BYT11332	Backhoe Attachment Mounting Kit <i>For Small Frame G-Series SSLs and CTLs</i>		2,631.00
	BYT11334	Backhoe Attachment Mounting Kit <i>For Mid Frame G-Series SSLs and CTLs</i>		2,417.00
	BYT11336	Backhoe Attachment Mounting Kit		2,381.00
		Miscellaneous		
	BYT11410	Rubber Stabilizer Pads		148.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BH10B BACKHOE

Equipment for Base Machine

Product Features:
Cushioned cylinders provide smooth operation and limit shock loads
Low-profile console maximizes visibility
Boom-lock and swing-lock levers are accessible from the seat for secure transport
Two-lever control of boom / swing (left) and dipperstick / bucket (right) allow precise control
Swing speed control and 180° swing range maximizes efficiency in confined areas
Heavy-duty buckets feature an easy clean-out design and three linkage options to maximize curl, reach, or breakout force
Machine ingress / egress is easy due to a convenient grab handle

and open design. Standard tilt-away seat allows easy access to skid steer / CTL cab. Seat includes height and fore / aft adjustment to ensure comfortable operation.
Dual lock arms quickly and easily latch to the SSL / CTL mainframe
Ideal for light construction, Ag, or utility work

Specifications:
Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers
1285 lb. [585 kg] overall weight, without mounting bracket
116 in. [2945 mm] maximum dig depth
99 in. [2515 mm] dip depth for 8 ft. flat bottom

Bucket widths of 18 in. [455 mm], 24 in. [610 mm], or 36 in. [915 mm]

Hydraulic Specifications:
9 12 gpm [34 45 l/min] hydraulic flow range
2500 psi [17000 kPa] system relief pressure
5675 lb. [2575 kg] maximum breakout force

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

75C1T	BH10B BACKHOE <i>For use on the following models:</i> SSL: 312GR - 332G CTL: 317G - 333G <i>If using on a 312GR - 318G SSL/CTL, machine must be equipped with Power Quick-Tatch. 320G and larger can be equipped with either Manual or Power Quick-Tatch. Rear counterweight may improve machine stability while operating.</i>	13,495.00
-------	---	-----------

MOUNTING KITS

1001	Mounting Kit - Small Frame SSL/CTL	2,631.00
1002	Mounting Kit - Mid Frame SSL/CTL	2,417.00
1003	Mounting Kit - Large Frame SSL/CTL	2,381.00

BUCKETS

2001	18 in. (457 mm) Bucket	966.00
2002	24 in. (610 mm) Bucket	1,011.00
2003	36 in. (914 mm) Bucket	1,299.00

DEALER-INSTALLED KITS

Buckets

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

BH10B BACKHOE

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	BYT11401	18 in. (457 mm) Bucket		966.00
	BYT11402	24 in. (610 mm) Bucket		1,011.00
	BYT11403	36 in. (914 mm) Bucket		1,299.00
		Kits & Accessories		
	BYT11332	Backhoe Attachment Mounting Kit <i>For Small Frame G-Series SSLs and CTLs</i>		2,631.00
	BYT11334	Backhoe Attachment Mounting Kit <i>For Mid Frame G-Series SSLs and CTLs</i>		2,417.00
	BYT11336	Backhoe Attachment Mounting Kit		2,381.00
		Miscellaneous		
	BYT11411	Rubber Stabilizer Pads		625.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BH11B BACKHOE

Equipment for Base Machine

Product Features:
Cushioned cylinders provide smooth operation and limit shock loads
Low-profile console maximizes visibility
Boom-lock and swing-lock levers are accessible from the seat for secure transport
Two-lever control of boom / swing (left) and dipperstick / bucket (right) allow precise control
Swing speed control and 180° swing range maximizes efficiency in confined areas
Heavy-duty buckets feature an easy clean-out design and three linkage options to maximize curl, reach, or breakout force
Machine ingress / egress is easy due to a convenient grab handle

and open design. Standard tilt-away seat allows easy access to skid steer / CTL cab. Seat includes height and fore / aft adjustment to ensure comfortable operation.
Dual lock arms quickly and easily latch to the SSL / CTL mainframe
Ideal for light construction, Ag, or utility work

Specifications:
Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers
1455 lb. [660 kg] overall weight, without mounting bracket
133 in. [3380 mm] maximum dig depth
119 in. [3025 mm] dip depth for 8 ft. flat bottom

Bucket widths of 18 in. [455 mm], 24 in. [610 mm], or 36 in. [915 mm]

Hydraulic Specifications:
9 12 gpm [34 45 l/min] hydraulic flow range
2500 psi [17000 kPa] system relief pressure
6200 lb. [2575 kg] maximum breakout force

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

75B1T	BH11B BACKHOE <i>For use on the following models:</i> SSL: 312GR - 332G CTL: 317G - 333G <i>If using on a 312GR - 318G SSL/CTL, machine must be equipped with Power Quick-Tatch. 320G and larger can be equipped with either Manual or Power Quick-Tatch. Rear counterweight may improve machine stability while operating.</i>	14,228.00
-------	---	-----------

MOUNTING KITS

1001	Mounting Kit - Small Frame SSL/CTL	2,631.00
1002	Mounting Kit - Mid Frame SSL/CTL	2,417.00
1003	Mounting Kit - Large Frame SSL/CTL	2,381.00

BUCKETS

2001	18 in. (457 mm) Bucket	966.00
2002	24 in. (610 mm) Bucket	1,011.00
2003	36 in. (914 mm) Bucket	1,299.00

DEALER-INSTALLED KITS

Buckets

03 January 2020
US

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

BH11B BACKHOE

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	BYT11401	18 in. (457 mm) Bucket		966.00
	BYT11402	24 in. (610 mm) Bucket		1,011.00
	BYT11403	36 in. (914 mm) Bucket		1,299.00
		Kits & Accessories		
	BYT11332	Backhoe Attachment Mounting Kit <i>For Small Frame G-Series SSLs and CTLs</i>		2,631.00
	BYT11334	Backhoe Attachment Mounting Kit <i>For Mid Frame G-Series SSLs and CTLs</i>		2,417.00
	BYT11336	Backhoe Attachment Mounting Kit		2,381.00
		Miscellaneous		
	BYT11411	Rubber Stabilizer Pads		625.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AH80 BALE HUGGER

Equipment for Base Machine

<p>Bale Hugger is designed for very large bales. It has a maximum opening of 110 inches and will squeeze the bales together to transport, stack or load bales.</p> <p>-Designed with round tubing to provide maximum durability while preventing damage to wrapped bale coverings</p> <p>-Provides constant pressure that eliminates the risk of dropping bales</p> <p>-Right-hand and left-hand sides</p>	<p>open and close simultaneously</p> <p>-Can lift, move, and stack round or rectangular bales</p> <p>-Ideal for 1,000 lb. silage bags with a maximum load of 2,400 lbs.</p> <p>Overall Width cm/(in) 120.65 (47.5)</p> <p>Overall Height cm/(in) 95.25 (37.5)</p> <p>Overall Depth cm/(in) 137.16 (54)</p> <p>Max. Opening cm/(in) 279.40</p>	<p>(110)</p> <p>Lift Capacity kg/(lb.) 1088.62 (2,400)</p> <p>Weight kg/(lb.) 217.72 (480)</p>
--	---	--

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03E0T	<p>AH80 BALE HUGGER</p> <p><i>For use on the following models:</i></p> <p>312G-332G SS</p> <p>318E-332E SS</p> <p>317G-333G CTL</p> <p>319E-333E CTL</p> <p>204K-324K Wheel Loader with Skid Steer Style Coupler.</p>	3,185.00
-------	---	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AB21 SINGLE BALE SPEAR

Equipment for Base Machine

Capacity at Load Center:
907 kg at 0.61 m (2,000 lbs. at
24 in.)

Depth: 1.28 m (50.50 in.)
Spear Length: 1.24 m (49 in.)
Weight: 66 kg (145 lbs.)

Width: 1.15 m (42.25 in.)
Height: 0.57 m (22.38 in.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05A0T	AB21 SINGLE BALE SPEAR <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>	587.00
-------	---	--------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AB32 DUAL BALE SPEAR

Equipment for Base Machine

Capacity at Load Center:
1361 kg at 0.61 m (3,000 lbs. at
24 in.)

Depth: 1.42 m (55.75 in.)
Spear Length: 1.35 m (53 in.)
Weight: 91 kg (200 lbs.)

Width: 1.24 m (48.75 in.)
Height: 0.64 m (25.00 in.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05B0T		AB32 DUAL BALE SPEAR <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>		723.00
-------	--	---	--	--------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AB31 SINGLE BALE SPEAR, HD

Equipment for Base Machine

Capacity at Load Center: 1361 kg at 0.61 m (3,000 lbs. at 24 in.)
Depth: 1.28 m (50.50in.)
Spear Length: 1.24 m (49in.)
Weight: 70 kg (155 lbs.)

Width: 1.15 m (42.25 in.)
Height: 0.59 m (23.13 in.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05C0T	AB31 SINGLE BALE SPEAR, HD <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>	720.00
-------	---	--------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AB42 DUAL BALE SPEAR, HD

Equipment for Base Machine

Capacity at Load Center: 1814 kg at 0.61 m (4,000 lbs. at 24 in.)
Depth: 1.42 m (55.75 in.)
Spear Length: 1.35 m (53 in.)
Weight: 109 kg (240 lbs.)

Width: 1.24 m (48.75 in.)
Height: 0.64 m (25.00 in.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05D0T	AB42 DUAL BALE SPEAR, HD <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>	875.00
-------	---	--------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AB43 TRIPLE BALE SPEAR

Equipment for Base Machine

Capacity at Load Center:
1814 kg at 0.61 m (4,000 lbs. at
24 in.)

Depth: 1.33 m (52.25 in.)
Spear Length: 1.24 m (49 in.)
Weight: 102 kg (225 lbs.)

Width: 1.42 m (56.00 in.)
Height: 0.62 m (24.25 in.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05E0T	AB43 TRIPLE BALE SPEAR <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL 110 TLB <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>	1,010.00
-------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BALE SPEAR, SQUARE
Equipment for Base Machine

No Base Equipment Description
Provided

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9350T		BALE SPEAR, SQUARE <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL <i>* With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.</i>		1,040.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835		Counterweight, Stackable (Single Set)		363.00
AT357576		ISO Adapter to Quik Tatch Coupler		1,584.00
KV14620		Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>		196.00
AT311312		Rear Weight Bracket Kit (325-332)		199.00
R66949Y		Yellow 42lb. Quik-Tatch Weight		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

72" Box Blade - Topcon 2D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2020 lb. [915 kg] overall weight
75 in. [1910 mm] overall width
72 in. [1830 mm] cutting width
11.5 ft.3 [0.33 m3] front box capacity
7.0 ft.3 [0.20 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57 95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03R2T	72" Box Blade - Topcon 2D Ready System <i>For use on the following models:</i> SSL: 312GR - 318G CTL: 317G - Requires machine equipped with 1/2 quick connect couplers and 3/8 case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	19,642.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

84" Box Blade - Topcon 2D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2070 lb. [940 kg] overall weight
87 in. [2220 mm] overall width
84 in. [2130 mm] cutting width
13.4 ft.3 [0.38 m3] front box capacity
8.0 ft.3 [0.23 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57-95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03S2T	84" Box Blade - Topcon 2D Ready System <i>For use on the following models:</i> SSL: 314G - 332G CTL: 317G - 333G - Requires machine equipped with 1/2" quick connect couplers and 3/8" case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	20,146.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

96" Box Blade - Topcon 2D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2155 lb. [980 kg] overall weight
99 in. [2520 mm] overall width
96 in. [2440 mm] cutting width
15.3 ft.3 [0.43 m3] front box capacity
9.0 ft.3 [0.25 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57-95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03T2T	96" Box Blade - Topcon 2D Ready System <i>For use on the following models:</i> SSL: 318G - 332G CTL: 317G - 333G - Requires machine equipped with 1/2" quick connect couplers and 3/8" case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	20,529.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

72" Box Blade - Topcon 3D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2020 lb. [915 kg] overall weight
75 in. [1910 mm] overall width
72 in. [1830 mm] cutting width
11.5 ft.3 [0.33 m3] front box capacity
7.0 ft.3 [0.20 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57-95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03R3T	72" Box Blade - Topcon 3D Ready System <i>For use on the following models:</i> SSL: 312GR - 318G CTL: 317G - Requires machine equipped with 1/2" quick connect couplers and 3/8" case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	21,060.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

84" Box Blade - Topcon 3D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2070 lb. [940 kg] overall weight
87 in. [2220 mm] overall width
84 in. [2130 mm] cutting width
13.4 ft.3 [0.38 m3] front box capacity
8.0 ft.3 [0.23 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57 95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03S3T	84" Box Blade - Topcon 3D Ready System <i>For use on the following models:</i> SSL: 314G - 332G CTL: 317G - 333G - Requires machine equipped with 1/2 quick connect couplers and 3/8 case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	21,564.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

96" Box Blade - Topcon 3D Ready System

Equipment for Base Machine

Features:

Push-pull design to move material for fine grading
Two cylinders to provide cross-slope operation
Reversible cutting edges
Convex mirror for material visibility
Power-coated paint finish
Foam-filled tires on oscillating axle
Two, 1.5 in. [38 mm] diameter mast poles

Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers and 3/8 in. case drain coupler
2155 lb. [980 kg] overall weight
99 in. [2520 mm] overall width
96 in. [2440 mm] cutting width
15.3 ft.3 [0.43 m3] front box capacity
9.0 ft.3 [0.25 m3] rear box capacity
Hydraulic Specifications:

15 - 25 gpm [57-95 l/min]
hydraulic flow range
4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

03T3T	96" Box Blade - Topcon 3D Ready System <i>For use on the following models:</i> SSL: 318G - 332G CTL: 317G - 333G - Requires machine equipped with 1/2" quick connect couplers and 3/8" case drain coupler - Requires 14-pin auxiliary electrical connector - Rear counterweight may improve machine stability while operating - Creeper Mode may improve machine performance while operating - Requires additional grade control components from Topcon dealer	21,947.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BA72C 72" Angle Broom Equipment for Base Machine

Features:

Heavy-duty, high-torque motor
protected within broom frame
50/50 poly-wire brush segments
32 in. [810 mm] brush diameter
Hydraulic angling ± 30°; either direction
Fold-away storage stands
Specifications:
Skid steer coupler attachment
interface
3-pin electrical connector
1/2 in. hydraulic quick couplers
15-25 gpm [57 95 l/min]

hydraulic flow range
910 lb. [410 kg] overall weight
72 in. [1830 mm] straight
sweeping width
62 in. [1580 mm] angled sweeping
width
92 in. [2330 mm] overall
straight width
88 in. [2230 mm] overall angled
width
Optional Equipment:
All-polypropylene brush segments
Hood extension with rubber
deflector for 180°; brush

coverage
Roof-mounted water tank kit with
30 gal. [113.5 l] capacity

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

0302KV	BA72C 72" Angle Broom <i>For use on the following models: SSL: 312GR - 332G CTL: 317G - 333G # Requires machine equipped with 3-pin electrical connector.</i>	7,335.00
--------	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

BYT11026	180 Degree Hood Extension Kit	998.00
BYT11025	Nozzle Kit <i>Nozzle kit for roof-mounted water tank kits</i>	248.00
AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G CTL: 317G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,328.00
AT435129	Roof-Mounted Water Tank Kit <i>SSL: 320G - 332G CTL: 325G - 333G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BA84C 84" Angle Broom

Equipment for Base Machine

Features:

Heavy-duty, high-torque motor
protected within broom frame
50/50 poly-wire brush segments
32 in. [810 mm] brush diameter
Hydraulic angling ± 30°; either direction
Fold-away storage stands
Specifications:
Skid steer coupler attachment
interface
3-pin electrical connector
1/2 in. hydraulic quick couplers
15-25 gpm [57 95 l/min]

hydraulic flow range
960 lb. [440 kg] overall weight
84 in. [2130 mm] straight
sweeping width
73 in. [1850 mm] angled sweeping
width
104 in. [2640 mm] overall
straight width
98 in. [2490 mm] overall angled
width
Optional Equipment:
All-polypropylene brush segments
Hood extension with rubber
deflector for 180°; brush

coverage

Roof-mounted water tank kit with
30 gal. [113.5 l] capacity

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

0303KV	BA84C 84" Angle Broom <i>For use on the following models: SSL: 320G - 332G CTL: 317G - 333G # Requires machine equipped with 3-pin electrical connector.</i>	7,538.00
--------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

BYT11027	180 Degree Hood Extension Kit	998.00
BYT11025	Nozzle Kit <i>Nozzle kit for roof-mounted water tank kits</i>	248.00
AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G CTL: 317G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,328.00
AT435129	Roof-Mounted Water Tank Kit <i>SSL: 320G - 332G CTL: 325G - 333G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BA96C 96" Angle Broom Equipment for Base Machine

Features:

Heavy-duty, high-torque motor
protected within broom frame
50/50 poly-wire brush segments
32 in. [810 mm] brush diameter
Hydraulic angling ± 30° either direction
Fold-away storage stands
Specifications:
Skid steer coupler attachment
interface
3-pin electrical connector
1/2 in. hydraulic quick couplers
15-25 gpm [57 95 l/min]

hydraulic flow range
1100 lb. [460 kg] overall weight
96 in. [2440 mm] straight
sweeping width
83 in. [2110 mm] angled sweeping
width
116 in. [2940 mm] overall
straight width
109 in. [2760 mm] overall angled
width
Optional Equipment:
All-polypropylene brush segments
Hood extension with rubber
deflector for 180° brush

coverage
Roof-mounted water tank kit with
30 gal. [113.5 l] capacity

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

0304KV	BA96C 96" Angle Broom <i>For use on the following models: SSL: 330G - 332G CTL: 331G - 333G # Requires machine equipped with 3-pin electrical connector.</i>	7,740.00
--------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

BYT11028	180 Degree Hood Extension Kit	998.00
BYT11025	Nozzle Kit <i>Nozzle kit for roof-mounted water tank kits</i>	248.00
AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G CTL: 317G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,328.00
AT435129	Roof-Mounted Water Tank Kit <i>SSL: 320G - 332G CTL: 325G - 333G 30 gal. [113.5 l] capacity Use with nozzle kit</i>	1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BP72C 72" Pick-Up Broom

Equipment for Base Machine

Features:	interface	Roof-mounted water tank kit with
Heavy-duty, high-torque	1/2 in. hydraulic quick couplers	30 gal. [113.5 l] capacity
bi-directional motor protected	15-25 gpm [57 95 l/min]	
within broom frame	hydraulic flow range	
50/50 poly-wire brush segments	1275 lb. [580 kg] overall weight	
26 in. [660 mm] brush diameter	72 in. [1830 mm] sweeping width	
Adjustable baffle to increase	91 in. [2310 mm] overall width	
hopper capacity by 22%	Optional Equipment:	
Tool-free system for brush	All-polypropylene brush segments	
adjustment	Gutter brush with wire bristles	
Specifications:	Broom-mounted water tank kit	
Skid steer coupler attachment	with 25 gal. [95 l] capacity	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

0314KV		BP72C 72" Pick-Up Broom <i>For use on the following models:</i> <i>SSL: 312GR - 332G</i> <i>CTL: 317G - 325G</i>		6,965.00
--------	--	---	--	----------

DEALER-INSTALLED KITS

	Kits & Accessories		
BYT11033	Broom-Mounted Water Tank Kit <i>SSL: 312G - 332G</i> <i>CTL: 317G - 333G</i> <i>30 gal. [113.5 l] capacity</i>		712.00
BYT11030	Gutter Broom Kit		1,201.00
BYT11025	Nozzle Kit <i>Nozzle kit for roof-mounted water tank kits</i>		248.00
AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G</i> <i>CTL: 317G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,328.00
AT435129	Roof-Mounted Water Tank Kit <i>SSL: 320G - 332G</i> <i>CTL: 325G - 333G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BP84C 84" Pick-Up Broom

Equipment for Base Machine

Features:	interface	Roof-mounted water tank kit with
Heavy-duty, high-torque	1/2 in. hydraulic quick couplers	30 gal. [113.5 l] capacity
bi-directional motor protected	15-25 gpm [57 95 l/min]	
within broom frame	hydraulic flow range	
50/50 poly-wire brush segments	1400 lb. [640 kg] overall weight	
26 in. [660 mm] brush diameter	84 in. [2130 mm] sweeping width	
Adjustable baffle to increase	103 in. [2620 mm] overall width	
hopper capacity by 22%	Optional Equipment:	
Tool-free system for brush	All-polypropylene brush segments	
adjustment	Gutter brush with wire bristles	
Specifications:	Broom-mounted water tank kit	
Skid steer coupler attachment	with 25 gal. [95 l] capacity	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

0315KV	BP84C 84" Pick-Up Broom <i>For use on the following models:</i> SSL: 320G - 332G CTL: 317G - 333G	8,097.00
--------	--	----------

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT11033	Broom-Mounted Water Tank Kit SSL: 312G - 332G CTL: 317G - 333G 30 gal. [113.5 l] capacity	712.00
BYT11030	Gutter Broom Kit	1,201.00
BYT11025	Nozzle Kit Nozzle kit for roof-mounted water tank kits	248.00
AT345212	Roof-Mounted Water Tank Kit SSL: 312GR - 318G CTL: 317G 30 gal. [113.5 l] capacity Use with nozzle kit	1,328.00
AT435129	Roof-Mounted Water Tank Kit SSL: 320G - 332G CTL: 325G - 333G 30 gal. [113.5 l] capacity Use with nozzle kit	1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BR60C 60" Rigid Pick-Up Broom

Equipment for Base Machine

Features:	15-25 gpm [57 95 l/min]	30 gal. [113.5 l] capacity
Heavy-duty, high-torque	hydraulic flow range	
bi-directional motor protected	880 lb. [400 kg] overall weight	
within broom frame	60 in. [1520 mm] sweeping width	
50/50 poly-wire brush segments	69 in. [1760 mm] overall width	
26 in. [660 mm] brush diameter	Optional Equipment:	
Precise brush-contact adjustment	All-polypropylene brush segments	
Specifications:	Gutter brush with wire bristles	
Skid steer coupler attachment	Broom-mounted water tank kit	
interface	with 25 gal. [95 l] capacity	
1/2 in. hydraulic quick couplers	Roof-mounted water tank kit with	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

8202T	BR60C 60" Rigid Pick-Up Broom	4,798.00
	<i>For use on the following models:</i>	
	<i>SSL: 312GR - 318G</i>	

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT11033	Broom-Mounted Water Tank Kit	712.00
	<i>SSL: 312G - 332G</i>	
	<i>CTL: 317G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
BYT11030	Gutter Broom Kit	1,201.00
BYT11025	Nozzle Kit	248.00
	<i>Nozzle kit for roof-mounted water tank kits</i>	
AT345212	Roof-Mounted Water Tank Kit	1,328.00
	<i>SSL: 312GR - 318G</i>	
	<i>CTL: 317G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	
AT435129	Roof-Mounted Water Tank Kit	1,829.00
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BR72C 72" Rigid Pick-Up Broom

Equipment for Base Machine

Features:	15-25 gpm [57 95 l/min]	30 gal. [113.5 l] capacity
Heavy-duty, high-torque	hydraulic flow range	
bi-directional motor protected	970 lb. [440 kg] overall weight	
within broom frame	72 in. [1830 mm] sweeping width	
50/50 poly-wire brush segments	81 in. [2060 mm] overall width	
26 in. [660 mm] brush diameter	Optional Equipment:	
Precise brush-contact adjustment	All-polypropylene brush segments	
Specifications:	Gutter brush with wire bristles	
Skid steer coupler attachment	Broom-mounted water tank kit	
interface	with 25 gal. [95 l] capacity	
1/2 in. hydraulic quick couplers	Roof-mounted water tank kit with	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

1521T	BR72C 72" Rigid Pick-Up Broom	5,215.00
	<i>For use on the following models:</i>	
	<i>SSL: 312GR - 332G</i>	
	<i>CTL: 317G - 325G</i>	
	<i>CWL: 204L - 304L *requires skid steer style coupler</i>	

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT11033	Broom-Mounted Water Tank Kit	712.00
	<i>SSL: 312G - 332G</i>	
	<i>CTL: 317G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
BYT11030	Gutter Broom Kit	1,201.00
BYT11025	Nozzle Kit	248.00
	<i>Nozzle kit for roof-mounted water tank kits</i>	
AT345212	Roof-Mounted Water Tank Kit	1,328.00
	<i>SSL: 312GR - 318G</i>	
	<i>CTL: 317G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	
AT435129	Roof-Mounted Water Tank Kit	1,829.00
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

BR84C 84" Rigid Pick-Up Broom

Equipment for Base Machine

Features:	15-25 gpm [57 95 l/min]	30 gal. [113.5 l] capacity
Heavy-duty, high-torque	hydraulic flow range	
bi-directional motor protected	1090 lb. [500 kg] overall weight	
within broom frame	84 in. [2130 mm] sweeping width	
50/50 poly-wire brush segments	93 in. [2370 mm] overall width	
26 in. [660 mm] brush diameter	Optional Equipment:	
Precise brush-contact adjustment	All-polypropylene brush segments	
Specifications:	Gutter brush with wire bristles	
Skid steer coupler attachment	Broom-mounted water tank kit	
interface	with 25 gal. [95 l] capacity	
1/2 in. hydraulic quick couplers	Roof-mounted water tank kit with	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

FOB Dubuque, Iowa.

1531T	BR84C 84" Rigid Pick-Up Broom	5,635.00
	<i>For use on the following models:</i>	
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 325G</i>	
	<i>CWL: 204L - 324L *requires skid steer style coupler</i>	

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT11033	Broom-Mounted Water Tank Kit	712.00
	<i>SSL: 312G - 332G</i>	
	<i>CTL: 317G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
BYT11030	Gutter Broom Kit	1,201.00
BYT11025	Nozzle Kit	248.00
	<i>Nozzle kit for roof-mounted water tank kits</i>	
AT345212	Roof-Mounted Water Tank Kit	1,328.00
	<i>SSL: 312GR - 318G</i>	
	<i>CTL: 317G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	
AT435129	Roof-Mounted Water Tank Kit	1,829.00
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 333G</i>	
	<i>30 gal. [113.5 l] capacity</i>	
	<i>Use with nozzle kit</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

CP12D COLD PLANER

Equipment for Base Machine

Drum Size:	0-5 in. (0-127 mm)
12 in. (305 mm) Cutting Width	Hydraulic Side Shift
	0-19 in. (0-483 mm)
Design Features:	Quantity of pics 37
Standard Flow Hydraulics	Spray Bar with nozzles, less
15-22 gpm (56-83 lpm)	water tank
Planetary Drive	
Manual Tilt of +/- 11 Degrees	NOTE: The eight-button control
Manual Depth Control	handle is NOT required.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8211T	CP12D COLD PLANER	10,810.00
	<i>For Standard Flow:</i>	
	<i>315-328 SSLs</i>	
	<i>318D-328D SSLs</i>	
	<i>318E-328E SSLs</i>	
	<i>316GR - 324G SSLs</i>	
	<i>CT315, CT322 CTLs</i>	
	<i>319D-323D CTLs</i>	
	<i>319E-323E CTLs</i>	
	<i>317G-325G CTLs</i>	
	<i>AT428072 hydraulic quick coupler adapter kit is available to adapt all HIGH FLOW E series SSL and CTL machines to standard flow attachment couplers.</i>	

PICK KIT

Pick kits are not factory installed and must be installed by the dealer.

1001	General Purpose	No Added Cost
	<i>Will do both concrete and asphalt, but will wear out in concrete.</i>	
1002	RP18	No Added Cost
	<i>Asphalt only.</i>	

DEALER-INSTALLED KITS

Kits & Accessories

AT462795	Carbide Cutting Tools, General Purpose	443.00
	<i>Will do both concrete and asphalt, but will wear out in concrete.</i>	
	<i>Contains one full set of CP24D replacement cutting tools.</i>	
AT462796	Carbide Cutting Tools, RP18	378.00
	<i>Asphalt only.</i>	
	<i>Contains one full set of CP12D replacement cutting tools.</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

CP12D COLD PLANER
Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G</i> <i>CTL: 317G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,328.00
	AT435129	Roof-Mounted Water Tank Kit		1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

CP18D COLD PLANER

Equipment for Base Machine

Drum Size:	Hydraulic Side Shift
18 in. (457 mm) Cutting Width	-3 - 22 in. (-76 - 559 mm)
Design Features:	Quantity of pics 45
High Flow Hydraulics	Spray Bar with nozzles, less water tank
29-41 gpm (110-155 lpm)	
Planetary Drive	
Tilt of +/- 8 Degrees	NOTE: Hi-Flow Hydraulics and Applicable Attachment Control Kit are Required.
Depth Control 0-5 in. (0-127 mm)	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8221T	CP18D COLD PLANER	21,083.00
	For High Flow:	
	320-332 SSLs	
	320D-332D SSLs	
	320E-332E SSLs	
	320G-332G SSLs	
	CT322, CT332 CTLs	
	323D-333D CTLs	
	323E-333E CTLs	
	325G-333G CTLs	
	244L, 324L CWLs - Requires skid-steer style Quick-Tach coupler.	
	Requires machine equipped with 14-pin electrical connector.	

PICK KIT

Pick kits are not factory installed and must be installed by the dealer.

1005	General Purpose	No Added Cost
	Will do both concrete and asphalt, but will wear out in concrete.	
1006	RP18	No Added Cost
	Asphalt only.	

DEALER-INSTALLED KITS

Kits & Accessories

AT462797	Carbide Cutting Tools, General Purpose	531.00
	Will do both concrete and asphalt, but will wear out in concrete.	
	Contains one full set of CP18D replacement cutting tools.	
AT462798	Carbide Cutting Tools, RP18	452.00
	Asphalt only.	
	Contains one full set of CP18D replacement cutting tools.	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

CP18D COLD PLANER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G</i> <i>CTL: 317G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,328.00
	AT435129	Roof-Mounted Water Tank Kit		1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

CP24D COLD PLANER

Equipment for Base Machine

Drum Size:	(0-127 mm)
24 in. (610 mm) Cutting Width	Hydraulic Side Shift
	-3 - 22 in.
	(-76 - 559 mm)
Design Features:	Quantity of pics 57
High Flow Hydraulics	Spray Bar with nozzles, less
29-41 gpm (110-155 lpm)	water tank
Planetary Drive	NOTE: Hi-Flow Hydraulics
Tilt of +/- 8 Degrees	and Applicable Attachment
Depth Control 0-5 in.	Control Kit are Required.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8231T	CP24D COLD PLANER	24,165.00
	<i>For High Flow:</i>	
	<i>325-332 SSLs</i>	
	<i>326D-332D SSLs</i>	
	<i>326E-332E SSLs</i>	
	<i>330G-332G SSLs</i>	
	<i>CT332 CTL</i>	
	<i>329D, 333D CTLs</i>	
	<i>329E, 333E CTLs</i>	
	<i>331G-333G CTLs</i>	
	<i>244L, 324L CWLs - Requires skid-steer style Quick-Tach coupler.</i>	
	<i>Requires machine equipped with 14-pin electrical connector.</i>	

PICK KIT

Pick kits are not factory installed and must be installed by the dealer.

1009	General Purpose	No Added Cost
	<i>Will do both concrete and asphalt, but will wear out in concrete.</i>	
1010	RP18	No Added Cost
	<i>Asphalt only.</i>	

DEALER-INSTALLED KITS

Kits & Accessories

AT462799	Carbide Cutting Tools, General Purpose	672.00
	<i>Will do both concrete and asphalt, but will wear out in concrete.</i>	
	<i>Contains one full set of CP24D replacement cutting tools.</i>	
AT462800	Carbide Cutting Tools, RP18	570.00
	<i>Asphalt only.</i>	
	<i>Contains one full set of CP24D replacement cutting tools.</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

CP24D COLD PLANER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G</i> <i>CTL: 317G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,328.00
	AT435129	Roof-Mounted Water Tank Kit		1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

CP30D COLD PLANER

Equipment for Base Machine

Drum Size:	Hydraulic Side Shift
30 in. (762 mm) Cutting Width	-3 - 22 in. (-76 - 559 mm)
Design Features:	Quantity of pics 69
High Flow Hydraulics	Spray Bar with nozzles, less water tank
29-41 gpm (110-155 lpm)	
Planetary Drive	
Tilt of +/- 8 Degrees	NOTE: Hi-Flow Hydraulics and Applicable Attachment Control Kit are Required.
Depth Control 0-5 in. (0-127 mm)	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9011T	CP30D COLD PLANER <i>For High Flow:</i> 325-332 SSLs 326D-332D SSLs 326E-332E SSLs 330G-332G SSLs CT332 CTL 329D, 333D CTLs 329E, 333E CTLs 331G-333G CTLs <i>Requires machine equipped with 14-pin electrical connector.</i>	25,079.00
-------	---	-----------

PICK KIT

Pick kits are not factory installed and must be installed by the dealer.

1013	General Purpose <i>Will do both concrete and asphalt, but will wear out in concrete.</i>	No Added Cost
1014	RP18 <i>Asphalt only.</i>	No Added Cost

DEALER-INSTALLED KITS

AT462801	Kits & Accessories Carbide Cutting Tools, General Purpose <i>Will do both concrete and asphalt, but will wear out in concrete.</i> <i>Contains one full set of CP30D replacement cutting tools.</i>	806.00
AT462802	Carbide Cutting Tools, RP18 <i>Asphalt only.</i> <i>Contains one full set of CP30D replacement cutting tools.</i>	712.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

CP30D COLD PLANER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT345212	Roof-Mounted Water Tank Kit <i>SSL: 312GR - 318G</i> <i>CTL: 317G</i> <i>30 gal. [113.5 l] capacity</i> <i>Use with nozzle kit</i>		1,328.00
	AT435129	Roof-Mounted Water Tank Kit		1,829.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

DB84 DOZER BLADE

Equipment for Base Machine

Overall width: 84.0 in. (2133 mm)
 Length: 31.5 in. (800 mm)
 Blade height: 24.0 in. (610 mm)
 Blade width (full angle): 74.1 in. (1882 mm)
 Cutting edge (reversible): 0.625 x 6 in. (16 x 153 mm)

Degrees of angle: 30, right or left
 Degrees of tilt: 10, up or down
 Adjustable skid shoe: Standard
 Comes Standard with 3 Pin Wire Harness

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9780T	DB84 DOZER BLADE <i>For:</i> 318G-324G SS 318E-326E SS 317G, 325G CTL 319E, 323E CTL AT428072 hydraulic quick coupler adapter kit is available to adapt all HIGH FLOW E series SSL and CTL machines to standard flow attachment couplers.	6,375.00
-------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

KV21995	12 Volt Demonstration Kit	320.00
KV25224	12 Volt Receptacle Kit (with Traditional Controls) (300 Series) <i>3-pin connector</i>	181.00
AT336190	14 Pin Wire Harness Adapter (300 Series) <i>For use when equipped with an Attachment Control (with Traditional Controls), AT320590</i> <i>For use when equipped with an Eight Button Control Handle, AT320590</i>	See Parts
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT348477	Attachment Control (with E-H Joystick Controls)	265.00
AT348475	Attachment Control (with Foot, Hand Controls)	732.00
AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>	245.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990). Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

DB96 DOZER BLADE

Equipment for Base Machine

Overall width: 96.0 in. (2438 mm)
 Length: 31.5 in. (800 mm)
 Blade height: 24.0 in. (610 mm)
 Blade width (full angle): 84.7 in. (2151 mm)
 Cutting edge (reversible): 0.625 x 6 in. (16 x 153 mm)

Degrees of angle: 30, right or left
 Degrees of tilt: 10, up or down
 Adjustable skid shoe: Standard
 Comes Standard with 3 Pin Wire Harness

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9790T		DB96 DOZER BLADE <i>For:</i> 328E-332E SS 330G-332G SS 329E-333E CTLs 331G-333G CTLs AT428072 hydraulic quick coupler adapter kit is available to adapt all HIGH FLOW E series SSL and CTL machines to standard flow attachment couplers.		6,894.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

KV21995	12 Volt Demonstration Kit	320.00
KV25224	12 Volt Receptacle Kit (with Traditional Controls) (300 Series) <i>3-pin connector</i>	181.00
AT336190	14 Pin Wire Harness Adapter (300 Series) <i>For use when equipped with an Attachment Control (with Traditional Controls), AT320590</i> <i>For use when equipped with an Eight Button Control Handle, AT320590</i>	See Parts
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT348477	Attachment Control (with E-H Joystick Controls)	265.00
AT348475	Attachment Control (with Foot, Hand Controls)	732.00
AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>	245.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990). Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

GS60 SCRAP GRAPPLE BUCKET

Equipment for Base Machine

TO BE DELIVERED

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7870T		GS60 SCRAP GRAPPLE BUCKET <i>For:</i> 312-318G SS CT315 CTL <i>Includes cylinder stop kit required for compatibility with large frame G-Series (330G, 331G, 332G, 333G) and some competitive brands.</i>		3,976.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT312692		2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
KV23054		Bolt on Side Plates for Scrap Grapple		166.00
AT475186		Cylinder Stop Kit		30.00
AT425249		Demolition Door Kit		936.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GS66B SCRAP GRAPPLE

Equipment for Base Machine

Features:

Two independent action grapples with integrated open stop
1.375 in. [35 mm] diameter
greaseable, hardened pivot pins
Improved hose routing to protect hydraulics
Enhanced construction throughout grapple
Predrilled cutting edge for bolt-on options
Specifications:
Skid steer coupler attachment

interface

1/2 in. hydraulic quick couplers
1070 lb. [485 kg] overall weight
66 in. [1675 mm] overall width
37.4 in. [950 mm] grapple opening at tips
40.75 in. [1035 mm] grapple opening
Cylinder Specifications:
1.4 in. [36 mm] rod diameter
2.5 in. [64 mm] bore diameter
8.1 in. [206 mm] stroke length
Optional Equipment:

Bolt-on side plates for increased capacity

Bolt-on straight or serrated cutting edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05S1T	GS66B SCRAP GRAPPLE <i>For use on the following models:</i> <i>SSL: 312GR - 318G</i> <i>CTL: 317G - 325G</i> <i>Requires machine equipped with boom mounted hose guide</i> <i>Rear counterweight may improve machine stability while operating</i>	4,096.00
-------	---	----------

DEALER-INSTALLED KITS

BYT10674	Kits & Accessories Bolt-on Side Plates	180.00
----------	--	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GS72B SCRAP GRAPPLE

Equipment for Base Machine

Features:

Two independent action grapples with integrated open stop
1.375 in. [35 mm] diameter
greaseable, hardened pivot pins
Improved hose routing to protect hydraulics
Enhanced construction throughout grapple
Predrilled cutting edge for bolt-on options
Specifications:
Skid steer coupler attachment

interface

1/2 in. hydraulic quick couplers
1110 lb. [505 kg] overall weight
72 in. [1830 mm] overall width
37.4 in. [950 mm] grapple opening at tips
40.75 in. [1035 mm] grapple opening
Cylinder Specifications:
1.4 in. [36 mm] rod diameter
2.5 in. [64 mm] bore diameter
8.1 in. [206 mm] stroke length
Optional Equipment:

Bolt-on side plates for increased capacity

Bolt-on straight or serrated cutting edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05T1T	GS72B SCRAP GRAPPLE	4,216.00
	<i>For use on the following models:</i>	
	<i>SSL: 318G - 332G</i>	
	<i>CTL: 317G - 325G</i>	
	<i>Requires machine equipped with boom mounted hose guide</i>	
	<i>Rear counterweight may improve machine stability while operating</i>	

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT10674	Bolt-on Side Plates	180.00
	Miscellaneous	
T385220	72 in. Bolt-on Serrated Cutting Edge	See Parts

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GS78B SCRAP GRAPPLE

Equipment for Base Machine

Features:

Two independent action grapples with integrated open stop
1.375 in. [35 mm] diameter
greaseable, hardened pivot pins
Improved hose routing to protect hydraulics
Enhanced construction throughout grapple
Predrilled cutting edge for bolt-on options
Specifications:
Skid steer coupler attachment

interface

1/2 in. hydraulic quick couplers
1150 lb. [520 kg] overall weight
78 in. [1980 mm] overall width
37.4 in. [950 mm] grapple opening at tips
40.75 in. [1035 mm] grapple opening
Cylinder Specifications:
1.4 in. [36 mm] rod diameter
2.5 in. [64 mm] bore diameter
8.1 in. [206 mm] stroke length
Optional Equipment:

Bolt-on side plates for increased capacity

Bolt-on straight or serrated cutting edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05U1T	GS78B SCRAP GRAPPLE	4,515.00
	<i>For use on the following models:</i>	
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 333G</i>	
	<i>CWL: 204L - 324L *requires skid steer style coupler</i>	
	<i>Requires SSL / CTL equipped with boom mounted hose guide</i>	
	<i>Rear counterweight may improve machine stability while operating</i>	

DEALER-INSTALLED KITS

	Kits & Accessories	
BYT10674	Bolt-on Side Plates	180.00
	Miscellaneous	
T385219	78 in. Bolt-on Serrated Cutting Edge	See Parts

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GS84B SCRAP GRAPPLE

Equipment for Base Machine

Features:

Two independent action grapples with integrated open stop
1.375 in. [35 mm] diameter
greaseable, hardened pivot pins
Improved hose routing to protect hydraulics
Enhanced construction throughout grapple
Predrilled cutting edge for bolt-on options
Specifications:
Skid steer coupler attachment

interface

1/2 in. hydraulic quick couplers
1185 lb. [540 kg] overall weight
84 in. [2135 mm] overall width
37.4 in. [950 mm] grapple opening at tips
40.75 in. [1035 mm] grapple opening
Cylinder Specifications:
1.4 in. [36 mm] rod diameter
2.5 in. [64 mm] bore diameter
8.1 in. [206 mm] stroke length
Optional Equipment:

Bolt-on side plates for increased capacity

Bolt-on straight or serrated cutting edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05V1T	GS84B SCRAP GRAPPLE	5,071.00
	<i>For use on the following models:</i>	
	SSL: 320G - 332G	
	CTL: 325G - 333G	
	CWL: 204L - 324L *requires skid steer style coupler	
	<i>Requires SSL / CTL equipped with boom mounted hose guide</i>	
	<i>Rear counterweight may improve machine stability while operating</i>	

DEALER-INSTALLED KITS

BYT10674	Kits & Accessories Bolt-on Side Plates	180.00
----------	--	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GR72B ROCK / BRUSH GRAPPLE

Equipment for Base Machine

Features:

Two independent action grapples with integrated open stop
1.375 in. [35 mm] diameter
greaseable, hardened pivot pins
Weld-in serrated cutting edge for difficult ground conditions
Improved hose routing to protect hydraulics
Enhanced construction throughout grapple
Specifications:

Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers
1165 lb. [530 kg] overall weight
72 in. [1830 mm] overall width
37.4 in. [950 mm] grapple opening at tips
40.75 in. [1035 mm] grapple opening
20 tines at 3 in. [75 mm] spacing
Cylinder Specifications:

1.4 in. [36 mm] rod diameter
2.5 in. [64 mm] bore diameter
8.1 in. [206 mm] stroke length

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05Q1T	GR72B ROCK / BRUSH GRAPPLE <i>For use on the following models:</i> <i>SSL: 312GR - 332G</i> <i>CTL: 317G - 325G</i> <i>Requires machine equipped with boom mounted hose guide</i> <i>Rear counterweight may improve machine stability while operating</i>	4,335.00
-------	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

GR84B ROCK / BRUSH GRAPPLE

Equipment for Base Machine

Features:	1/2 in. hydraulic quick couplers	2.5 in. [64 mm] bore diameter
Two independent action grapples with integrated open stop	1255 lb. [570 kg] overall weight	8.1 in. [206 mm] stroke length
1.375 in. [35 mm] diameter greaseable, hardened pivot pins	84 in. [2135 mm] overall width	
Improved hose routing to protect hydraulics	37.4 in. [950 mm] grapple opening at tips	
Enhanced construction throughout grapple	40.75 in. [1035 mm] grapple opening	
Specifications:	23 tines at 3 in. [75 mm] spacing	
Skid steer coupler attachment interface	Cylinder Specifications:	
	1.4 in. [36 mm] rod diameter	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

05R1T	GR84B ROCK / BRUSH GRAPPLE	5,064.00
	<i>For use on the following models:</i>	
	<i>SSL: 320G - 332G</i>	
	<i>CTL: 325G - 333G</i>	
	<i>CWL: 204L - 324L *requires skid steer style coupler</i>	
	<i>Requires SSL / CTL equipped with boom mounted hose guide</i>	
	<i>Rear counterweight may improve machine stability while operating</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

HH20C HYDRAULIC HAMMER

Equipment for Base Machine

Performance:

Blows Per Minute: 800 - 3000
Flow Requirements:
6.6 - 14.5 gpm (25 - 55 lpm)

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

Includes Moil Point.

Operating Pressure:

1305 - 2175 psi
Moil Tool Point 1.9 in.
(48 mm) Diameter

Note: Units Must be
Equipped with Demolition or
Severe Duty Door and
Shoulder Belt Kits
or Protection Screens.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0C80T	HH20C HYDRAULIC HAMMER	7,188.00
	<i>For use on the following models:</i>	
	<i>Compact Excavators: 17G, 26G and 35G</i>	

MOUNTING BRACKETS

1000	Less Mounting Bracket	No Added Cost
1002	Mounting Bracket, 17 Compact Excavator	445.00
1003	Mounting Bracket, 26-35 Compact Excavator	591.00

DEALER-INSTALLED KITS

Adapters & Mounting Frames

AT458340	Mounting Bracket, 17 Compact Excavator	424.00
AT458341	Mounting Bracket, 26-35 Compact Excavator	591.00

Kits & Accessories

AT312692	2-inch Seat Belt with Shoulder Harness for Suspension Seat	317.00
AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00
AT425249	Demolition Door Kit	936.00
AT417602	Severe Duty Door	3,169.00

REFERRAL ATTACHMENTS

G.r.mfg.

G.R. Manufacturing, Inc.

** Kits listed below must be ordered through John Deere.*

** F.O.B. Trussville, Alabama*

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

HH20C HYDRAULIC HAMMER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
REFERRAL ATTACHMENTS Continued...				
<i>* All kits include installation instructions</i>				
<i>* All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc.</i>				
<i>G.R. Manufacturing, Inc. 4800 Commerce Drive Trussville, Alabama 35173 Phone: (800)841-8001 Fax: (205)655-8005</i>				
AT318959		Front Protection Screen for Cab (GR#704995) (26-60 CE)		No Charge
AT318960		Front Protection Screen for Canopy (GR#704996) (26-50 CE)		No Charge
AT337084		Front Protection Screen for Canopy (GR#705155) (17 CE) <i>* Required when a Hydraulic Breaker is equipped on a 17D/17G/ZX17U Compact Excavator with a canopy. *Required when a Hydraulic Breaker is equipped on a 17D/17G/ZX17-U Compact Excavator with a Canopy.</i>		683.00
BYT10076		Front Screen, Cab (GR#705923) (17 CE)		1,129.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

HH40C HYDRAULIC HAMMER

Equipment for Base Machine

Performance:

Blows Per Minute: 700-2600
Flow Requirements:
10.6 - 18.5 gpm (40 - 70 lpm)

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

Includes Moil Point.

Operating Pressure:

1450 - 2465 psi
Moil Tool Point 2.2 in.
(56 mm) Diameter

Note: Units Must be
Equipped with Demolition or
Severe Duty Door and
Shoulder Belt Kits
or Protection Screens.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0C90T		HH40C HYDRAULIC HAMMER <i>For use on the following models:</i> <i>Skid Steer Loaders: 316G-324G, 318E, 320E and 324E</i> <i>Compact Track Loaders: 317G, 325G, 319E, 323E, and 329E</i> <i>Compact Excavators: 26G and 35G</i> <i>Backhoe Loader: 110 TLB</i>		8,405.00
-------	--	--	--	----------

MOUNTING BRACKETS

1000		Less Mounting Bracket		No Added Cost
1003		Mounting Bracket, 26-35 Compact Excavator		591.00
1001		Mounting Bracket, SSL & CTL		1,623.00

DEALER-INSTALLED KITS

	Adapters & Mounting Frames		
AT457979	Skid Steer Mounting Bracket		1,824.00
	Adapters & Mounting Frames		
AT458340	Mounting Bracket, 17 Compact Excavator		424.00
AT458341	Mounting Bracket, 26-35 Compact Excavator		591.00
	Kits & Accessories		
AT312692	2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
AT436025	Boom-Mounted Hose Guide Kit		102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>		107.00
AT425249	Demolition Door Kit		936.00
AT417602	Severe Duty Door		3,169.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

HH40C HYDRAULIC HAMMER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
REFERRAL ATTACHMENTS				
		G.r.mfg. <i>G.R. Manufacturing, Inc.</i> <i>* Kits listed below must be ordered through John Deere.</i> <i>* F.O.B. Trussville, Alabama</i> <i>* All kits include installation instructions</i> <i>* All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc.</i> <i>G.R. Manufacturing, Inc.</i> <i>4800 Commerce Drive</i> <i>Trussville, Alabama 35173</i> <i>Phone: (800)841-8001</i> <i>Fax: (205)655-8005</i>		
	AT318959	Front Protection Screen for Cab (GR#704995) (26-60 CE)		No Charge
	AT318960	Front Protection Screen for Canopy (GR#704996) (26-50 CE)		No Charge
	AT435404	Front Screen, Cab (GR#705578) (30-50G CE) <i>*Required when a Hydraulic Breaker is equipped on a Deere G-Series or Hitachi -5 Compact Excavator with a Canopy.</i>		539.00
	AT451135	Front Screen, Cab (GR#705753) (26-50 CE) <i>*Required when a Hydraulic Breaker is equipped on a Deere G-Series or Hitachi -5 Compact Excavator with a Cab.</i>		653.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

HH60C HYDRAULIC HAMMER

Equipment for Base Machine

Performance:
Blows Per Minute: 600-1800
Flow Requirements:
9.2 - 23.8 gpm (35 - 90 lpm)

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

Includes Moil Point.

Operating Pressure:
1305 - 2030 psi
Moil Tool Point 2.8 in.
(72 mm) Diameter

Note: Units Must be
Equipped with Demolition or
Severe Duty Door and
Shoulder Belt Kits
or Protection Screens.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

OCA0T		HH60C HYDRAULIC HAMMER <i>For use on the following models:</i> <i>Skid Steer Loaders: 312G-324G, 318E, 320E, 326E, 328E, 332E, 330G & 332G</i> <i>Compact Track Loaders: 317G, 325G, 319E, 323E, 329E, 333E, 331G & 333G</i> <i>Compact Excavators: 35G, 50G and 60G</i> <i>Backhoe Loader: 110 TLB</i>		10,501.00
-------	--	--	--	-----------

MOUNTING BRACKETS

1000		Less Mounting Bracket		No Added Cost
1003		Mounting Bracket, 26-35 Compact Excavator <i>For use on 35G only.</i>		591.00
1001		Mounting Bracket, SSL & CTL		1,623.00
1004		Mounting Bracket, 50-60 Compact Excavator		741.00

DEALER-INSTALLED KITS

	Adapters & Mounting Frames		
AT457979	Skid Steer Mounting Bracket		1,824.00
	Adapters & Mounting Frames		
AT458340	Mounting Bracket, 17 Compact Excavator		424.00
AT458341	Mounting Bracket, 26-35 Compact Excavator		591.00
AT460178	Mounting Bracket, 410 Backhoe Loader <i>For use on:</i> <i>310SG-SL</i> <i>310SL HL</i> <i>315SG-SL</i> <i>410G-L</i> <i>Not compatible with Backhoe Loader New Series Multi-Brand Quick Coupler.</i>		884.00
AT458342	Mounting Bracket, 50-60 Compact Excavator		741.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

2

HH60C HYDRAULIC HAMMER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
DEALER-INSTALLED KITS Continued...				
Kits & Accessories				
	AT312692	2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
	AT436025	Boom-Mounted Hose Guide Kit		102.00
	BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>		107.00
	AT425249	Demolition Door Kit		936.00
	AT458343	Mounting Bracket, 310 Backhoe Loader <i>For use on: 310K/L EP & 310G-L</i>		859.00
	AT417602	Severe Duty Door		3,169.00
 REFERRAL ATTACHMENTS				
G.r.mfg.				
<i>G.R. Manufacturing, Inc.</i>				
<i>* Kits listed below must be ordered through John Deere.</i>				
<i>* F.O.B. Trussville, Alabama</i>				
<i>* All kits include installation instructions</i>				
<i>* All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc.</i>				
 <i>G.R. Manufacturing, Inc.</i>				
<i>4800 Commerce Drive</i>				
<i>Trussville, Alabama 35173</i>				
<i>Phone: (800)841-8001</i>				
<i>Fax: (205)655-8005</i>				
	AT318959	Front Protection Screen for Cab (GR#704995) (26-60 CE)		No Charge
	AT318960	Front Protection Screen for Canopy (GR#704996) (26-50 CE)		No Charge
	ETN112936	Front Screen, Cab (GR#705577) (60 CE)		653.00
	AT435404	Front Screen, Cab (GR#705578) (30-50G CE) <i>*Required when a Hydraulic Breaker is equipped on a Deere G-Series or Hitachi -5 Compact Excavator with a Canopy.</i>		539.00
	AT451135	Front Screen, Cab (GR#705753) (26-50 CE) <i>*Required when a Hydraulic Breaker is equipped on a Deere G-Series or Hitachi -5 Compact Excavator with a Cab.</i>		653.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

HH80C Hydraulic Hammer

Equipment for Base Machine

Performance:

Blows Per Minute: 500 - 1700
Flow Requirements:
10.6-31.7 gpm (40-120 lpm)

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

Includes Moil Point.

Operating Pressure:

1305 - 2030 psi
Moil Tool Point 3.14 in.
(80 mm) Diameter

Note: Units Must be
Equipped with Demolition or
Severe Duty Door and
Shoulder Belt Kits
or Protection Screens.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

OCB0T		HH80C Hydraulic Hammer <i>For use on the following models:</i> <i>Skid Steer Loaders: 318E, 320E, 326E, 328E, 332E, 320G-332G</i> <i>Compact Track Loaders: 319E, 323E, 329E, 333E, 325G-333G</i> <i>Compact Excavators: 50G and 60G</i> <i>Backhoe Loaders: 310K/L EP, 310K/L, 310SK/SL, 310SK TMC, 315SK/SL, 325K/L, 410K/L, 410K TMC</i>		12,121.00
-------	--	--	--	-----------

MOUNTING BRACKETS

1000		Less Mounting Bracket		No Added Cost
1001		Mounting Bracket, SSL & CTL		1,623.00
1004		Mounting Bracket, 50-60 Compact Excavator		741.00
1005		Mounting Bracket, 310 Backhoe Loader <i>For use on:</i> <i>310K/L EP & 310G-L</i>		859.00
1006		Mounting Bracket, 410 Backhoe Loader <i>For use on:</i> <i>310SG-SL</i> <i>310SL HL</i> <i>315SG-SL</i> <i>410G-L</i> <i>Not compatible with Backhoe Loader New Series Multi-Brand Quick Coupler.</i>		884.00

DEALER-INSTALLED KITS

AT457979	Adapters & Mounting Frames Skid Steer Mounting Bracket	1,824.00
AT458340	Adapters & Mounting Frames Mounting Bracket, 17 Compact Excavator	424.00
AT458341	Mounting Bracket, 26-35 Compact Excavator	591.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

2

HH80C Hydraulic Hammer

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT460178	Mounting Bracket, 410 Backhoe Loader <i>For use on:</i> 310SG-SL 310SL HL 315SG-SL 410G-L <i>Not compatible with Backhoe Loader New Series Multi-Brand Quick Coupler.</i>		884.00
	AT458342	Mounting Bracket, 50-60 Compact Excavator		741.00
		Attachments & Accessories		
	AT450567	Backhoe Coupler Adapter Kit (Pin & Bushing) <i>For use on:</i> 310K/L EP & 310G-L <i>Not for use on Backhoes equipped with Bucket Coupler.</i> <i>For use on:</i> 310K/L EP & 310G-L		1,215.00
		Kits & Accessories		
	AT312692	2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
	AT450568	Backhoe Coupler Adapter Kit (Pin & Bushing) <i>For use on:</i> 310SG-SL 310SL HL 315SG-SL 410G-L <i>Not for use on Backhoes equipped with Bucket Coupler.</i> <i>For use on:</i> 310SG-SL 310SL HL 315SG-SL 410G-L		1,038.00
	AT436025	Boom-Mounted Hose Guide Kit		102.00
	BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>		107.00
	AT458343	Mounting Bracket, 310 Backhoe Loader <i>For use on:</i> 310K/L EP & 310G-L		859.00
	AT417602	Severe Duty Door		3,169.00

REFERRAL ATTACHMENTS

G.r.mfg.

G.R. Manufacturing, Inc.

* Kits listed below must be ordered through John Deere.

* F.O.B. Trussville, Alabama

* All kits include installation instructions

* All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc.

G.R. Manufacturing, Inc.

4800 Commerce Drive

Trussville, Alabama 35173

Phone: (800)841-8001

Fax: (205)655-8005

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

HH80C Hydraulic Hammer
Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
REFERRAL ATTACHMENTS Continued...				
	AT318959	Front Protection Screen for Cab (GR#704995) (26-60 CE)		No Charge
	AT318960	Front Protection Screen for Canopy (GR#704996) (26-50 CE)		No Charge
	ETN112936	Front Screen, Cab (GR#705577) (60 CE)		653.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MS60 MATERIAL / MANURE SCRAPER

Equipment for Base Machine

Features:

Units come standard with
the pull back kit installed
Rubber edges are reversible
and replaceable

Manure removal
Flood clean up
Light snow removal
Any place where pushing
material is needed
with a rubber edge

Applications include but not
limited to:

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

8500T	MS60 MATERIAL / MANURE SCRAPER <i>For use on the following models:</i> 312G-318G SS 110 TLB 300CX, 400X/400CX Loaders* <i>*Please refer to A&T Sales Manual for other requirements</i>	1,698.00
-------	---	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MS72 MATERIAL / MANURE SCRAPER

Equipment for Base Machine

Features:

Units come standard with
the pull back kit installed
Rubber edges are reversible
and replaceable

Manure removal
Flood clean up
Light snow removal
Any place where pushing
material is needed
with a rubber edge

Applications include but not
limited to:

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

8510T	MS72 MATERIAL / MANURE SCRAPER	2,255.00
	<i>For use on the following models:</i>	
	312G-324G SS	
	318E-324E SS	
	317G CTL	
	110 TLB	
	300CX, 400X/400CX Loaders*	
	<i>*Please refer to A&T Sales Manual for other requirements</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MS84 MATERIAL / MANURE SCRAPER
Equipment for Base Machine

Features:
Units come standard with
the pull back kit installed
Rubber edges are reversible
and replaceable
Applications include but not
limited to:

Manure removal
Flood clean up
Light snow removal
Any place where pushing
material is needed
with a rubber edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

8520T	MS84 MATERIAL / MANURE SCRAPER <i>For use on the following models:</i> 318E-332E SS 320G-332G SS 317G-333G CTLs 319E-333E CTLs	2,344.00
-------	---	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MS96 MATERIAL / MANURE SCRAPER
Equipment for Base Machine

Features:
Units come standard with
the pull back kit installed
Rubber edges are reversible
and replaceable
Applications include but not
limited to:

Manure removal
Flood clean up
Light snow removal
Any place where pushing
material is needed
with a rubber edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

8530T	MS96 MATERIAL / MANURE SCRAPER <i>For use on the following models:</i> 318E-332E SS 320G-332G SS 319E-333E CTLs 325G-333G CTLs	2,135.00
-------	---	----------

MH60D MULCHING HEAD

Equipment for Base Machine

Features:

Remove up to 8 in. [203 mm]
trees and 12 in. [305 mm] stumps
30 double carbide-tipped teeth
to mulch materials
Heavy-duty mulching door for
finer processing
Heavy-duty, 2-speed motor
efficiently uses available
horsepower
Hydraulic pressure gauge to
monitor performance
Adjustable, 3-position

heavy-duty push bar
Enhanced frame construction and
bolt-on skid shoes
Specifications:
Skid steer coupler attachment
interface
14-pin electrical connector
1/2 in. hydraulic quick couplers
24-45 gpm [91 170 l/min]
hydraulic flow range
2730 lb. [1240 kg] overall
weight
60 in. [1520 mm] cutting width

74 in. [1880 mm] overall width
Optional Equipment:
Knife cutting tools for smoother
cutting and finer chip size

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE*F.O.B. Dubuque, Iowa*

07A1T	MH60D MULCHING HEAD <i>For use on the following models:</i> SSL: 330G - 332G CTL: 331G - 333G - Requires machine equipped with high flow hydraulics - Requires machine equipped with 14-pin electrical connector. - Requires applicable severe-duty door - Requires applicable operator protection - For optimal performance, recommend non-hydraulic self-leveling machines - Rear counterweight may improve machine stability while operating	36,623.00
-------	--	-----------

DEALER-INSTALLED KITS

AT433505	Kits & Accessories Knife Tool Kit	201.00
----------	---	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MP66B MULTI-PURPOSE BUCKET

Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0AQ0T		MP66B MULTI-PURPOSE BUCKET <i>For use on the following models:</i> 312-324G SSL 318E-324E SSL 317G CTL <i>Requires SSL / CTL equipped with boom mounted hose guide</i>		3,719.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

	Cutting Edges		
AT436470	66 in. Bolt-On Cutting Edge for MP66B		374.00
	Kits & Accessories		
AT436025	Boom-Mounted Hose Guide Kit		102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>		107.00
AT436718	Spill Guard Assembly, MP66B		194.00
	Tooth Bars		
AT436521	66 in. Tooth Bar - 7 Teeth, MP66B		825.00
AT436489	MP66 Over BOCE Toothbar, MP66B		885.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MP72B MULTI-PURPOSE BUCKET
Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0AR0T		MP72B MULTI-PURPOSE BUCKET <i>For use on the following models:</i> 312G-324G SSL 318E-328E SSL 317G, 325G CTL 319E, 323E CTL <i>Requires SSL / CTL equipped with boom mounted hose guide</i>		4,468.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

	Cutting Edges		
AT436471	Bolt-On Cutting Edge for 72 in. Bucket		381.00
	Kits & Accessories		
AT436025	Boom-Mounted Hose Guide Kit		102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>		107.00
AT436525	Side Cutter Assembly, (MP72B, MP78B, MP84B)		97.00
AT436719	Spill Guard Assembly, MP72B		199.00
	Tooth Bars		
AT436522	72 in. Tooth Bar - 7 Teeth, MP72B		710.00
AT436490	MP72 Over BOCE Toothbar, MP72B		1,005.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MP78B MULTI-PURPOSE BUCKET

Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0AS0T		MP78B MULTI-PURPOSE BUCKET <i>For use on the following models:</i> 318E-332E SSL 320G-332G SSL 317G, 325G CTL 319E-333E CTL 331G-333G CTL <i>Requires SSL / CTL equipped with boom mounted hose guide</i>		4,594.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

Cutting Edges

AT436472	78 in. Bolt-On Cutting Edge for MP78B	416.00
----------	---------------------------------------	--------

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
----------	-----------------------------	--------

BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00
----------	---	--------

AT436525	Side Cutter Assembly, (MP72B, MP78B, MP84B)	97.00
----------	---	-------

AT436720	Spill Guard Assembly, MP78B	230.00
----------	-----------------------------	--------

Tooth Bars

AT436523	78 in. Tooth Bar - 8 Teeth, MP78B	727.00
----------	-----------------------------------	--------

AT436491	MP78 Over BOCE Toothbar, MP78B	1,279.00
----------	--------------------------------	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

MP84B MULTI-PURPOSE BUCKET
Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0AT0T		MP84B MULTI-PURPOSE BUCKET <i>For use on the following models:</i> 326E-332E SSLs 330G-332G SSLs 323E-333E CTLs 325G-333G CTLs <i>Requires SSL / CTL equipped with boom mounted hose guide</i>		4,749.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

	Cutting Edges	
AT436473	Bolt-On Cutting Edge for 84 in. Bucket	494.00
	Kits & Accessories	
AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00
AT436525	Side Cutter Assembly, (MP72B, MP78B, MP84B)	97.00
AT436721	Spill Guard Assembly, MP84B	244.00
	Tooth Bars	
AT436524	84 in. Tooth Bar - 8 Teeth, MP84B	856.00
AT436492	MP84 Over BOCE Toothbar, MP84B	1,002.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

NF44 Nursery Fork
Equipment for Base Machine

WORKSITE NF44 NURSERY FORK

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, IA

0BU0T		NF44 Nursery Fork <i>For:</i> 312G-332G SS 318E-332E SS 317G-333G CTLs 319E-333E CTLs 204K-324K CWL		4,066.00
-------	--	---	--	----------

PICK ONE

1000		PRESSURE CONTROL VALVE ASSEMBLY		403.00
1001		LESS CONTROL VALVE ASSEMBLY		No Added Cost

DEALER-INSTALLED KITS

		Miscellaneous		
AT460780		Pressure Control Valve		403.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

Heavy Duty 45 In. Frame and Set of Forks
Equipment for Base Machine

45 in. Wide Heavy Duty Pallet Available
Fork Frame and Guard
Unrestricted Visibility to Fork
Tips
42 in. or 48 in. Long Fork Tines

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03J1T		Heavy Duty 45 In. Frame and Set of Forks <i>Includes 45" Heavy Duty Frame and Two Fork Set For:</i> 312G-332G SS 320E-324E SS 317G-333G CTLs 323E CTL <i>Additional tine options available.</i>		864.00
-------	--	---	--	--------

PICK ONE

1001		45" FRAME W/ 42" TINES RATED 3750 LBS <i>For:</i> 312G-324G SS 320E-324E SS 317G-323G CTLs		No Added Cost
1002		45" FRAME W/ 48" TINES RATED 3750 LBS <i>For:</i> 312G-324G SS 320E-324E SS 317G-323G CTLs		33.00
1003		45" FRAME W/ 42" TINES RATED 5500 LBS <i>For:</i> 312G-332G SS 320E-324E SS 317G-325G CTLs 323E CTL		83.00
1004		45" FRAME W/ 48" TINES RATED 5500 LBS <i>For:</i> 312G-332G SS 320E-324E SS 317G-325G CTLs 323E CTL		149.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

Heavy Duty 45 In. Frame and Set of Forks

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
1005		PICK ONE Continued... 45" FRAME W/ 48" TINES RATED 6200 LBS <i>For:</i> 312G-332G SS 320E-324E SS 317G-325G CTLs 323E CTL		241.00

DEALER-INSTALLED KITS

AT492257	Frame Kit Heavy Duty 45 in. Fork Frame (No Forks)	679.00
----------	---	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

Heavy Duty 60 in. Frame and Set of 48" Forks
Equipment for Base Machine

Heavy Duty Forks - 6,200 lb.
Load Capacity
60 in. Wide Pallet Fork Frame
and Guard
Unrestricted Visibility to Fork
Tips
48 in. Long Fork Tines Available

Fork Tine Load Capacity of 6,200
lb. per Pair
NOTE: Rear Counterweights is Not
Required, but May Enhance
Machine Stability.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03K1T		Heavy Duty 60 in. Frame and Set of 48" Forks <i>Includes 60" Frame and Two Fork Set of 48" HD Tines</i> For: 320E-324E SS 320G-332G SS 317G-333G CTLs 323E CTL		1,415.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

	Frame Kit			
AT492262	Heavy Duty 60 in. Fork Frame (No Forks)			989.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

Severe Duty Pallet Fork Equipment for Base Machine

Frame has option of 45 inch or 60 inch width of the rails
Forks have options of 48 inch or 60 inch length of tines
8800 lb. rating on forks (per pair of tines)
Robust, two-piece walk-through brick guard

Optional bolt-on brick guard kit to complete backrest
Unrestricted Visibility to Fork Tips

Rear Ballast is not required but may enhance machine stability.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
06U0T		Severe Duty Pallet Fork <i>For:</i> 330G-332G SS 331G-333G CTLs		1,622.00
PICK KIT				
1000		45" Severe Duty Fork Frame		No Added Cost
1001		60" Severe Duty Fork Frame		200.00
PICK ONE				
2000		48" TINES ITA CLASS 3B		300.00
2001		60" TINES ITA CLASS 3B		400.00
BRACKET KITS				
9001		Bolt-On Walk-Through Brick Guard		124.00
DEALER-INSTALLED KITS				
Fork Kit				
AT468499		48 in. Fork Tines ITA Class 3B		300.00
AT470816		60 in. Fork Tines ITA Class 3B		400.00
Frame Kit				
BYT10071		Severe Duty 45 in. Fork Frame (No Forks)		1,622.00
BYT10008		Severe Duty 60 in. Fork Frame (No Forks)		1,822.00
Miscellaneous				
BYT10349		Bolt-On Walk-Through Brick Guard		124.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PC4 PLATE COMPACTOR

Equipment for Base Machine

Impulse Force 4,000 lbf / 17.8 kN	Operating Pressure 2600 psi / 17930 kPa
Cycles/Minute at Regulated Flow 2,000 rpm	Pressure Relief Setting 3000 psi / 20680 kPa
Base Plate Dimensions 13 x 25 in. / 330 x 635 mm	Weight* 397 lb. / 180 kg
Compaction Area 325 in. sq. / 209550 mm sq.	Length 30.7 in. / 780 mm
Hydraulic Flow Range 9-14 gpm / 34-53 l/min	Width 13.0 in. / 330 mm
Regulated Flow 9 gpm / 34 l/min	Height* 20.3 in. / 515 mm
	*Without mounting adapter - requires respective machine mounting adapter

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03W1T		PC4 PLATE COMPACTOR <i>For:</i> 26G, 30G, 35G CE		5,616.00
-------	--	--	--	----------

PICK ONE

1000		Less mounting bracket and hoses		No Added Cost
1001		Mounting Adapter Kit <i>For use on 26G and 30G with PC4</i>		860.00
1002		Mounting Adapter Kit <i>For use on 35G with PC4</i>		882.00

DEALER-INSTALLED KITS

	Kits & Accessories		
BYT10728	Mounting Adapter Kit, PC4 (26G/30G)		860.00
BYT10828	Mounting Adapter Kit, PC4 (35G)		882.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PC7 PLATE COMPACTOR

Equipment for Base Machine

Impulse Force 6,400 lbf / 28.5kN	Operating Pressure 2000 psi /	mounting adapter
Cycles/Minute at Regulated Flow	13790 kPa	
2,000 rpm	Pressure Relief Setting 2200 psi	
Base Plate Dimensions 18 x 27.5	/ 15170 kPa	
in. / 460 x 700 mm	Weight* 600 lb. / 272 kg	
Compaction Area 499 in. sq. /	Length 35 in. / 890 mm	
322000 mm sq.	Width 18.1 in. / 460 mm	
Hydraulic Flow Range 15-20 gpm /	Height* 21.5 in. / 546 mm	
57-76 l/min	*Without mounting adapter -	
Regulated Flow 18 gpm / 68 l/min	requires respective machine	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03X1T		PC7 PLATE COMPACTOR For: 50G, 60G CE		6,739.00
-------	--	--	--	----------

PICK ONE

1000		Less mounting bracket and hoses		No Added Cost
1003		Mounting Adapter Kit For use on 50G, 60G with PC7		920.00

DEALER-INSTALLED KITS

Kits & Accessories

BYT10729		Mounting Adapter Kit, PC7 (50G/60G)		920.00
----------	--	-------------------------------------	--	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PC10 PLATE COMPACTOR

Equipment for Base Machine

Impulse Force 8,000 lbf / 35.6 kN	Operating Pressure 2000 psi / 13790 kPa
Cycles/Minute at Regulated Flow 2,000 rpm	Pressure Relief Setting 2200 psi / 15170 kPa
Base Plate Dimensions 24 x 28 in. / 610 x 710 mm	Weight* 888 lb. / 403 kg
Compaction Area 671 in. sq. / 433100 mm sq.	Length 37.0 in. / 940 mm
Hydraulic Flow Range 20-24 gpm / 76-91 l/min	Width 24.0 in. / 610 mm
Regulated Flow 21 gpm / 79 l/min	Height* 25.5 in. / 648 mm
	*Without mounting adapter - requires respective machine mounting adapter

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03Y1T	PC10 PLATE COMPACTOR <i>For:</i> 60G CE 310L/EL, 310L/HL, 410L BHL	7,863.00
-------	---	----------

PICK ONE

1000	Less mounting bracket and hoses	No Added Cost
1004	Mounting Adapter Kit <i>For use on 60G with PC10</i>	940.00
1005	Mounting Adapter Kit <i>For use on 310L/EL BHL with PC10</i>	983.00
1006	Mounting Adapter Kit <i>For use on 310SL/HL, 410L BHL with PC10</i>	1,044.00

DEALER-INSTALLED KITS

Kits & Accessories

BYT10827	Mounting Adapter Kit, PC10 (310 BHL w/Coupler)	983.00
----------	--	--------

Miscellaneous

BYT10731	Mounting Adapter Kit, PC10 (410 BHL w/Coupler)	1,044.00
BYT10863	Mounting Adapter Kit, PC10 (60G)	940.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

PR60 ANGLE POWER RAKE
Equipment for Base Machine

NOTE: 12V Receptacle Kit is
Required.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7830T		PR60 ANGLE POWER RAKE <i>For: 312G-318G SS</i>		8,913.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

KV21995	12 Volt Demonstration Kit	320.00
AT332454	12 Volt Receptacle Kit	208.00
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990).Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PR72B ANGLE POWER RAKE

Equipment for Base Machine

Box End Plates:	72 in. Rake	Control Kit is Required
Front or Rear	72 in. (1827 mm) Raking	
	Width	
Angle Control:	81 in. (2056 mm) Operating	
12V Electric Actuator	Width	
Rotate 20 Degrees Either	64 in. (1625 mm) Length	
Direction From Center	31 in. (787 mm) Height	
	8.6 in. (22 mm) Tooth	
Bi-Directional Raking	Roller Diameter	
Capability	11 gpm (42 lpm) Hydraulics	
Specifications:	NOTE: Applicable Attachment	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0264KV	PR72B ANGLE POWER RAKE	10,252.00
	For:	
	312G-332G SSL	
	318E-332E SS	
	317G, 325G CTL	
	319E, 323E CTLs	

DEALER-INSTALLED KITS

Kits & Accessories

KV21995	12 Volt Demonstration Kit	320.00
AT332454	12 Volt Receptacle Kit	208.00
KV25224	12 Volt Receptacle Kit (with Traditional Controls) (300 Series) <i>3-pin connector</i>	181.00
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT348477	Attachment Control (with E-H Joystick Controls)	265.00
AT348475	Attachment Control (with Foot, Hand Controls)	732.00
AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>	245.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990). Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PR84B ANGLE POWER RAKE

Equipment for Base Machine

Box End Plates:	84 in. Rake	Control Kit is Required
Front or Rear	84 in. (2134 mm) Raking	
	Width	
Angle Control:	93 in. (2362 mm) Operating	
12V Electric Actuator	Width	
Rotate 20 Degrees Either	64 in. (1625 mm) Length	
Direction From Center	32 in. (812 mm) Height	
	8.6 in. (220 mm) Tooth	
Bi-Directional Raking	Roller Diameter	
Capability	18 gpm (68 lpm) Hydraulics	
Specifications:	NOTE: Applicable Attachment	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

1580T		PR84B ANGLE POWER RAKE <i>For:</i> 318E-332E SS 320G-332G SSL 317G-333G CTL 319E-333E CTLs		10,835.00
-------	--	---	--	-----------

DEALER-INSTALLED KITS

	Kits & Accessories	
KV21995	12 Volt Demonstration Kit	320.00
KV25224	12 Volt Receptacle Kit (with Traditional Controls) (300 Series) <i>3-pin connector</i>	181.00
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT348477	Attachment Control (with E-H Joystick Controls)	265.00
AT348475	Attachment Control (with Foot, Hand Controls)	732.00
AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>	245.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990). Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

PR96B ANGLE POWER RAKE

Equipment for Base Machine

Box End Plates:	96 in. Rake	Control Kit is Required
Front or Rear	90 in. (2284 mm) Raking	
	Width	
Angle Control:	99 in. (2513 mm) Operating	
12V Electric Actuator	Width	
Rotate 20 Degrees Either	64 in. (1625 mm) Length	
Direction From Center	32 in. (812 mm) Height	
	8.6 in. (22 mm) Tooth	
Bi-Directional Raking	Roller Diameter	
Capability	15 gpm (57 lpm) Hydraulics	
Specifications:	NOTE: Applicable Attachment	

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0265KV	PR96B ANGLE POWER RAKE	11,650.00
	For:	
	320E-332E SS	
	320G-332G SS	
	319E-333E CTLs	
	325G-333G CTLs	

DEALER-INSTALLED KITS

Kits & Accessories		
KV21995	12 Volt Demonstration Kit	320.00
KV25224	12 Volt Receptacle Kit (with Traditional Controls) (300 Series) <i>3-pin connector</i>	181.00
AT427986	Attachment Control	423.00
AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)	469.00
AT348477	Attachment Control (with E-H Joystick Controls)	265.00
AT348475	Attachment Control (with Foot, Hand Controls)	732.00
AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>	245.00
AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990). Includes 3-pin and 14-pin connector. Replaces existing handles.</i>	743.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

R66 ROCK BUCKET
Equipment for Base Machine

3" Tine Spacing to each other to add strength.

The tine tips are fully gusseted on both sides for added durability and dependability. These buckets also incorporate a feature to hold rocks and debris in the bucket while digging.

The tine tips are also connected

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7950T		R66 ROCK BUCKET <i>For:</i> 312G-320G SSLs 318E, 320E SSLs 317G CTL		1,735.00
-------	--	---	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

R75 ROCK BUCKET
Equipment for Base Machine

3" Tine Spacing to each other to add strength.

The tine tips are fully gusseted on both sides for added durability and dependability. These buckets also incorporate a feature to hold rocks and debris in the bucket while digging.

The tine tips are also connected

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7960T		R75 ROCK BUCKET <i>For:</i> 318E-332E SSLs 320G-332G SSLs 317G-333G CTLs 319E-333E CTLs 110 TLB		1,855.00
-------	--	---	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

R84 ROCK BUCKET
Equipment for Base Machine

3" Tine Spacing to each other to add strength.

The tine tips are fully gusseted on both sides for added durability and dependability. These buckets also incorporate a feature to hold rocks and debris in the bucket while digging.

The tine tips are also connected

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7970T		R84 ROCK BUCKET <i>For:</i> 320E-332E SSLs 320G-332G SSLs 319E-333E CTLs 325G-333G CTLs		1,977.00
-------	--	--	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

RL84 ROLLER LEVEL
Equipment for Base Machine

Features:	66.7 in. (1694 mm)
2 Std Greaseable Bearings	Length
Front & Rear Bolt-on	25.6 in. (650 mm)
Cutting Edges	Height
	84 in. (2133 mm)
	Box Width
	0.5 x 6 x 84 in.
Specifications:	Front Cutting Edge
93.3 in. (2367 mm)	0.5 x 6 x 84 in.
Overall Width	Rear Cutting Edge

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

	<i>F.O.B. Dubuque, Iowa</i>	
7070T	RL84 ROLLER LEVEL <i>For:</i> 326E-332E SS 330G-332G SS 317G-331G CTLs 319E-333E CTLs	4,146.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RB72 ROLLOUT BUCKET
Equipment for Base Machine

Equipment for Base Machine

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05F1T		RB72 ROLLOUT BUCKET <i>High Dump Rollout Bucket. For use on the following models: 312G-324G SS 318E-326E SS 317G-325G CTLs 319E-323E CTLs * With the 312GR-318G, the Boom Mounted Hose Guide Kit, BYT10477, is recommended for proper hose routing. * With the E-series and 320G-333G, the Boom Mounted Hose Guide Kit, AT436025, is recommended. * For a replacement cutting edge, use the 72" Bolt-on Cutting Edge Kit, AT436471.</i>		5,012.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

	Cutting Edges	
AT436471	Bolt-On Cutting Edge for 72 in. Bucket	381.00
	Kits & Accessories	
AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RB84 ROLLOUT BUCKET
Equipment for Base Machine

Equipment for Base Machine

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	----------------	-------------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05G1T		RB84 ROLLOUT BUCKET <i>High Dump Rollout Bucket. For use on the following models:</i> 320G-332G SS 326E-332E SS 325G-333G CTLs 323E-333E CTLs 204K-324K CWLs * With the 312GR-318G, the Boom Mounted Hose Guide Kit, BYT10477, is recommended for proper hose routing. * With the E-series and 320G-333G, the Boom Mounted Hose Guide Kit, AT436025, is recommended. * For a replacement cutting edge, use the 84" Bolt-on Cutting Edge Kit, AT436473.		5,290.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Cutting Edges

AT436473	Bolt-On Cutting Edge for 84 in. Bucket	494.00
----------	--	--------

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RB96 ROLLOUT BUCKET
Equipment for Base Machine

Equipment for Base Machine

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

05H1T		RB96 ROLLOUT BUCKET <i>High Dump Rollout Bucket. For use on the following models:</i> 330G-332G SS 328E-332E SS 317G-325G CTLs 331E-333E CTLs 204K-324K CWLs * With the 312GR-318G, the Boom Mounted Hose Guide Kit, BYT10477, is recommended for proper hose routing. * With the E-series and 320G-333G, the Boom Mounted Hose Guide Kit, AT436025, is recommended. * For a replacement cutting edge, use the 96" Bolt-on Cutting Edge Kit, BYT10747.		5,557.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Cutting Edges

BYT10747	96 in. Bolt-On Cutting Edge for RB96	537.00
----------	--------------------------------------	--------

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RR72 ROOT RAKE

Equipment for Base Machine

Replaceable pin-on teeth
Greaseable pivot pins
Hardened-steel bushings
Weld-on "D" ring
Width: 1830 mm (72 in.)
Length: 780 mm (30.8 in.)

Grapple Opening: 1295 mm (51 in.)
Weight: 497 kg (1,095 lb.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03A0T	RR72 ROOT RAKE	5,574.00
	<i>For:</i>	
	318E-328E SS	
	318G-332G SS	
	319E-323E CTL	
	317G-333G CTLs	
	204K & 304K Compact Wheel Loader	

DEALER-INSTALLED KITS

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit	107.00
	<i>For: 312GR-318G</i>	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RR78 ROOT RAKE
Equipment for Base Machine

Replaceable pin-on teeth
Greaseable pivot pins
Hardened-steel bushings
Weld-on "D" ring
Width: 1980 mm (78 in.)
Length: 780 mm (30.8 in.)

Grapple Opening: 1295 mm (51 in.)
Weight: 522 kg (1,150 lb.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03B0T	RR78 ROOT RAKE <i>For:</i> 318E-332E SS 320G-332G SS 319E-333E CTLs 317G-333G CTLs 204K, 244K & 304K Compact Wheel Loader	6,033.00
-------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RR84 ROOT RAKE
Equipment for Base Machine

Replaceable pin-on teeth
Greaseable pivot pins
Hardened-steel bushings
Weld-on "D" ring
Width: 2135 mm (84 in.)
Length: 780 mm (30.8 in.)

Grapple Opening: 1295 mm (51 in.)
Weight: 553 kg (1,220 lb.)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03C0T	RR84 ROOT RAKE <i>For:</i> 326E-332E SS 330G-332G SS 323E-333E CTLs 325G-333G CTLs 204K, 244K, 304K & 324K Compact Wheel Loader	6,378.00
-------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT436025	Boom-Mounted Hose Guide Kit	102.00
BYT10477	Boom-Mounted Hose Guide Kit <i>For: 312GR-318G</i>	107.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RX72 ROTARY CUTTER

Equipment for Base Machine

Product Features:

Clear medium to heavy brush and hardwoods up to 10 in. [254 mm] in diameter

Direct drive bearing for higher efficiency and extended durability

Hydraulic valving stops blades from spinning in seconds upon shutdown

Retractable forward shield rolls back to expose blades to larger trees and falls closed for processing material and minimizing flying debris

Three blades made of 0.625 in. [15.9 mm] thick forged steel

Optimized blade carrier design for quick start-up and recovery performance

Standard pressure gauge to monitor blade load for optimal performance

Specifications:

Skid steer coupler attachment interface

1/2 in. hydraulic quick couplers
1810 lb. [820 kg] overall weight

77 in. [1960 mm] overall width
72 in. [1830 mm] cutting width

10 in. [254 mm] maximum tree diameter cutting capacity

Three 0.625 in. [15.9 mm] single bevel blades

Hydraulic Specifications:

30 - 45 gpm [114 170 l/min]

hydraulic flow range

4000 psi [28000 kPa] maximum operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

83A1T

RX72 ROTARY CUTTER

For use on the following models:

SSL: 330G 332G

CTL: 331G 333G

Requires machine equipped with high flow hydraulics

Requires applicable severe-duty door

Rear counterweight may improve machine stability while operating

11,866.00

DEALER-INSTALLED KITS

Kits & Accessories

BYT11465

Replacement Blade Kit

450.00

AT456636

Wear Plate Kit

121.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RX84 ROTARY CUTTER

Equipment for Base Machine

Product Features:

Clear medium to heavy brush and hardwoods up to 10 in. [254 mm] in diameter

Direct drive bearing for higher efficiency and extended durability

Hydraulic valving stops blades from spinning in seconds upon shutdown

Retractable forward shield rolls back to expose blades to larger trees and falls closed for processing material and minimizing flying debris

Three blades made of 0.625 in. [15.9 mm] thick forged steel

Optimized blade carrier for

improved start-up and recovery performance

Standard pressure gauge to monitor blade load for optimal performance

Specifications:

Skid steer coupler attachment interface

1/2 in. hydraulic quick couplers with 3/8 in. case drain coupler

2260 lb. [1025 kg] overall weight

89 in. [2265 mm] overall width

84 in. [2135 mm] cutting width

10 in. [254 mm] maximum tree

diameter cutting capacity

Three 0.625 in. [15.9 mm] single

bevel blades

Hydraulic Specifications:

30 - 45 gpm [114 170 l/min]

hydraulic flow range

4000 psi [28000 kPa] maximum

operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

83B1T

RX84 ROTARY CUTTER

For use on the following models:

SSL: 330G 332G

CTL: 331G 333G

Requires machine equipped with high flow hydraulics

Requires applicable severe-duty door

Rear counterweight may improve machine stability while operating

13,936.00

DEALER-INSTALLED KITS

Kits & Accessories

BYT11465

Replacement Blade Kit

450.00

BYT11426

Wear Plate Kit

132.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RC60B ROTARY CUTTER

Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

		<i>F.O.B. Dubuque, Iowa</i>		
8281T		RC60B ROTARY CUTTER <i>Requires a demolition door (Code 5201, 5203, or AT425249) or a severe-duty door installation (Code 5201, 5203, 5205, or AT348784). For: 316G-324G SS 318E-324E SS</i>		6,465.00

WHEEL KIT

1000		FRONT WHEEL KIT <i>Dealer-Installed</i>		850.00
1001		LESS FRONT WHEEL KIT		No Added Cost

DEALER-INSTALLED KITS

	Kits & Accessories		
AT312692	2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
AT425249	Demolition Door Kit <i>(313, 315, CT315) 2- or 3-inch Seat Belt with Shoulder Harness required. This is a roll up door. (313, 315, CT315) 2- or 3-inch Seat Belt with Shoulder Harness required. This is a roll up door.</i>		936.00
AT442703	Front Wheel Kit		850.00
AT442698	Pressure Gauge Kit <i>Allows operator to monitor motor inlet pressure resulting in reduced stalling and increased productivity.</i>		290.00
AT417602	Severe Duty Door <i>Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below. Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below.</i>		3,169.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

RC60B ROTARY CUTTER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT387526	Severe-Duty Door Hardware Kit. <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle. Use for D Series Models.</i> <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle.</i> <i>Use for D Series Models.</i>		174.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RC72B ROTARY CUTTER

Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8341T		RC72B ROTARY CUTTER <i>Requires a demolition door (Code 5201, 5203, or AT425249) or a severe-duty door installation (Code 5201, 5203, 5205, or AT348784). For: 318G-332G SS 320E-332E SS 317G-333G CTLs 323E- 333E CTLs</i>		6,674.00
-------	--	--	--	----------

WHEEL KIT

1000		FRONT WHEEL KIT <i>Dealer-Installed</i>		850.00
1001		LESS FRONT WHEEL KIT		No Added Cost

DEALER-INSTALLED KITS

Kits & Accessories

AT312692		2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
AT425249		Demolition Door Kit <i>(313, 315, CT315) 2- or 3-inch Seat Belt with Shoulder Harness required. This is a roll up door. (313, 315, CT315) 2- or 3-inch Seat Belt with Shoulder Harness required. This is a roll up door.</i>		936.00
AT442703		Front Wheel Kit		850.00
AT442698		Pressure Gauge Kit <i>Allows operator to monitor motor inlet pressure resulting in reduced stalling and increased productivity.</i>		290.00
AT417602		Severe Duty Door <i>Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below. Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below.</i>		3,169.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

RC72B ROTARY CUTTER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT387526	Severe-Duty Door Hardware Kit. <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle. Use for D Series Models.</i> <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle.</i> <i>Use for D Series Models.</i>		174.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

RC78B ROTARY CUTTER
Equipment for Base Machine

No Base Equipment Description.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8351T		RC78B ROTARY CUTTER <i>Requires a demolition door (Code 5201 or 5203) or a severe-duty door installation (Code 5201, 5203, 5205, or AT348784). For: 326E-332E SS 330G-332G SS 317G-333G CTLs 323E- 333E CTLs</i>		7,143.00
-------	--	---	--	----------

WHEEL KIT

1000		FRONT WHEEL KIT <i>Dealer-Installed</i>		850.00
1001		LESS FRONT WHEEL KIT		No Added Cost

DEALER-INSTALLED KITS

Kits & Accessories

AT312692		2-inch Seat Belt with Shoulder Harness for Suspension Seat		317.00
AT442703		Front Wheel Kit		850.00
AT442698		Pressure Gauge Kit <i>Allows operator to monitor motor inlet pressure resulting in reduced stalling and increased productivity.</i>		290.00
AT417602		Severe Duty Door <i>Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below. Includes windshield wiper. For ROPS Canopy units also order AT387526. Required to meet ISO 8084 Forestry Applications. Use for D and E Series Models. S/N 269401 and below.</i>		3,169.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

2

RC78B ROTARY CUTTER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	AT387526	Severe-Duty Door Hardware Kit. <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle. Use for D Series Models.</i> <i>For use with ROPS Canopy units only. Not required for cab units.</i> <i>Kit includes mounting hardware for the severe-duty door including the latch & striker, heavy-duty gas-spring cylinder, and windshield washer bottle.</i> <i>Use for D Series Models.</i>		174.00
		REFERRAL ATTACHMENTS		
		G.r.mfg. <i>G.R. Manufacturing, Inc.</i> <i>* Kits listed below must be ordered through John Deere.</i> <i>* F.O.B. Trussville, Alabama</i> <i>* All kits include installation instructions</i> <i>* All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc.</i> <i>G.R. Manufacturing, Inc.</i> <i>4800 Commerce Drive</i> <i>Trussville, Alabama 35173</i> <i>Phone: (800)841-8001</i> <i>Fax: (205)655-8005</i>		
	AT432854	Front Work Lights and Rear Light Guards		218.00
	AT437325	Lift Cylinder Hose Guards		320.00
	AT372950	Toe Guard and Door Upgrade Kit <i>Required to meet ISO 8084 Forestry Applications</i> <i>Required to meet ISO 8084 Forestry Applications</i>		565.00
	AT372948	Referral Attachments Auxiliary Hydraulic Line Quick Coupler Guard (326-332 SSLs & 329-333 CTLs High Flow)		220.00
	AT388939	Lift Cylinder Hose Guards		420.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RS72 ROTARY CUTTER

Equipment for Base Machine

Product Features:

Clear medium to heavy brush and hardwoods up to 10 in. [254 mm] in diameter

Direct drive bearing for higher efficiency and extended durability

Hydraulic valving stops blades from spinning in seconds upon shutdown

Retractable forward shield rolls back to expose blades to larger trees and falls closed for processing material and minimizing flying debris

Four alternating bevel blades are made of 0.75 in. [19.1 mm] thick high-grade steel in a

reversible design to provide a deep, self-clearing cut and long wear life.

Standard pressure gauge to monitor blade load for optimal performance

Optional bolt-on carbide stump grinder teeth for debris and ground cleanup

Specifications:

Skid steer coupler attachment interface

1/2 in. hydraulic quick couplers

2008 lb. [910 kg] overall

weight

77 in. [1960 mm] overall width

72 in. [1830 mm] cutting width

10 in. [254 mm] maximum tree

diameter cutting capacity

Four 0.75 in. [19.1 mm] double bevel reversible blades

Hydraulic Specifications:

30 - 45 gpm [114 170 l/min]

hydraulic flow range

4000 psi [28000 kPa] maximum

operating pressure

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

8342T	RS72 ROTARY CUTTER <i>Requires machine equipped with high flow hydraulics Requires applicable severe-duty door Rear counterweight may improve machine stability while operating</i>	13,445.00
	<i>For: 330G-332G SSL 331G-333G CTLs</i>	

CARBIDE TOOTH KIT

1100	CARBIDE TOOTH KIT	424.00
1101	LESS CARBIDE TOOTH KIT	No Added Cost

DEALER-INSTALLED KITS

	Kits & Accessories	
AT456608	Carbide Tooth Kit	424.00
AT456609	Replacement Blade Kit	723.00
AT456636	Wear Plate Kit	121.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RT52 ROTARY TILLER

Equipment for Base Machine

Performance:

Tills to a 6 in. (152 mm)
Depth
Standard Offset Left Making
It Useful For All Tilling
Jobs

Maximum System Pressure:

3000 psi (21 Mpa)

NOTE: Optional Scarifier
may improve performance.

Hydraulics:

Standard Flow Hydraulics
Minimum Hydraulic Flow:
18 gpm (68 lpm)
Maximum Hydraulic Flow:
28 gpm (106 lpm)

Dimensions:

Tilling Width:
52 in. (1.3m)
Overall Width:
62 in. (1.6m)
Overall Length:
48 in. (1.2m)
Overall Height:
35 in. (0.9m)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7520T	RT52 ROTARY TILLER	5,658.00
	For:	
	318E-332E SS	
	320G-332G SS	
	319E-333E CTLs	
	325G-333G CTLs	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

RT66 ROTARY TILLER

Equipment for Base Machine

Performance:	28 gpm (106 lpm)	
Tills to a 6 in. (152 mm)	Maximum System Pressure:	NOTE: Optional Scarifier
Depth	3000 psi (21 Mpa)	may improve performance.
Standard Offset Left and		
Center Position Make	Dimensions:	
It Useful For All	Tilling Width:	
Tilling Jobs	66 in. (1.7m)	
	Overall Width:	
	76 in. (1.9m)	
Hydraulics:	Overall Length:	
Standard Flow Hydraulics	48 in. (1.2m)	
Minimum Hydraulic Flow:	Overall Height:	
18 gpm (60 lpm)	35 in. (0.9m)	
Maximum Hydraulic Flow:		

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7530T	RT66 ROTARY TILLER	6,212.00
	For:	
	318E-332E SS	
	320G-332G SS	
	319E-333E CTLs	
	325G-333G CTLs	

DEALER-INSTALLED KITS

AT340330	Kits & Accessories Scarifier Kit RT66 <i>Contains 5 teeth</i>	272.00
----------	--	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SA60 SIDE DISCHARGE BUCKET

Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9090T		SA60 SIDE DISCHARGE BUCKET <i>For:</i> 312G-324G SS 318E-324E SS 317G, 325G CTL 319E-323E CTLs		5,510.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835		Counterweight, Stackable (Single Set)		363.00
KV14620		Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>		196.00
R66949Y		Yellow 42lb. Quik-Tatch Weight <i>Must be ordered in quantity of 8.</i>		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SA72 SIDE DISCHARGE BUCKET

Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9100T		SA72 SIDE DISCHARGE BUCKET <i>For:</i> 326E-332E SS 330G-332G SS 329E-333E CTLs		7,678.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835		Counterweight, Stackable (Single Set)		363.00
AT311312		Rear Weight Bracket Kit (325-332)		199.00
R66949Y		Yellow 42lb. Quik-Tatch Weight <i>Must be ordered in quantity of 8.</i>		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SD72 SIDE DISCHARGE BUCKET
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9110T		SD72 SIDE DISCHARGE BUCKET <i>For:</i> 312G-324G SS 318E-328E SS 317G, 325G CTL 319E-323E CTLs <i>Early model SD72 (below following s/n's) are not compatible with MF E-Series machines (318, 319, 320, 323E) due to bucket interference with couplers on machine.</i> ITOSD72XLB0000007		7,058.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

	Kits & Accessories		
AT348835	Counterweight, Stackable (Single Set)		363.00
AT311312	Rear Weight Bracket Kit (325-332)		199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight <i>Must be ordered in quantity of 8.</i>		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SD84 SIDE DISCHARGE BUCKET

Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9120T		SD84 SIDE DISCHARGE BUCKET <i>For:</i> 320E-332E SS 320G-332G SS 319E-333E CTLs 325G-333G CTLs <i>Early model SD84 (below following s/n's) are not compatible with MF E-Series machines (318, 319, 320, 323E) due to bucket interference with couplers on machine.</i> ITOSD84XAB0000008		9,602.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

	Kits & Accessories		
AT348835	Counterweight, Stackable (Single Set)		363.00
AT311312	Rear Weight Bracket Kit (325-332)		199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight <i>Must be ordered in quantity of 8.</i>		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AD11 SILAGE DEFACER

Equipment for Base Machine

Silage Defacer allows removal of haylage & silage from bunkers. Open design allows for great operator visibility and provides adjustable guides for depth of cut. Loosen silage while maintaining a smooth, compacted bunker space with the Silage Defacer. This unique tool pierces, separates, and rakes

without cutting or reducing the size of the silage, helping to ensure complete blending.
Cutting Width 96.9 in. (2460.6 mm)
Depth of cut 0-3 in
Reach 7 ft.
Weight 910 lb. (413 kg)
Hydraulic Flow 16-25 gpm

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03F0T	AD11 SILAGE DEFACER	6,048.00
	<i>For use on the following models:</i>	
	320G-332G SS	
	318E-332E SS	
	325G-333G CTL	
	319E-333E CTL	
	204K-324K Wheel Loader with Skid Steer Style Coupler.	

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

AD7 SILAGE DEFACER

Equipment for Base Machine

Silage Defacer allows removal of haylage & silage from bunkers. Open design allows for great operator visibility and provides adjustable guides for depth of cut. Loosen silage while maintaining a smooth, compacted bunker space with the Silage Defacer. This unique tool pierces, separates, and rakes

without cutting or reducing the size of the silage, helping to ensure complete blending.
Cutting Width 96.9 in. (2460.6 mm)
Depth of cut 0-3 in
Reach 11 ft.
Weight 1037 lb. (470 kg)
Hydraulic Flow 16-25 gpm

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

03G0T	AD7 SILAGE DEFACER <i>For use on the following models:</i> 312G-332G SS 318E-332E SS 317G-333G CTL 319E-333E CTL 204K-324K Wheel Loader with Skid Steer Style Coupler.	5,982.00
-------	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SB72H Snow Blower - High Flow
Equipment for Base Machine

No Base Equipment provided.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9550T		SB72H Snow Blower - High Flow <i>For:</i> 318E-324E SS 320G-324G SS 323E CTL 325G CTL <i>Also must order applicable 14-Pin Connector Harness from Attachments below.</i>		12,586.00
-------	--	--	--	-----------

PICK ONE

1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i> <i>For:</i> 315-320 SS 318D-320D SS 318E-320E SS 320G SS CT322 CTL 323D CTL 323E CTL 325G CTL		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>For:</i> 317-320 SS CT322 CTL		215.00
1003		14-Pin Connector Harness <i>For 300-series with E-H Joystick Controls and D-Series with Traditional Controls or E-H Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if base unit not equipped with it</i> <i>For:</i> 318D-320D SS 318E-320E SS 320G SS 323D CTL 323E CTL 325G CTL		270.00

DEALER-INSTALLED KITS

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

SB72H Snow Blower - High Flow

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
DEALER-INSTALLED KITS Continued...				
Kits & Accessories				
	AT361652	14-Pin Connector Harness (For 300-series with Traditional Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>For 300-series with 8-button handle.</i> <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>Installation Instructions T249659.</i>		210.00
	AT361654	14-Pin Connector Harness (required to connect snow blower to Skid Steer/CTL Attachment Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H.</i> <i>For 300-Series with E-H Joystick controls.</i> <i>For D-Series with E-H Joystick Controls.</i> <i>For E-Series with E-H Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped in base unit.</i> <i>Installation Instructions T250796.</i>		268.00
	AT427986	Attachment Control		423.00
	AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)		469.00
	AT348477	Attachment Control (with E-H Joystick Controls)		265.00
	AT348475	Attachment Control (with Foot, Hand Controls)		732.00
	AT320590	Attachment Control (with Foot, Hand Controls) (317-332, CT322-CT332) <i>* 14-pin connector</i> <i>* Includes 8-Button Control Handle</i>		808.00
	AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990).Includes 3-pin and 14-pin connector. Replaces existing handles.</i>		743.00
	AT361655	Control Box and Harness <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>This is for units not equipped with an Attachment Control Kit.</i> <i>Installation Instructions T249658.</i>		525.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SB78H Snow Blower - High Flow
Equipment for Base Machine

No Base Equipment provided.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9570T		SB78H Snow Blower - High Flow <i>For:</i> 318E-328E SS 320G-330G SS 323E-333E CTLs 325G-333G CTLs <i>Also must order applicable 14-Pin Connector Harness from Attachments below.</i>		12,789.00
-------	--	--	--	-----------

PICK ONE

1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i> <i>For:</i> 315-328 SS 318D-328D SS 318E-328E SS 320G-324G SS CT322-CT332 CTLs 323D-333D CTLs 323E-333E CTLs 325G CTL		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>For:</i> 317-328 SS CT322-CT332 CTLs		215.00
1003		14-Pin Connector Harness <i>Also order applicable Attachment Control Kit if base unit not equipped with it</i> <i>For:</i> 318D-328D SS 318E-328E SS 316G-332G SS 323D-333D CTLs 323E-333E CTLs 317G-333G CTLs <i>For 300-series with E-H Joystick Controls and D-Series with Traditional Controls or E-H Joystick Controls.</i>		270.00

DEALER-INSTALLED KITS

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

SB78H Snow Blower - High Flow

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
		Kits & Accessories		
	AT361652	14-Pin Connector Harness (For 300-series with Traditional Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>For 300-series with 8-button handle.</i> <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>Installation Instructions T249659.</i>		210.00
	AT361654	14-Pin Connector Harness (required to connect snow blower to Skid Steer/CTL Attachment Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H.</i> <i>For 300-Series with E-H Joystick controls.</i> <i>For D-Series with E-H Joystick Controls.</i> <i>For E-Series with E-H Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped in base unit.</i> <i>Installation Instructions T250796.</i>		268.00
	AT427986	Attachment Control		423.00
	AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)		469.00
	AT348477	Attachment Control (with E-H Joystick Controls)		265.00
	AT348475	Attachment Control (with Foot, Hand Controls)		732.00
	AT320590	Attachment Control (with Foot, Hand Controls) (317-332, CT322-CT332) <i>* 14-pin connector</i> <i>* Includes 8-Button Control Handle</i>		808.00
	AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>		245.00
	AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990).Includes 3-pin and 14-pin connector. Replaces existing handles.</i>		743.00
	AT361655	Control Box and Harness <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>This is for units not equipped with an Attachment Control Kit.</i> <i>Installation Instructions T249658.</i>		525.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SB84H Snow Blower - High Flow
Equipment for Base Machine

No Base Equipment provided.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9600T		SB84H Snow Blower - High Flow <i>For:</i> 326E-332E SS 330G-332G SS 329E-333E CTLs 331G-333G CTLs <i>Also must order applicable 14-Pin Connector Harness from Attachments below.</i>		13,786.00
-------	--	--	--	-----------

PICK ONE

1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i> <i>For:</i> 325-332 SS 326D-332D SS 326E-332E SS CT332 CTL 329D-333D CTL 329E-333E CTL		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>For:</i> 325-332 SS CT332 CTL		215.00
1003		14-Pin Connector Harness <i>For 300-series with E-H Joystick Controls and D-Series with Traditional Controls or E-H Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if base unit not equipped with it</i> <i>For:</i> 326D-332D SS 326E-332E SS 316G-332G SS 329D-333D CTLs 329E-333E CTLs 317G-333G CTLs		270.00

DEALER-INSTALLED KITS

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

SB84H Snow Blower - High Flow

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
		Kits & Accessories		
	AT361652	14-Pin Connector Harness (For 300-series with Traditional Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>For 300-series with 8-button handle.</i> <i>Also order applicable Attachment Control Kit if base unit not equipped with it.</i> <i>Installation Instructions T249659.</i>		210.00
	AT361654	14-Pin Connector Harness (required to connect snow blower to Skid Steer/CTL Attachment Controls) <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H.</i> <i>For 300-Series with E-H Joystick controls.</i> <i>For D-Series with E-H Joystick Controls.</i> <i>For E-Series with E-H Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped in base unit.</i> <i>Installation Instructions T250796.</i>		268.00
	AT427986	Attachment Control		423.00
	AT394637	Attachment Control (with E-H Joystick Controls without Joystick Buttons)		469.00
	AT348477	Attachment Control (with E-H Joystick Controls)		265.00
	AT348475	Attachment Control (with Foot, Hand Controls)		732.00
	AT320590	Attachment Control (with Foot, Hand Controls) (317-332, CT322-CT332) <i>* 14-pin connector</i> <i>* Includes 8-Button Control Handle</i>		808.00
	AT339786	Attachment Control (with Joystick Controls) (300 Series) <i>14-pin connector and 3-pin connector included</i>		245.00
	AT427985	Attachment Control Kit <i>For E series (models 318, 319, 320, 323, and 326) with manual control with Foot Controls (0900) or Hand Controls (0925) OR with EH controls (0950, 0975, 0980, and 0990).Includes 3-pin and 14-pin connector. Replaces existing handles.</i>		743.00
	AT361655	Control Box and Harness <i>For use with Snow Blowers SB60B, SB72B, SB78B, SB84B, SB72H, SB78H, SB84H</i> <i>This is for units not equipped with an Attachment Control Kit.</i> <i>Installation Instructions T249658.</i>		525.00

SB60B Snow Blower
Equipment for Base Machine

14-21 GPM

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
9712T		SB60B Snow Blower <i>For:</i> 312G-318G SS 317G CTL		7,485.00
PICK ONE				
1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i>		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		215.00
1003		14-Pin Connector Harness <i>For machines equipped with EH Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		270.00

SB72B Snow Blower
Equipment for Base Machine

14-21 GPM

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
9972T		SB72B Snow Blower <i>For:</i> 312-324G SS 318E-324E SS 317G, 325G CTL 319E-323E CTL 204K, 304K CWL		7,650.00
PICK ONE				
1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i>		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		215.00
1003		14-Pin Connector Harness <i>For machines equipped with EH Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		270.00

SB78B Snow Blower
Equipment for Base Machine

18-27 GPM

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
6981T		SB78B Snow Blower <i>For:</i> 320E-332E SS 320G-332G SS 319E-333E CTLs 331G-333G CTLs 244J CWL (must be equipped with high flow option or kit)		8,162.00
PICK ONE				
1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i>		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		215.00
1003		14-Pin Connector Harness <i>For machines equipped with EH Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		270.00

SB84B Snow Blower
Equipment for Base Machine

18-27 GPM

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
7091T		SB84B Snow Blower <i>For:</i> 324E-332E SS 324G-332G SS 323E-333E CTLs 325G-333G CTLs 244J CWL (must be equipped with high flow option or kit) 324J CWL		8,269.00
PICK ONE				
1001		Control Box and Harness <i>This is for units not equipped with an Attachment Control Kit.</i>		536.00
1002		14-Pin Connector Harness (For 300-series with Traditional Controls) <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		215.00
1003		14-Pin Connector Harness <i>For machines equipped with EH Joystick Controls.</i> <i>Also order applicable Attachment Control Kit if not equipped on base machine.</i>		270.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SP8C SNOW PUSH
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9801T		SP8C SNOW PUSH <i>For:</i> 316G-332G SS 318E-332E SS 317G-331G CTLs 319E-333E CTLs 204K, 244J, 304K, 324J CWL With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required. Includes a heavy-duty, replaceable rubber cutting edge.		3,392.00
-------	--	--	--	----------

PICK ONE

Dealer installed option.

1000		Pullback Kit SP8C Pullback Kit.		1,632.00
1001		Less Pullback Kit		No Added Cost

DEALER-INSTALLED KITS

Kits & Accessories

AT357576		ISO Adapter to Quik Tatch Coupler		1,584.00
AT440274		SP8C Pullback Kit		1,717.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

SP10C SNOW PUSH
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9371T		SP10C SNOW PUSH <i>For:</i> 326E-332E SS 330G-332G SS 319E-333E CTLs 325G-333G CTLs 204K, 244J, 304K, 324J CWL With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required. Includes a heavy-duty, replaceable rubber cutting edge.		3,801.00
-------	--	---	--	----------

PICK ONE

Dealer installed option.

1000		Pullback Kit SP10C Pullback Kit.		1,938.00
1001		Less Pullback Kit		No Added Cost

DEALER-INSTALLED KITS

Kits & Accessories

AT357576		ISO Adapter to Quik Tatch Coupler		1,584.00
AT440275		SP10C Pullback Kit		1,970.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BL6B SNOW / UTILITY BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9610T		BL6B SNOW / UTILITY BLADE <i>For:</i> 312G-318G SS 317G CTL		3,328.00
-------	--	--	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BL7B SNOW / UTILITY BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9620T		BL7B SNOW / UTILITY BLADE <i>For:</i> 312G-332G SS 318E-332E SS 317G-331G CTLs 319E-333E CTLs 110 TLB 300CX, 400X/400CX Loaders* <i>*Please refer to A&T Sales Manual for other requirements</i>		3,432.00
-------	--	--	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BL8B SNOW / UTILITY BLADE
Equipment for Base Machine

no Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9630T		BL8B SNOW / UTILITY BLADE <i>For:</i> 318G-332G SS 318E-332E SS 317G-331G CTLs 319E-333E CTLs 110 TLB 400X/400CX Loaders* <i>*Please refer to A&T Sales Manual for other requirements</i>		3,536.00
-------	--	---	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BL9B SNOW / UTILITY BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9650T		BL9B SNOW / UTILITY BLADE <i>For:</i> 318E-332E SS 320G-332G SS 319E-333E CTLs 325G-333G CTLs 204K, 244J, 304K, 324J CWL * With the 244J & 324J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.		4,202.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

AT357576	Kits & Accessories ISO Adapter to Quik Tatch Coupler	1,584.00
----------	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BL10B SNOW / UTILITY BLADE

Equipment for Base Machine

no Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

9660T		BL10B SNOW / UTILITY BLADE <i>For:</i> 324E-332E SS 324G-332G SS 319E-333E CTLs 325G-333G CTLs 204K, 244J, 304K, 324J CWL * With the 244J, the Worksite Pro Skid Steer Style Coupler, AT357576, is required.		4,991.00
-------	--	---	--	----------

DEALER-INSTALLED KITS

Kits & Accessories

AT357576	ISO Adapter to Quik Tatch Coupler	1,584.00
----------	-----------------------------------	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BV6 SNOW V BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0BY0T		BV6 SNOW V BLADE <i>For:</i> 312G-324G SS 318E-326E SS 319E-323E CTL 325G CTL		4,755.00
-------	--	--	--	----------

AT428072 Hydraulic Quick Coupler Adapter kit is available to adapt all HIGH FLOW series SSL and CTL machines to standard flow attachment couplers.

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BV8 SNOW V BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0BX0T		BV8 SNOW V BLADE <i>For:</i> 318G-332G SS 318E-332E SSL 317G-333G CTLs 319E-333E CTL		4,995.00
-------	--	---	--	----------

AT428072 Hydraulic Quick Coupler Adapter kit is available to adapt all HIGH FLOW series SSL and CTL machines to standard flow attachment couplers.

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

BV9 SNOW V BLADE
Equipment for Base Machine

No Base Equipment Description

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0BW0T		BV9 SNOW V BLADE <i>For:</i> 318G-332G SS 318E-332E SSL 317G-333G CTLs 319E-333E CTL 204-324 CWL AT428072 Hydraulic Quick Coupler Adapter kit is available to adapt all HIGH FLOW series SSL and CTL machines to standard flow attachment couplers.		5,159.00
-------	--	--	--	----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

SS30 STUMP SHREDDER

Equipment for Base Machine

Features:

Remove stumps from 8 in. [200 mm] to 28 in. [710 mm] in one pass
Easily remove larger stumps with multiple bores
Low speed, high torque planetary drive shreds stumps with less debris
Bore up to 20 in. [510 mm] into the ground
Low operating costs with

maintenance every 1000 stumps
Specifications:
Skid steer coupler attachment interface
1/2 in. hydraulic quick couplers
20-45 gpm [76 170 l/min]
hydraulic flow range
30000 lb-ft. [40670 N m] maximum output torque
1300 lb. [590 kg] overall weight
30 in. [760 mm] cutting width
47 in. [1200 mm] overall width

0.75 in. [19 mm] thick AR500 steel auger blade

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, IA

07C1T	SS30 STUMP SHREDDER <i>For use on the following models:</i> SSL: 320G - 332G CTL: 325G - 333G <i>Requires machine equipped with cab door</i> <i>Recommend machine equipped with high flow hydraulics</i> <i>Rear counterweight may improve machine stability while operating</i>	21,366.00
-------	--	-----------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

THREE-POINT HITCH ADAPTER
Equipment for Base Machine

Hookup and quickly move tractor
implements
Category 1&2 Hitch Rating

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

02C0T		THREE-POINT HITCH ADAPTER		928.00
-------	--	---------------------------	--	--------

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

10 IN. STEEL TRACKS
Equipment for Base Machine

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

9020T		10 IN. STEEL TRACKS <i>For the following units with Heavy Duty Tires: 318E-320E SS Contains Chain Binder and Strap.</i>		3,131.00
-------	--	--	--	----------

DEALER-INSTALLED KITS

	Kits & Accessories		
AT320928	2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required. * Allows tires to be mounted 2 inches further away from Skid Steer.</i>		554.00
AT351259	Bucket Offset Adapter		590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

10 IN. STEEL TRACKS

Equipment for Base Machine

Self Cleaning CasTrac Design
Replaceable Bushings, Links,
and Pads

Outside Plate is Open for
Easy Cleaning and Length
Adjustment

Heavy Duty Bushings for Long
Wear Life

Tires must be in Wide
Position when Tracks are
Installed. Wheel Spacers
are NOT Required on 317-320.

Drilled Link Holes for
Increased Strength

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

0023KV	10 IN. STEEL TRACKS <i>For the following units with Heavy Duty Tires: 312G-318G SS Contains Chain Binder and Strap.</i>	3,131.00
--------	--	----------

DEALER-INSTALLED KITS

Kits & Accessories		
AT320928	2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required. * Allows tires to be mounted 2 inches further away from Skid Steer.</i>	554.00
AT345942	3/4 in. Wheel Spacer Kit (Required for 313-315) <i>* For special applications when increased track clearance is required. * Allows tires to be mounted 3/4 inches further away from Skid Steer.</i>	1,378.00
AT340611	Boom Stop Kit (Required for 313-315)	154.00
AT351259	Bucket Offset Adapter	590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

12 IN. STEEL TRACKS / 320 & 324E

Equipment for Base Machine

Self Cleaning CasTrac Design
Replaceable Bushings, Links,
and Pads

Outside Plate is Open for
Easy Cleaning and Length
Adjustment

Heavy Duty Bushings for Long
Wear Life

Tires must be in Wide
Position when Tracks are
Installed. Wheel Spacers
are NOT Required on 320.

Drilled Link Holes for
Increased Strength

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

0024KV	12 IN. STEEL TRACKS / 320 & 324E <i>For the following units with 12 in. Heavy Duty Tires:</i> 320 SS 320D SS 320E/G SS 324E/G SS <i>Contains Chain Binder and Strap.</i>	3,434.00
--------	--	----------

DEALER-INSTALLED KITS

AT320928	Kits & Accessories 2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required.</i> <i>* Allows tires to be mounted 2 inches further away from Skid Steer.</i>	554.00
AT351259	Bucket Offset Adapter	590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

12 IN. STEEL TRACKS / 325-328 & 326D-328D

Equipment for Base Machine

Self Cleaning CasTrac Design
Replaceable Bushings, Links,
and Pads

Outside Plate is Open for
Easy Cleaning and Length
Adjustment

Heavy Duty Bushings for Long
Wear Life

Tires must be in Wide
Position when Tracks are
Installed. Wheel Spacers
are NOT Required on 325-328.

Drilled Link Holes for
Increased Strength

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

0025KV	12 IN. STEEL TRACKS / 325-328 & 326D-328D <i>For the following units with 12 in. Heavy Duty Tires:</i> 325, 328 SS 326D, 328D SS 326E, 328E SS <i>Contains Chain Binder and Strap.</i>	4,040.00
--------	---	----------

DEALER-INSTALLED KITS

AT320928	Kits & Accessories 2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required.</i> <i>* Allows tires to be mounted 2 inches further away from Skid Steer.</i>	554.00
AT351259	Bucket Offset Adapter	590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

14 IN. STEEL TRACKS

Equipment for Base Machine

Self Cleaning CasTrac Design
Replaceable Bushings, Links,
and Pads

Outside Plate is Open for
Easy Cleaning and Length
Adjustment

Heavy Duty Bushings for Long
Wear Life

Tires must be in Wide
Position when Tracks are
Installed. Wheel Spacers
are NOT Required on 325-328.

Drilled Link Holes for
Increased Strength

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

0026KV	14 IN. STEEL TRACKS <i>For the following units with 14 in. Heavy Duty Tires: 328D and 328E (No kits required). 328 Skid Steer Loaders (Requires track guard kit KV17333). 332 332D, and 332E Skid Steer Loaders (Requires axle block spacer kit KV23789). Contains Chain Binder and Strap. Recommend Tire Code: 2330 14x75 17.5 12 PR SKS Extra-Wall; Other 14" tire offers not compatible.</i>	4,545.00
--------	--	----------

DEALER-INSTALLED KITS

AT320928	Kits & Accessories 2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required. * Allows tires to be mounted 2 inches further away from Skid Steer.</i>	554.00
KV23789	Axle Blocks for 332	104.00
AT351259	Bucket Offset Adapter	590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

14 IN. STEEL TRACKS (330G & 332G)

Equipment for Base Machine

Improves Skid Steer traction
Reduces ground pressure
Adds counterbalance weight
Track pitch: 10 in. (254 mm)
Total number of pads: 42

Track weight: 1,066 lb. (484 kg)

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

9021T	14 IN. STEEL TRACKS (330G & 332G) <i>For the following units with 14 in. Heavy Duty Tires: 330G and 332G (No kits required). Contains Chain Binder and Strap. Recommend Tire Code: 2330 14x75 17.5 12 PR SKS Extra-Wall; Other 14" tire offers not compatible.</i>	4,683.00
-------	---	----------

DEALER-INSTALLED KITS

Kits & Accessories		
AT320928	2 in. Wheel Spacer Kit <i>* For special applications when increased track clearance is required. * Allows tires to be mounted 2 inches further away from Skid Steer.</i>	554.00
KV23789	Axle Blocks for 332	104.00
AT351259	Bucket Offset Adapter	590.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

TR36B TRENCHER

Equipment for Base Machine

Features:

Heavy Duty Planetary Drive
Manual Side Shift
Excellent Visibility
Indicators for Proper
Digging Control

Performance:

16 to 44 gpm
2000 to 3300 psi

Integral Quik-Tatch Mounting
Frame

NOTE: Rear Ballast is not
Required, but Will Enhance
Machine Stability During
Transport.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0011KV	TR36B TRENCHER <i>For:</i> 316G-332G SS 318E-332E SS 317G-331G CTL 319E-333E CTLs	4,490.00
--------	--	----------

MOTOR KITS

1002	16-20 gpm Motor Kit <i>For Standard Flow:</i> 313-320 SS 318D, 320D SS 318E, 320E SS CT322 CTL 319D, 323D CTLs 319E, 323E CTLs	840.00
1003	21-25 gpm Motor Kit <i>For Standard Flow:</i> 325-332 SS 326D-332D SS 326E-332E SS CT332 CTL 329D, 333D CTLs 329E, 333E CTLs	972.00
1004	27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS 318E-328E SS CT322, CT332 CTLs 323D-333D CTLs 323E-333E CTLs	2,045.00
1005	36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS 332E SS	2,075.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

2

TR36B TRENCHER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
MOTOR KITS Continued...				
CHAIN OPTIONS				
2001		Wide Standard Cup Every Station 36" x 6"		920.00
2002		Wide Standard Cup Every Station 36" x 8"		954.00
2003		36" x 10" Wide Standard Cup Every Station		1,177.00
2004		36" x 12" Wide Standard Cup Every Station		1,352.00
2005		Wide 70/30 Combo Shark Tooth 36" x 6"		1,225.00
DEALER-INSTALLED KITS				
		Kits & Accessories		
AT377714		16-20 gpm Motor Kit <i>For Standard Flow:</i> 313-320 SS 318D, 320D SS CT322 CTL 319D, 323D CTLs		854.00
AT377715		21-25 gpm Motor Kit <i>For Standard Flow:</i> 325-332 SS 326D-332D SS CT332 CTL 329D, 333D CTLs		880.00
AT377716		27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS CT322, CT332 CTLs 323D-333D CTLs		2,337.00
AT347421		36 in. x 10 in. Wide Standard Cup Every Station		980.00
AT347422		36 in. x 12 in. Wide Standard Cup Every Station		1,113.00
AT347423		36 in. x 6 in. Wide 70/30 Combo Shark Tooth		967.00
AT347419		36 in. x 6 in. Wide Standard Cup Every Station		744.00
AT347420		36 in. x 8 in. Wide Standard Cup Every Station		806.00
AT377717		36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS		2,388.00
AT348835		Counterweight, Stackable (Single Set)		363.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

3

TR36B TRENCHER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
	KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>		196.00
	AT311312	Rear Weight Bracket Kit (325-332)		199.00
	R66949Y	Yellow 42lb. Quik-Tatch Weight		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

TR48B TRENCHER

Equipment for Base Machine

Features:

Heavy Duty Planetary Drive
Manual Side Shift
Excellent Visibility
Indicators for Proper
Digging Control

Performance:

16 to 44 gpm
2000 to 3300 psi

Integral Quik-Tatch Mounting
Frame

NOTE: Rear Ballast is not
Required, but Will Enhance
Machine Stability During
Transport.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

0012KV	TR48B TRENCHER <i>For:</i> 316G-332G SS 318E-332E SS 317G-331G CTL 319E-333E CTLs	4,543.00
--------	--	----------

MOTOR KITS

1002	16-20 gpm Motor Kit <i>For Standard Flow:</i> 313-320 SS 318D, 320D SS 318E, 320E SS CT322 CTL 319D, 323D CTLs 319E, 323E CTLs	840.00
1003	21-25 gpm Motor Kit <i>For Standard Flow:</i> 325-332 SS 326D-332D SS 326E-332E SS CT332 CTL 329D, 333D CTLs 329E, 333E CTLs	972.00
1004	27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS 318E-328E SS CT322, CT332 CTLs 323D-333D CTLs 323E-333E CTLs	2,045.00
1005	36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS 332E SS	2,075.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

2

TR48B TRENCHER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
MOTOR KITS Continued...				
CHAIN OPTIONS				
2001		Wide Standard Cup Every Station 48" x 6"		1,114.00
2002		Wide Standard Cup Every Station 48" x 8"		1,235.00
2005		Wide 70/30 Combo Shark Tooth 48" x 6"		1,394.00
DEALER-INSTALLED KITS				
		Kits & Accessories		
AT377714		16-20 gpm Motor Kit <i>For Standard Flow:</i> 313-320 SS 318D, 320D SS CT322 CTL 319D, 323D CTLs		854.00
AT377715		21-25 gpm Motor Kit <i>For Standard Flow:</i> 325-332 SS 326D-332D SS CT332 CTL 329D, 333D CTLs		880.00
AT377716		27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS CT322, CT332 CTLs 323D-333D CTLs		2,337.00
AT377717		36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS		2,388.00
AT347426		48 in. x 6 in. Wide Combo Shark Tooth		1,155.00
AT347424		48 in. x 6 in. Wide Standard Cup Every Station		867.00
AT347425		48 in. x 8 in. Wide Standard Cup Every Station		942.00
AT348835		Counterweight, Stackable (Single Set)		363.00
KV14620		Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>		196.00
AT311312		Rear Weight Bracket Kit (325-332)		199.00
R66949Y		Yellow 42lb. Quik-Tatch Weight		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS

WORKSITE PRO ATTACHMENTS

1

TR60B TRENCHER

Equipment for Base Machine

Features:

Heavy Duty Planetary Drive
Manual Side Shift
Excellent Visibility
Indicators for Proper
Digging Control

Performance:

27 to 44 gpm
2000 to 3300 psi

Integral Quik-Tatch Mounting
Frame

NOTE: Rear Ballast is not
Required, but Will Enhance
Machine Stability During
Transport.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
Select One Code From Each Required Category				
BASE MACHINE				
<i>F.O.B. Dubuque, Iowa</i>				
0013KV		TR60B TRENCHER <i>For High Flow:</i> 318E-332E SS 320G-332G SS 323E-333E CTLs 325G-333G CTLs		4,666.00
MOTOR KITS				
1004		27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS 318E-328E SS CT322, CT332 CTLs 323D-333D CTLs 323E-333E CTLs		2,045.00
1005		36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS 332E SS		2,075.00
CHAIN OPTIONS				
2001		Wide Standard Cup Every Station 60" x 6"		1,300.00
2005		Wide 70/30 Combo Shark Tooth 60" x 6"		1,775.00

DEALER-INSTALLED KITS

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

2

TR60B TRENCHER

Continued

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
		DEALER-INSTALLED KITS Continued...		
		Kits & Accessories		
	AT377716	27-35 gpm Motor Kit <i>For High Flow:</i> 317-325 SS 318D-328D SS CT322, CT332 CTLs 323D-333D CTLs		2,337.00
	AT377717	36-44 gpm Motor Kit <i>For High Flow:</i> 328-332 SS 332D SS		2,388.00
	AT347428	60 in. x 6 in. Wide 70/30 Combo Shark Tooth		1,356.00
	AT347427	60 in. x 6 in. Wide Standard Cup Every Station		1,038.00
	AT348835	Counterweight, Stackable (Single Set)		363.00
	AT311312	Rear Weight Bracket Kit (325-332)		199.00
	R66949Y	Yellow 42lb. Quik-Tatch Weight		62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

VR66C SMOOTH VIBRATORY ROLLER
Equipment for Base Machine

Performance:

Powered by Standard
Auxiliary

Drum Diameter 24 in.
(61.0 cm)

Hydraulics

Drum Oscillation of +/- 15
Degrees

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

66 in. (1.7 m) Smooth Drum

7800 lbf (3538 kg)

Dynamic Force

2600 vpm @ 20 gpm

Frequency

NOTE: Rear Ballast is
Required on the 317 & 320.
Rear Ballast May Enhance
Stability on Other Models.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7760T	VR66C SMOOTH VIBRATORY ROLLER <i>For:</i> 312G-332G SS 318E-332E SS 317G-331G CTLs 319E-333E CTLs	10,033.00
-------	--	-----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

VR73C SMOOTH VIBRATORY ROLLER
Equipment for Base Machine

Performance:	Frequency
Powered by Standard	
Auxiliary	Drum Diameter - 24 in.
Hydraulics	(61.0 cm)
Drum Oscillation of +/- 15 Degrees	Quik-Tatch Mounting with
73 in. (1.8 m) Smooth Drum	1/2 in. Couplers and Hoses
8,550 lbf (3878 kg)	
Dynamic Force	NOTE: Rear Ballast May
2600 vpm @ 20 gpm	Enhance Stability.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7770T	VR73C SMOOTH VIBRATORY ROLLER	10,461.00
	For:	
	324E-332E SS	
	320G-332G SS	
	317G-333G CTLs	
	319E-333E CTLs	

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

VR84C SMOOTH VIBRATORY ROLLER
Equipment for Base Machine

Performance:	Frequency
Powered by Standard	
Auxiliary	Drum Diameter - 24 in.
Hydraulics	(61.0 cm)
Drum Oscillation of +/- 15 Degrees	Quik-Tatch Mounting with
84 in. (2.1 m) Smooth Drum	1/2 in. Couplers and Hoses
9,370 lbf (4250 kg)	
Dynamic Force	NOTE: Rear Ballast May
2600 vpm @ 20 gpm	Enhance Stability.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7780T	VR84C SMOOTH VIBRATORY ROLLER	10,925.00
	For:	
	324E-332E SS	
	324G-332G SS	
	319E-333E CTLs	
	325G-333G CTLs	

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

VR66C PADDED VIBRATORY ROLLER
Equipment for Base Machine

Performance:

Powered by Standard
Auxiliary

Hydraulics

Drum Oscillation of +/- 15
Degrees
66 in. (1.7 m) Padded Drum
7800 lbf (3538 kg)
Dynamic Force
2600 vpm @ 20 gpm
Frequency

Drum Diameter less Pads -
20 in. (51.0 cm)

Quik-Tatch Mounting with
1/2 in. Couplers and Hoses

NOTE: Rear Ballast is
Required on the 317 & 320.
Rear Ballast May Enhance
Stability on Other Models.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7790T	VR66C PADDED VIBRATORY ROLLER <i>For:</i> 312G-332G SS 318E-332E SS 317G-331G CTLs 319E-333E CTLs	10,715.00
-------	--	-----------

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
KV14620	Rear Weight Bracket Kit (317-320) <i>* Requires Eight R66949Y Weights</i>	196.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00

JOHN DEERE COMMERCIAL WORKSITE PRODUCTS
WORKSITE PRO ATTACHMENTS

1

VR73C PADDED VIBRATORY ROLLER
Equipment for Base Machine

Performance:	Frequency
Powered by Standard	
Auxiliary	Drum Diameter less Pads -
Hydraulics	20 in. (51.0 cm)
Drum Oscillation of +/- 15	
Degrees	Quik-Tatch Mounting with
73 in. (1.8 m) Padded Drum	1/2 in. Couplers and Hoses
8,550 lbf (3878 kg)	
Dynamic Force	NOTE: Rear Ballast May
2600 vpm @ 20 gpm	Enhance Stability.

Code	Attachment Identifier	Description	WEIGHT LBS.	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

F.O.B. Dubuque, Iowa

7800T	VR73C PADDED VIBRATORY ROLLER	11,156.00
	For:	
	324E-332E SS	
	324G-332G SS	
	317G-333G CTLs	
	319E-333E CTLs	

DEALER-INSTALLED KITS

Kits & Accessories

AT348835	Counterweight, Stackable (Single Set)	363.00
AT311312	Rear Weight Bracket Kit (325-332)	199.00
R66949Y	Yellow 42lb. Quik-Tatch Weight	62.00