

Thomas Bus Sales - Trailer Specifications and Pricing

Dump Trailer #1 - 18CRDPBCKLC-100G

Bid Price: \$10,473.00

Gooseneck Dump Trailer (2 5/16 inch Coupler with adjustable height)
Integrated side body stiffening system
Integrated tarp system
All LED lights
Minimum GVWR (LBS) 14,000
Minimum GVWR per axle (LBS) 7,000
Electric brakes on all wheels
Mounted full size spare tire
Hydraulic Scissor Lift
Overall Length Minimum 16.75 feet (201 inches) Maximum 18.75 feet (225 inches)*
Bed Width Minimum 6.666 feet (80 inches) Maximum 7 feet (84 inches)*
Bed Length 14 feet (168 inches)*
Bed Height Minimum 2 feet (24 inches) Maximum 2 feet (24 inches)*
Minimum 10 gauge steel bed
Two drop legs jacks
Rear double doors and spreader gate combination Two
o ramps (integrated storage on trailer)
Remote dump option

Dump Trailer #2 - 18CRDPBDSLEE-100G

Bid Price: \$8,830.00

Integrated side body stiffening system
Integrated tarp mount
All LED light s
Four wheel electric brake s
Hydraulic lift with remote
Minimum GVWR (LBS) 14,000
Minimum GVWR per axle (LBS) 7,000
Minimum Payload Single Ram (LBS) 9,990
Overall Length Minimum 16.75 feet (201 inches) Maximum 19.33 feet (232 inches)
Bed Width Minimum 6 feet (72 inches) Maximum 7 feet (84 inches)
Bed Length Minimum 12 feet (144 inches) Maximum 14 feet (168 inches)
Bed Height Minimum 1.67 feet (24 inches) Maximum 2 feet (26 inches)
Deck Minimum 10-gauge steel
Barn Door Gate
Ramps Minimum GVWR (LBS) 3,000 each

Thomas Bus Sales - Trailer Specifications and Pricing

Dump Trailer #4 - 18CRDPBMTSCH-100G

Bid Price: \$7,668.00

Sure-Trac SD Low Profile Dump
6 foot x 12 foot Single Ram Model STK7212D IR-B-10
Integrated side body stiffening system
Integrated tarp mount
Hydraulic Lift
All LED light s
GVWR (LBS) 9,990
GVWR per axle (LBS) 5,000
Payload Single Ram (LBS) 6,800
Overall Length 16.75 feet (201 inches)
Bed Width 6 feet (72 inches)
Bed Length 12 feet (144 inches)
Bed Height 1.67 feet (20 inches)
Coupler Height 1.5 feet 18 inch inches)

Dump Trailer #5 -18CRDPBTBAST-100G

Bid Price: \$9,156.00

14 Foot Dump Trailer
Integrated side body stiffening system
Integrated tarps mount with tarp kit All
LED lights
Four-wheel electric brakes
Hydraulic lift with remote
Minimum GVWR (LBS) 14,000
Minimum GVWR per axle (LBS) 7,000
Minimum Payload Single Ram (LBS) 9,990
Overall Length Minimum 16.75 feet (201 inches) Maximum 19.33 feet (232 inches)
Bed Width Minimum 7 feet {84 inches)
Bed Length Minimum 14 feet (168 inches)
Bed Height Minimum 1.67 feet (24 inches) Maximum 2 feet (26 inches)
Deck Minimum 10-gauge steel
Barn Door Gate
Ramps Minimum GVWR (LBS) 3,000 each

Dump Trailer #7

12' Bid Price : \$8,830.00

14' Bid Price: \$9,156.00

12 foot and 14 foot Dump Trailers
Integrated side body stiffening system
Integrated tarps mount with tarp kit All
LED lights
Four wheel electric brakes
Hydraulic lift with remote
Minimum GVWR {LBS) 14,000
Minimum GVW R per axle (LBS) 7,000
Minimum Pay load Single Ram (LBS) 9,990
Overall Length Minimum 16.75 feet (201 inches) Maximum 19.33 feet (232 inches)

Thomas Bus Sales - Trailer Specifications and Pricing

Dump Trailer #7 (Cont.)

Bed Width Minimum 6 feet {72 inches} Maximum 7 feet {84 inches}
Bed Length Minimum 12 feet {144 inches} Maximum 14 feet {168 inches}
Bed Height Minimum 1.67 feet {24 inches} Maximum 2 feet {26 inches}
Deck Minimum 10-gauge steel
Barn Door Gate
Ramps Minimum GVWR {LBS} 3,000 each

Dump Trailer #8 - 19CRDPBKDUYS-100G

Bid Price: \$9,156.00

14 Foot Dump Trailer
Integrated side body stiffening system
Integrated tarps mount with tarp kit All
LED lights
Four-wheel electric brakes
Hydraulic lift with remote
Minimum GVWR (LBS) 14,000
Minimum GVWR per axle {LBS} 7,000
Minimum Payload Single Ram {LBS} 9,990
Overall Length Minimum 16.75 feet {201 inches} Maximum 19.33 feet {232 inches}
Bed Width Minimum 82 inches
Bed Length Minimum 168 inches
Bed Height Minimum 1.67 feet {24 inches} Maximum 2 feet {26 inches}
Deck Minimum 10-gauge steel
Barn Door and Spreader Gate
Ramps Minimum GVWR (LBS) 3,000 each

Dump Trailer #9 - 19CRDWBKHENN-100G

Bid Price: \$15,053.00

Midsota Versadump HV-14
GVWR 15,400
Axles 7000 lbs.
Brakes self-adjusting electric on all wheels
Bed width 82 inch
Bed height 25 inch
Cross member spacing 16-inch
Coupler 2 5/16 inch easy latch
12,000 Hydraulic power tongue jack
Poly toolbox
Tires 16 inch E range radial 235/80R16
Wheel 16 inch 8 bolt
Spare tire and carrier
Scissor lift hoist
Floor 3/16 inch one piece
Sides 1/8 inch X 24 inch tall
Swing side door
3 way double door rear gate
Tuck under ramps and carriers

Thomas Bus Sales - Trailer Specifications and Pricing

Dump Trailer #9 - 19CRDW BKHENN-100 G (Cont.)

4 D ring tie downs
LED lights
110V on-board charger
Paint PPG (Black)
5 year frame warranty
Wireless remote for dumpbox
Rear drop legstands
Pallet fork holder
Ro ll tarp kit

Dump Trailer #11 - 19CRDPBTBAST00G

Bid Price: \$9,156.00

14 Foot Dump Trailer
Integrated side body stiffening system
Integrated tarps mount with tarp kit All
LEDlights
Four w heel electric brakes
Hydraulic lift with remote
Minimum GVWR (LBS) 14,000
Minimum GVWR per axle (LBS) 7,000
Minimum Payload Single Ram (LBS) 9,990
Overall Length Minimum 16.75 feet (201 inches) Maximum 19.33 feet (232 inches)
Bed Width Minimum 7 feet (84 inches)
Bed Length Minimum 14 feet (168 inches)
Bed Height Minimum 1.67 feet (24 inches) Maximum 2 feet (26 inches)
Deck Minimum 10-gauge steel
Barn Door Gate
Ramps Minimum GVWR (LBS) 3,000 each

Thomas Bus Sales - Trailer Specifications and Pricing

Equipment Trailer #1 - 18CRDPBCKELC-101G

Bid Price: \$13,181.00

Gooseneck Equipment Trailer (2 5/16 inch Coupler with adjustable height)
I-Beam mainframe, riser, and neck
All LED lights
Minimum GVWR (LBS) 25,000
Minimum GVWR per axle (LBS) 10,000 (5 year axle warranty)
Two oil bath breaks axles (LBS) 12,000
Eight radial tires
Electric breakaway kit with charger
Sealed wire harness with 7-way RV plug
Bed Width Minimum 12.75 feet (102 inches)
Bed Length Minimum 25 feet (300 inches) with 5 foot (60 inches) beaver tail
Bed rub rails and stake pockets
Minimum 2 inch treated wood deck
Minimum 10 gauge steel bed
Two rope legs jacks
Two ramps (integrated storage on trailer)
Locking toolbox and chain holder
Safety chains

Equipment Trailer #2 - 18CRDWBHVNW -100G

Bid Price: \$14,001.00

Gooseneck Equipment Trailer (2 5/16 inch Coupler with adjustable height)
I-Beam mainframe, riser, and neck
All LED lights
Minimum GVWR (LBS) 24,000
Minimum GVWR per axle (LBS) 10,000 (5 year axle warranty)
Two oil bath breaks axles (LBS) 12,000
Eight radial tires plus spare
Electric breakaway kit with charger
Sealed wire harness with 7-way RV plug
Bed Width Minimum 8 1/2 feet (102 inches)
Bed Length Minimum 28 feet (336 inches) with 5-foot Dovetail
Bed rub rails and stake pockets
Minimum 2 inch treated wood deck
Two-drop legs jacks and Two flip over mega ramps
Locking toolbox and chain holder
Safety chains

Thomas Bus Sales - Trailer Specifications and Pricing

Equipment Trailer #3 - 19CRDFBCSCHN-100

Bid Price: \$9,197.00

Single Wheel Tandem Axle Gooseneck Trailer
14GN-20+5 Specifications
102 inch overall width
20-foot deck plus 5 foot dovetail
G.V.W.R. 15,900#
G.A.W. R. (Ea. Axle) (2) 7,000#
Nev-R-Adjustor equivalent Electric Brakes on all Hubs
Suspension Multi-Leaf Spring with Equalizer
Coupler 2 5/16 inch Ball Adj. Pipe
Tires ST235/ 80 R- 16 Load Range E
Safety chains 3/ 8 inch Grd. 70 w/ Safety Latch Hook (2 each) Wheels
16 inch x 6 inch Heavy White, 8 Bolt
Jacks Dual 12,000# Drop Leg Side Wind (Bolted On)
Lights L.E.D. D.O.T. Stop, Tail, Turn & Clearance Floor
2 inch Treated Pine or Douglas Fir
Neck 12 inch I-Beam
Frame 12 inch I-Beam
Electric plug 7-Way RV
Cross members 3 inch Channel
Side rail 5 inch Channel w/ Rub Rail, Tie Down Pockets on 24 inch Center & Chain Spools
Dovetail 5 foot Cleated Dovetail w/5 foot Mega Ramps
Lockable toolbox
Professional smooth superior quality protective finish

Equipment Trailer #5 - 19CRDWBVANW-100G

Bid Price: \$17,004.00

25PH 28+5 Trailer Specifications
102 inch x 28 foot x 5 foot HD Tandem Dual Wheel Pintle Trailer
AXLE (2) 12,000# Dual Wheel w/ Electric Brakes (Oil Bath)
JACK Dual Single -Speed Drop-Leg Jacks
RAMPS (2) 5 MEGA Ramps
TIRE ST235/ 80 R-16 Load Range E Dual
FLOOR 2 inch Treated Pine or Douglas Fir
FRAME 12 inch I-Beam, 19#
WHEEL 16 inch x 6 inch; Dual Wheel 8 Bolt
FINISH Superior Quality Highly Decorative and Protective Finish.
LIGHTS L.E.D. D.O.T. Stop, Tail, Turn & Clearance
TONGUE 12 inch I-Beam, 19#
COUPLER 3 inch ID Pintle Ring
G.V.W.R. 25,900#
TOP RAIL NONE
ELEC. PLUG 7-Way RV
HITCH TYPE Pintle Hitch
SIDE RAILS 8 inch Channel w/ Rub Rail, Tie Down
Pockets on 24-inch Centers, and Chain Spools
SUSPENSION Heavy Duty 30,000# Adjustable
CROSSMEMBERS 3 inch Channel
SAFETYCHAINS 3/ 8 inch Grd. 70 w/ Safety Latch Hook (2 each)

Thomas Bus Sales - Trailer Specifications and Pricing

Equipment Trailer #5 - 19CRDWBVANW -100G (Cont.)

BODY Lockable Lid Over Tool Storage In Tongue
Low Profile Bed, Pierced- Beam Frame
(2) Side Bed Steps
3/8 inch Heavy Duty Rub Rail
Tie Down Pockets Along Sides, 24 inch On Center
1-1/4 inch Pipe Chain Spools Between Tie Down Pockets
Dexter Brand Axles
Oil Bath Hubs
Forward Self Adjusting Brakes
Grommet Mount Sealed Lighting
Modular Sealed Wiring Harness
Spare Tire Mount and Spare Tire & Wheel
Complete Break-A-Way System w/Charger
Radial Tires
Mudflaps

Equipment Trailer #6 - 19CRDWBNJONE- 100G

Bid Price: \$13,181.00

Low Profile Model Size: (8 foot 6 inch x 25 foot x 5 foot) 20K Trailer Specifications
GVWR 20,000 lbs (10,000 lbs GVWR per axle)
12 inch Wide Flange, I-Beam Frame and Tongue with 3 inch Steel Channel Cross members
Channel Steel Sides with Stake Pockets & Pipe Spools with Rub Rails
5 foot Self-Cleaning Dovetail
45 inch x 57 inch Double Spring Assist Deluxe Ramps (11,500 lb. Load Rating)
Adjustable Height Gooseneck Coupler
Slipper Spring Suspension
Radial Tires on Steel Wheels, Mud Flaps
Treated, #1 Grade Wood Deck - Front and rear end caps
Full DOT Compliant, LED Lighting, Sealed Wiring Harness & 7-Way Plug
Dual 12K Rated Spring Loaded Drop Leg Jack
Lockable Chain Storage Tray
Spare Tire Mount

Equipment Trailer #7

Bid Price: \$8,847.00

Equipment Trailer (2 5/16 inch Adjustable Coupler)
All LED lights
Minimum GVWR (LBS) 16,000
Minimum GVWR per axle (LBS) 8,000 (5-year axle warranty)
2 oil bath breaks axles (LBS) 8,000
Four 14 ply radial tires
Electric breakaway kit with charger
Sealed wire harness with 7-way RV plug
Bed Width Minimum 6.83 feet (82 inches)
Bed Length Minimum 18 feet (216 inches)
Bed rub rails and stake pockets
Removable fenders

Thomas Bus Sales - Trailer Specifications and Pricing

Equipment Trailer #7 (Cont.)

Minimum 2 inch treated wood deck
Minimum 10 gauge steel bed
One-drop legs jack
Two attached ramps
Safety chain

OTHER TRAILER TYPES

Snowmobile Trailer - 18CRDPBRS6N-10 0G

Bid Price: \$3,570.00

Open trailer with a minimum bed width and length of 101 inch by 144 inch
Capable of carrying two snowmobiles safely
Tilt bed with trailer lift kit with gas shock
Minimum 13 inch steel rim wheel and tire
Salt shield
2 inch coupler with safety chains and spring loaded clips
Sealed LED Lights installed with rubber grommets to reduce vibration and protection from elements, and wiring harness to connect to the vehicle while towing.
Minimum 5/8 inch thickness Treated Marine tech plywood floor or equivalent
(2) ski hold down bars with plastic sleeves, to secure front snowmobile skis onto the trailer
(4) tie down anchor points to secure the back portion of two snowmobiles onto the trailer
Ski gates, or guides kits, for two snowmobiles for loading and unloading onto the trailer.
(2) Paddle grabbers, or track assist center guides for two snowmobiles for loading and unloading onto the trailer.
Swivel tongue Jack

Amendment #1 - Additional Trailer

Dump Trailer - Sure Trac ST9614HLODOD-B-140

Contract Price: \$10,757.00 with standard

options Base Specs with Standard Options:

96" X 14' of Bed Space
2 – 7K Axle with EZ Lube Hubs
Electric Brakes on all 4 wheels
Integrated Side Body Stiffening System
Integrated Tarp Mount
Underbody Spare Tire Tub – Spare Tire and Wheel not Included in base bid
Combo Barn Door Spreader Gate with Cambar
All LED Lights
Slipper Springs
Sealed Brake Connections
EverLink™ - High-Performance Wiring Harness
Power-Up, Gravity-Down Hydraulics (Scissor)
Deep Cycle Marine Grade Battery
110 Volt Battery Charger
Easy-Lube Hubs
16" Radial Tires
HD 12K Dropleg Jack
Tongue Mounted HD Control Box with Key Lock
10 Gauge Floor
20" Fold-Down Sides
(5) D-Ring Tie-Downs
Ramps (Stored Underneath Bed)

Available Options:

Spare Tire and Wheel: \$150
Solar Charger: \$250
Wireless Remote Control Dump: \$250
Front Mounted Roll Tarp Kit: \$300

Amendment #2 – Additional Trailer

Big Tex 22GNHD Gooseneck Trailer

Contract Price: \$12,706.00 with options listed below

Gooseneck Equipment Trailer (2 5/16 inch Coupler with adjustable height)
I-Beam main frame, riser, and neck
All LED lights
Minimum GVWR (LBS) 23,900
Minimum GVWR per axle (LBS) 10,000 (5 year axle warranty)
Two oil bath breaks axles (LBS) 10,000
Eight radial tires with spare tire and wheel
Electric breakaway kit with charger
Sealed wire harness with 7-way RV plug
Bed Width Minimum 12.75 feet (102 inches) – 102 inch overall width
Bed Length Minimum 20 feet (240 inches) with 5 foot (60 inches) beaver tail
Bed rub rails and stake pockets
Minimum 2 inch treated wood deck
Two drop legs jacks
Two ramps (integrated storage on trailer) – full width Mega Ramps included in price
Locking toolbox and chain holder - mounted between Jacks
Safety chains

Amendment #3 – Additional Trailer

Sure Trac Tube Top Tandem Axle Utility Trailer

Contract Price: Call for Pricing. Pricing subject to change.

82" X 16'
2 – 3500# Axles with EZ Lube hubs and electric brakes
New 15" Radial Tires
Square Pipe top railing approximately 14" above deck
LED Lights
4' Spring Assisted Rear Rampgate with Fold Flat Feature
2" Treated Wood Decking
Set Back Top Crank Tongue Jack
Protected Wiring
2 5/16" Coupler
7 Pin RV Wiring Connector
3 Year Structural Warranty