



## Composite Toe, Leather Boot B625

<b>ITEM #</b>	B625(width)-(size)	
<b>COLOR</b>	Black	
<b>DESCRIPTION</b>	6" Leather Boot with Composite Toe	
<b>WIDTHS</b>	Regular (D), Wide (E), Extra Wide (EEE)	
<b>WIDTH D SIZES</b>	Whole: 5-16    Half: 5.5-11.5	
<b>WIDTH E SIZES</b>	Whole: 5-16    Half: 5.5-11.5	
<b>WIDTH EEE SIZES</b>	Whole: 5-15    Half: 5.5-11.5	
<b>CASE PACK</b>	Selling UOM: PR	Purchasing UOM: 6
<b>MATERIAL(S)</b>	<p><b>Upper:</b> Action leather (split)</p> <p><b>Outsole:</b> Slip resistant, oil resistant, non-marking. Stitched and cemented to upper for double reinforcement.</p> <p><b>Heel:</b> integrated with outsole; cannot be separate from outsole</p> <p><b>Midsole:</b> Stitched to upper for double reinforcement</p> <p><b>Stress Points:</b> Non-metal rivets and reinforced stitching</p> <p><b>Eyelets:</b> 7 non-metal, reinforced</p> <p><b>Insole:</b> Triple cushioned</p> <p><b>Lining:</b> Cambrelle comparable, moisture wicking</p> <p><b>Tongue:</b> Padded</p> <p><b>Counter Pocket:</b> 1.82mm action leather (split)</p> <p><b>Backstay:</b> Double stitched loop</p> <p><b>Collar:</b> PU</p> <p><b>Shank:</b> No shank</p> <p><b>Construction:</b> Goodyear welt</p>	
<b>TOE CAP</b>	Composite Toe, no metal, meets ASTM F2413-18/ASTM F2412-18A Class I/75 Impact Resistance, Class C/75 Compression Resistance	
<b>THREAD</b>	Heavy-Duty Nylon	
<b>CLOSURE</b>	Laces – high quality Talsan, polyester with plastic tip	
<b>COUNTRY OF ORIGIN</b>	China	



Phone: 1-800-334-9880 • Fax: 1-800-322-7537 • [www.bobbarker.com](http://www.bobbarker.com)

**BobBarker**<sup>®</sup>P.O. Box 429  
Fuquay-Varina, NC 27526PH: 1-800-334-9880  
Fax: 1-800-322-7537  
[www.bobbarker.com](http://www.bobbarker.com)Steel Toe Leather  
Safety Boot  
Style 82221  
(Width)-Size**Steel Toe Leather Boot, Black**

<b>Item Number:</b>	82221(Width) •Size
<b>Color:</b>	Black
<b>Upper Stock:</b>	Black corrected split cow leather with minimum 1" padded collar, must be breathable
<b>Outsole:</b>	Non-marking, oil resistant, slip resistant, lug outsole
<b>Front Sole:</b>	Front Sole thickness minimum 9mm
<b>Side Facing:</b>	Cow leather (corrected split), lining cambrelle with minimum 5mm sponge
<b>Construction:</b>	Goodyear welt construction sewn-thru with nylon thread
<b>Insole:</b>	6-10mm thickness, water resistant, cambrelle lining
<b>Tongue:</b>	Black PU with cushioning,
<b>Thread:</b>	100% Nylon, Black
<b>Counter:</b>	Thermal molded, water resistant
<b>Shank:</b>	No Shank for added security
<b>Vamp:</b>	First grade corrected split leather lined with 100% cotton
<b>Laces:</b>	Black, Heavy Nylon laces, 45 inches with 45kg tensile strength
<b>Eyelets:</b>	6 pair eyelets, heavy-weight, non-rusting metal, no hooks
<b>Heel:</b>	Heel thickness minimum 21mm
<b>Toe Cap:</b>	Steel Toe Meets ASTM F2413-18/ASTM F2412-18A Class I/75 Impact Resistance, Class C/75 Compression Resistance
<b>Height:</b>	6" minimum
<b>Sizing:</b>	Whole sizes 6-15, half sizes 7.5-10.5 in EE width. Custom sizes available upon request.
<b>Unit of Measure:</b>	6 same size pair per master carton. Each pair is individually boxed with sizes clearly labeled.

**BobBarker**®

P.O. Box 429  
Fuquay-Varina, NC 27526

PH: 1-800-334-9880  
Fax: 1-800-322-7537  
[www.bobbarker.com](http://www.bobbarker.com)



Plain Toe  
leather boot  
Black  
Style B515

## Specifications

- Item Number:** B515+Width -Size
- Upper Stock:** Black Cow Leather (split)
- Outsole:** Slip-resistant gum rubber outsole is oil-resistant and non-marking, features Goodyear Welt construction. Outsole is stitched and cemented to upper for double reinforcement.
- Construction:** Goodyear - Welt, Sew-through with strong nylon thread. Outsole is glued to midsole and midsole is stitched to upper for double reinforcement. Metal rivets or reinforced stitching at main stress points.
- Insole:** Triple cushioned insole with Cambrelle moisture wicking lining
- Backstay:** Double-stitched, looped
- Tongue:** Padded tongue and PU collar
- Counter Pocket:** Black Cow Leather (split), thickness (1.8-2.0mm)
- Shank:** No Shank
- Laces:** High Quality Talson shoelace with plastic tip
- Eyelets:** Non-rust eyelets, 7 pairs per boot
- Vamp:** Black Cow Leather (split), thickness 1.8-2.0mm
- Heel:** Heel is integral with outsole – cannot separate.
- Lining:** Cambrelle moisture wicking lining
- Color:** Black
- Width:** Regular, Wide
- Size:** Whole sizes 4-18, half sizes 6.5-11.5, Regular and Wide Widths. Custom sizes available upon request.



# Bob Barker® Plain-Toe Leather Boots, Brown B525

<b>ITEM #</b>	B525(width)-(size)	
<b>DESCRIPTION</b>	Bob Barker® Plain-Toe Leather Boots, Brown	
<b>SIZES</b>	Whole sizes 5-18, half sizes 6.5-11.5, Regular and Wide Widths. Custom sizes available upon request.	
<b>UPPER STOCK</b>	Brown Cow Leather (split)	
<b>OUTSOLE</b>	Slip-resistant gum rubber outsole is oil-resistant and non-marking, features Goodyear Welt construction. Outsole is stitched and cemented to upper for double reinforcement.	
<b>CONSTRUCTION</b>	Goodyear - Welt, Sew-through with strong nylon thread. Outsole is glued to midsole and midsole is stitched to upper for double reinforcement. Metal rivets or reinforced stitching at main stress points.	
<b>INSOLE</b>	Triple cushioned insole with Cambrelle moisture wicking lining	
<b>BACKSTAY</b>	Double-stitched, looped	
<b>TONGUE</b>	Padded tongue and PU collar	
<b>COUNTER POCKET</b>	Brown Cow Leather (split), thickness (1.8-2.0mm)	
<b>SHANK</b>	No Shank	
<b>LACES</b>	High Quality Talsen shoelace with plastic tip	
<b>EYELETS</b>	Non-rust eyelets, 7 pair per boot	
<b>VAMP</b>	Brown Cow Leather (split), thickness 1.8-2.0mm	
<b>HEEL</b>	Heel is integral with outsole – cannot separate.	
<b>LINING</b>	Cambrelle moisture wicking lining	
<b>CASE PACK</b>	STANDARD CASE: 1 Pair	MASTER CASE: 6 Pairs

**BobBarker**®

P.O. Box 429  
Fuquay-Varina, NC 27526

PH: 1-800-334-9880  
Fax: 1-800-322-7537  
[www.bobbarker.com](http://www.bobbarker.com)



Knee Boots  
Anti-Skid PVC

Style: KBP

**14" Plain Toe, Anti-Skid PVC Knee Boots, Black**

<b>Item Number:</b>	KBP -Size
<b>Color:</b>	Black
<b>Material:</b>	PVC (Polyvinyl Chloride)
<b>Construction:</b>	One-piece injection molded Waterproof; seamless
<b>Toe:</b>	Plain toe
<b>Insole:</b>	Removable washable insole
<b>Outsole:</b>	Anti- skid
<b>Shank:</b>	Molded -in Shank
<b>Sizing:</b>	Whole sizes 3-15
<b>Unit of Measure:</b>	Each