

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - U.S. Equipment for Base Machine

Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer	Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes
---	--

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

1601XF		HP2025 - Hydraulic Power Unit, 25 HP - U.S. <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i>	6,499.00
--------	--	--	----------

OIL COOLER

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,660.00

ATTACHMENTS - ORDER AS DESIRED

		Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	92.00
--	--	--	-------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	127.68
5RDF0038		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,214.00
5RDF0036		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	185.76

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - U.S.

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - U.S. Equipment for Base Machine

Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer	Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes
---	--

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

1611XF		HP2134 - Hydraulic Power Unit, 34 HP - U.S. <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i>	6,610.00
--------	--	--	----------

OIL COOLER

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,660.00

ATTACHMENTS - ORDER AS DESIRED

9040		Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	92.00
------	--	--	-------

ATTACHMENTS FOR FIELD CONVERSION

5RDF0038		Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	127.68
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,214.00
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	185.76

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - U.S.

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - Canada Equipment for Base Machine

Function: Hydraulic Power Unit	Parking Stand: Standard
Pressure: 2700 psi	Hitch Category: Category I
Flow: 16 gpm	Quick Hitch Compatibility: iMatch Compatible
Reservoir Capacity: 15 gal.	Approximate Set-Up Time: 120 Minutes
System Capacity: 17 gal.	
System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch	
Hoses, Tips, and Brackets included	
Tractor RPM: 540 RPM	
PTO Manufacturer: Comer	

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

160AXF		HP2025 - Hydraulic Power Unit, 25 HP - Canada <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i>	7,441.38
--------	--	--	----------

OIL COOLER

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,900.82

ATTACHMENTS - ORDER AS DESIRED

9040		Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	111.47
------	--	--	--------

FRONTIER PRODUCTS

Snow Products

HP2025 - Hydraulic Power Unit, 25 HP - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - Canada Equipment for Base Machine

Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer	Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes
---	--

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

161AXF		HP2134 - Hydraulic Power Unit, 34 HP - Canada <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes wiring harness to control the loader mounted implement.</i>	7,564.26
--------	--	--	----------

OIL COOLER

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,900.82

ATTACHMENTS - ORDER AS DESIRED

9040		Wiring Harness: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	111.47
------	--	--	--------

FRONTIER PRODUCTS

Snow Products

HP2134 - Hydraulic Power Unit, 34 HP - Canada
Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 73.75 In.

Shipping Weight: 490 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W74.5 In. x H30.75 In. x D34 In.

Capacity:

3.5 Cubic Foot

Operational Weight: 440 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2191XF		AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,105.00
--------	--	---	----------

ATTACHMENTS - ORDER AS DESIRED

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge
------	--	--	-----------

ATTACHMENTS FOR FIELD CONVERSION

5MP43052		Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
----------	--	--	--------

FRONTIER PRODUCTS

Snow Products

**AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 85.75 In.

Shipping Weight: 527 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W86.25 In. x H30.75 In. x D34 In.

Capacity:

4 Cubic Foot

Operational Weight: 477 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2192XF		AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,333.00
--------	--	---	----------

ATTACHMENTS - ORDER AS DESIRED

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge
------	--	--	-----------

ATTACHMENTS FOR FIELD CONVERSION

5MP43052		Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
----------	--	--	--------

FRONTIER PRODUCTS

Snow Products

**AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

Equipment for Base Machine

Cutting Width: 97.75 In.

Shipping Weight: 564 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W98.25 In. x H30.75 In. x D34 In.

Capacity:

4.5 Cubic Foot

Operational Weight: 514 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2193XF		AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,579.00
--------	--	---	----------

ATTACHMENTS - ORDER AS DESIRED

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge
------	--	--	-----------

ATTACHMENTS FOR FIELD CONVERSION

5MP43052		Miscellaneous: French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
----------	--	--	--------

FRONTIER PRODUCTS

Snow Products

**AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series
Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 98 In.
 Loader Series:
 300, 400, and 500
 Dimensions:
 W98.38 In. x H39.8 In. x D41.5 In.
 Capacity:
 7 Cubic Foot
 Optional Bolt-on Pull Back Kit Weight:
 163 lbs.

Operational Weight: 900 lbs.
 Shipping Weight: 950 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2201XF		AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	3,731.00
--------	--	--	----------

ATTACHMENTS - ORDER AS DESIRED

9000		Back Drag Attachment for AS11E (Less Rubber Edge) <i>For 8 Ft. Model.</i>	750.00
9010		Rubber Edge Kit for AS11E <i>8 Ft. Back Drag attachment required.</i>	401.00
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
5FP10730		Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge)	1,305.27
5MP43052		French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
5FP10733		Rubber Edge Kit for 8 Ft. AS11E <i>5FP10730 - 8 Ft. Back Drag attachment required.</i>	733.71

FRONTIER PRODUCTS

Snow Products

**AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500
Series Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 110 In.

Loader Series:
300, 400, and 500

Dimensions:

W110.38 In. x H39.8 In. x D41.5 In.

Capacity:

7.8 Cubic Foot

Optional Bolt-on Pull Back Kit Weight:
175 lbs.

Operational Weight: 943 lbs.

Shipping Weight: 993 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2202XF		AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	4,104.00
--------	--	--	----------

ATTACHMENTS - ORDER AS DESIRED

9000		Back Drag Attachment for AS11E (Less Rubber Edge) <i>For 9 Ft. Model.</i>	779.00
9010		Rubber Edge Kit for AS11E <i>9 Ft. Back Drag attachment required.</i>	447.00
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
5FP10731		Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge)	1,423.16
5MP43052		French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
5FP10734		Rubber Edge Kit for 9 Ft. AS11E <i>5FP10731 - 9 Ft. Back Drag attachment required.</i>	734.38

FRONTIER PRODUCTS

Snow Products

**AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500
Series Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Equipment for Base Machine

Cutting Width: 119.5 In.

Loader Series:
300, 400, and 500

Dimensions:
W110.875 In. x H39.8 In. x D41.5 In.

Capacity:
8.5 Cubic Foot

Optional Bolt-on Pull Back Kit Weight:
185 lbs.

Operational Weight: 980 lbs.

Shipping Weight: 1030 lbs.

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2203XF		AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	4,467.00
--------	--	---	----------

ATTACHMENTS - ORDER AS DESIRED

9000		Back Drag Attachment for AS11E (Less Rubber Edge) <i>For 10 Ft. Model.</i>	817.00
9010		Rubber Edge Kit for AS11E <i>10 Ft. Back Drag attachment required.</i>	489.00
9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Charge

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous:	
5FP10732		Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge)	1,458.60
5MP43052		French Operator's Manual and Decal Kit for Models: AB15, AB16, AE11, AF11, AF12, AG10, AH11, AS10, AS11	163.56
5FP10735		Rubber Edge Kit for 10 Ft. AS11E <i>5FP10732 - 10 Ft. Back Drag attachment required.</i>	771.25

FRONTIER PRODUCTS

Snow Products

**AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500
Series Carrier**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 48 In.
 Transport Width: 48.5 In.
 Working Height: 24 5/8 In.
 Length: 38.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 1/4 In.
 Impeller Diameter: 20 In.
 Impeller Width: 6 In.
 Impeller Shaft Diameter: 1 In.
 Number of Impeller Blades: 4
 Roller Chain: 50
 Drive Sprocket: 17 Teeth
 Driven Sprocket: 36 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model L-25J
 Gear Box HP (Through Gears): 11
 Gear Box HP (Straight Through): 30
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 20
 PTO Clutch Setting (Number): 900
 Shearbolt Bolt Size and Grade (PTO):
 M6 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 1/4 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 375 lbs.
 Shipping Weight: 415 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose
 an Option, Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor,
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3801XF	SB1148 - 48 In. 3-Point Medium Snowblower - U.S.	2,448.97
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	350.56

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	283.00
9010	Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,067.04
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	321.84
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	369.36
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	585.36
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	686.88
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	177.12
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	177.12

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 54 In.
 Transport Width: 54.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 455 lbs.
 Shipping Weight: 495 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: MN/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3802XF		SB1154 - 54 In. 3-Point Medium Snowblower - U.S.	2,721.00
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	350.56

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	283.00
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
5RDF0020		Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	1,067.04
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,067.04
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	321.84
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	369.36
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	585.36
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	686.88
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	177.12
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	177.12

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In.
 Transport Width: 64.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 479 lbs.
 Shipping Weight: 519 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3803XF		SB1164 - 64 In. 3-Point Medium Snowblower - U.S.	2,803.00
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	350.56

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	283.00
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
5RDF0020		Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	1,067.04
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,067.04
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	321.84
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	369.36
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	585.36
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	686.88
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	177.12
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	177.12

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In.
 Transport Width: 74.5 In.
 Working Height: 26 In.
 Length: 47.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 9 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting (Number): 1700
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 1/4 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 590 lbs.
 Shipping Weight: 635 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictor, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3804XF		SB1174 - 74 In. 3-Point Medium Snowblower - U.S.	3,531.00
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	350.56

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	283.00
9010		Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
5RDF0021		Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,067.04
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	369.36
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0018		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	764.64
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	686.88
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	177.12
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	177.12

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 84 In.
 Transport Width: 85.5 In.
 Working Height: 34 In.
 Length: 55.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 20 In.
 Auger Flighting Thickness: 3/8 In.
 Impeller Diameter: 27-1/2 In.
 Impeller Width: 10.5 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 38 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 3/16 In.
 Cutting Edge: Welded

Cutting Edge Dimension: 1/2 In. x 3 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I/II
 Quick Hitch Compatibility:
 iMatch Compatible and
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 35-90 HP
 Operating Weight: 958 lbs.
 Shipping Weight: 1003 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Cylinder (2 In. x 8 In.),
 Including Bracket, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3805XF	SB1184 - 84 In. 3-Point Medium Snowblower - U.S.	4,880.14
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	439.86

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	300.00
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
	5RDF0021	Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,067.04
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	390.96
	5RDF0018	Hydraulic Cylinder Kit for Chute Rotation	764.64
	5RDF0016	Manual Chute Rotation Kit (SB11)	177.12

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - U.S. Equipment for Base Machine

<p>Function: Snow Removal Working Width: 94 In. (2,387.6 mm) Transport Width: 95.5 In. (2,425.7 mm) Working Height: 34 In. (863.6 mm) Length: 55.5 In. (1,409.7 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.5 mm) Impeller Diameter: 27-1/2 In. (698.5 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1-9/16 In. (39.7 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 N-m Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 11 Gauge (3.18 mm) Impeller Blade Thickness: 3/8 In. (9.5 mm) Side Panel Bottom Thickness: 3/16 In. (4.8 mm) Cutting Edge: Welded</p>	<p>Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm) Chute Diameter: 12 In. (304.8 mm) Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 35-90 HP (26.1 kW - 67.1 kW) Operating Weight: 1,121 lbs. (508.5 kg) Shipping Weight: 1,166 lbs. (528.9 kg) Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A</p>
--	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3806XF	SB1194 - 94 In. 3-Point Medium Snowblower - U.S.	5,063.14
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	439.86

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	300.00
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	820.01

ATTACHMENTS FOR FIELD CONVERSION

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Miscellaneous:	
5RDF0021		Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,067.04
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0018		Hydraulic Cylinder Kit for Chute Rotation	764.64
5RDF0016		Manual Chute Rotation Kit (SB11)	177.12

FRONTIER PRODUCTS

Snow Products

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In. (1,879.6 mm)
 Transport Width: 74.5 In. (1892.3 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8mm)

Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 835 lbs. (378.7 kg)
 Shipping Weight: 875 lbs. (396.9 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses,
 and tips Rotating Drum (Including Hoses and
 Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3831XF	SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	6,828.00
--------	--	----------

ATTACHMENTS FOR FIELD CONVERSION

5RDF0028	Miscellaneous: Cutting Edge - CHT400 Steel	354.24
----------	--	--------

FRONTIER PRODUCTS

Snow Products

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 80 In. (2,032 mm)
 Transport Width: 80.5 In. (2,044.7 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8mm)

Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 895 lbs. (406 kg)
 Shipping Weight: 935 lbs. (424.1 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses,
 and tips Rotating Drum (Including Hoses and
 Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3832XF		SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	7,029.00
--------	--	--	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous: Cutting Edge - CHT400 Steel	388.80
--	--	--	--------

FRONTIER PRODUCTS

Snow Products

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2233 lbs.
 Shipping Weight: 2280 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses, and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3812XF	SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	12,109.57
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	557.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	295.74
9002	Cutting Edge - Tivar	631.16

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	612.59
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,405.83
9012		Serrated Main Auger	2,691.73
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,078.44
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	255.14
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	742.54
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0065		2nd Auger Kit - 15 In. Diameter	1,775.52
5RDF0052		Cutting Edge - CHT400 Steel	380.16
5RDF0060		Cutting Edge for SB1308 & SB1308R - Stainless Steel	781.92
5RDF0056		Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	805.68
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	946.08
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	321.84
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,881.52
5RDF0069		Serrated Main Auger for SB1308 & SB1308R	3,430.08

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0062	Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2160 lbs.
 Shipping Weight: 2205 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3811XF	SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	10,426.08
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	557.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	295.74
9002	Cutting Edge - Tivar	631.16

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	612.59
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,405.83
9012		Serrated Main Auger	2,691.73
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,078.44
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	255.14
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	742.54
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0065		2nd Auger Kit - 15 In. Diameter	1,775.52
5RDF0052		Cutting Edge - CHT400 Steel	380.16
5RDF0060		Cutting Edge for SB1308 & SB1308R - Stainless Steel	781.92
5RDF0056		Cutting Edge for SB1308 & SB1308R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	805.68
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	946.08
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	321.84
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,881.52
5RDF0069		Serrated Main Auger for SB1308 & SB1308R	3,430.08

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0062	Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

**SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 104 In.
 Transport Width: 105 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2336 lbs.
 Shipping Weight: 2385 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3813XF	SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	12,398.61
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	557.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	317.56
9002	Cutting Edge - Tivar	659.02

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	621.89
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,422.00
9012		Serrated Main Auger	2,784.55
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,078.44
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	255.14
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	742.54
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0066		2nd Auger Kit - 15 In. Diameter	1,846.80
5RDF0053		Cutting Edge - CHT400 Steel	406.08
5RDF0061		Cutting Edge for SB1309R - Stainless Steel	792.72
5RDF0057		Cutting Edge for SB1309R - Tivar <i>Fully Plastic - Wear and Rust Resistant</i>	840.24
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	946.08
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	321.84
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,881.52
5RDF0070		Serrated Main Auger for SB1309R	3,548.88

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0062	Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

<p>Function: Snow Removal Working Width: 88 In. Transport Width: 88.5 In. Working Height: 40 In. Length: 62.5 In. Single/Dual Auger: Single/Dual Auger Diameter: 22 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 28-1/2 In. Impeller Width: 12 In. Impeller Shaft Diameter: 1-9/16 In. Number of Impeller Blades: 5 Roller Chain: 80 Drive Sprocket: 11 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP Gear Box HP (Straight Through): 105 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 175 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 1/4 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 3/8 In. Side Panel Bottom Thickness: 5/8 In.</p>	<p>Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 12 3/4 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 45-95 HP Operating Weight: 1670 lbs. Shipping Weight: 1715 lbs. Approximate Set-Up Time: 90 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 14 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard</p>
--	--

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3815XF	SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	9,718.28
--------	---	----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	608.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	257.11
9002	Cutting Edge - Tivar	584.76

FRONTIER PRODUCTS

Snow Products

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	594.03
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,312.10
9012		Serrated Main Auger	2,552.49
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	649.72
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0063		2nd Auger Kit - 14 In. Diameter	1,656.72
5RDF0050		Cutting Edge - CHT400 Steel	336.96
5RDF0058		Cutting Edge for SB1388 & SB1388R - Stainless Steel	758.16
5RDF0054		Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	745.20
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0077		Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	829.44
5RDF0067		Serrated Main Auger for SB1388 & SB1388R	3,252.96
5RDF0062		Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 61 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12-3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1552 lbs.
 Shipping Weight: 1597 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3814XF	SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	8,252.41
--------	---	----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	608.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	257.11
9002	Cutting Edge - Tivar	584.76

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	594.03
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,312.10
9012		Serrated Main Auger	2,552.49
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	649.72
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0063		2nd Auger Kit - 14 In. Diameter	1,656.72
5RDF0050		Cutting Edge - CHT400 Steel	336.96
5RDF0058		Cutting Edge for SB1388 & SB1388R - Stainless Steel	758.16
5RDF0054		Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	745.20
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0077		Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	829.44
5RDF0067		Serrated Main Auger for SB1388 & SB1388R	3,252.96
5RDF0062		Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Equipment for Base Machine

<p>Function: Snow Removal Working Width: 92 In. Transport Width: 93 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In. Side Panel Bottom Thickness: 5/8 In.</p>	<p>Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 75-125 HP Operating Weight: 2183 lbs. Shipping Weight: 2230 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard</p>
---	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3817XF	SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	11,583.20
--------	---	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	557.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	269.77
9002	Cutting Edge - Tivar	603.32

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	603.32
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,330.85
9012		Serrated Main Auger	2,598.49
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,078.44
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	255.14
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	742.54
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0064		2nd Auger Kit - 15 In. Diameter	1,704.24
5RDF0051		Cutting Edge - CHT400 Steel	356.40
5RDF0059		Cutting Edge for SB1392 & SB1392R - Stainless Steel	768.96
5RDF0055		Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	768.96
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	946.08
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	321.84
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,881.52
5RDF0068		Serrated Main Auger for SB1392 & SB1392R	3,311.28

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0062	Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 92 In.
 Transport Width: 93 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 75-125 HP
 Operating Weight: 2044 lbs.
 Shipping Weight: 2100 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3816XF	SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	10,006.00
--------	---	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	557.00

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	269.77
9002	Cutting Edge - Tivar	603.32

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	603.32
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,330.85
9012		Serrated Main Auger	2,598.49
9020		Drift Cutters	348.58
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	300.00
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,078.44
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	255.14
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	742.54
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	510.50
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous:			
5RDF0064		2nd Auger Kit - 15 In. Diameter	1,704.24
5RDF0051		Cutting Edge - CHT400 Steel	356.40
5RDF0059		Cutting Edge for SB1392 & SB1392R - Stainless Steel	768.96
5RDF0055		Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	768.96
5RDF0074		Drift Cutters	451.44
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	390.96
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i>	946.08
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	321.84
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,881.52
5RDF0068		Serrated Main Auger for SB1392 & SB1392R	3,311.28

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION ...Continued...	
	5RDF0062	Stainless Steel Pivoting Skid Shoes	652.32

FRONTIER PRODUCTS

Snow Products

**SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - U.S.**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S. Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3822XF	SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S. <i>Must only be used with HP2025 Hydraulic Power Unit.</i>	13,259.57
--------	---	-----------

HYDRAULIC POWER UNITS

1000	HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness to control the loader mounted implement.</i>	In Base Price
1095	Less Hydraulic Power Unit	-6,499.00

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i>	In Base Price
2095	Less Oil Cooler	-1,660.00

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
CHUTES			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	585.00
ATTACHMENTS - ORDER AS DESIRED			
9020		Drift Cutters (SB21)	140.00
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i>	92.00
ATTACHMENTS FOR FIELD CONVERSION			
5RDF0038		Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	127.68
5RDF0026		Drift Cutters (SB21)	187.92
5RDF0027		Kit for Hydraulic Chute Deflector (SB2164)	781.92
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,214.00
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	185.76

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S.

Equipment for Base Machine

Function: Snow Removal
 Working Width: 76 In. (1,931.4 mm)
 Transport Width: 76 In. (1,931.4 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 8.5 In. (215.9 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 580 RPM
 Auger RPM: 180 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 5/16 In. (8 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 mm x 76.2 mm)
 Chute Diameter: 12 In. (0.3m)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual or Hydraulic Adjustable Tie Rod or Hydraulic Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, Wiring Harness and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3821XF	SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S. <i>Must only be used with HP2134 Hydraulic Power Unit.</i>	13,639.58
--------	--	-----------

HYDRAULIC POWER UNITS

1010	HP2134 - Hydraulic Power Unit, 34 HP <i>Includes wiring harness to control the loader mounted implement.</i>	In Base Price
1095	Less Hydraulic Power Unit	-6,610.00

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i>	In Base Price
2095	Less Oil Cooler	-1,660.00

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S.

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
CHUTES			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	585.00
ATTACHMENTS - ORDER AS DESIRED			
9020		Drift Cutters (SB21)	140.00
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i>	92.00
ATTACHMENTS FOR FIELD CONVERSION			
5RDF0038		Miscellaneous: Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	127.68
5RDF0026		Drift Cutters (SB21)	187.92
5RDF0025		Kit for Hydraulic Chute Deflector (SB2176)	781.92
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,214.00
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	185.76

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 48 In.
 Transport Width: 48.5 In.
 Working Height: 24 5/8 In.
 Length: 38.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 1/4 In.
 Impeller Diameter: 20 In.
 Impeller Width: 6 In.
 Impeller Shaft Diameter: 1 In.
 Number of Impeller Blades: 4
 Roller Chain: 50
 Drive Sprocket: 17 Teeth
 Driven Sprocket: 36 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model L-25J
 Gear Box HP (Through Gears): 11
 Gear Box HP (Straight Through): 30
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 20
 PTO Clutch Setting (Number): 900
 Shearbolt Bolt Size and Grade (PTO):
 M6 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 1/4 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 375 lbs.
 Shipping Weight: 415 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose
 an Option, Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380AXF		SB1148 - 48 In. 3-Point Medium Snowblower - Canada	2,776.40
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	423.24

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	344.48
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1148 - 48 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 54 In.
 Transport Width: 54.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 16-35 HP
 Operating Weight: 455 lbs.
 Shipping Weight: 495 lbs.
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: MN/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380BXF		SB1154 - 54 In. 3-Point Medium Snowblower - Canada	3,062.82
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	423.24

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	344.48
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1154 - 54 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In.
 Transport Width: 64.5 In.
 Working Height: 26 In.
 Length: 41 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 7 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 40
 PTO Clutch Setting (Number): 1300
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 12 Gauge
 Impeller Housing Thickness: 12 Gauge
 Impeller Blade Thickness: 3/16 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 8 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 479 lbs.
 Shipping Weight: 519 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses, and Tips
 Electric Actuator (5In).
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380CXF		SB1164 - 64 In. 3-Point Medium Snowblower - Canada	3,174.32
--------	--	--	----------

CHUTES

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	423.24

ATTACHMENTS - ORDER AS DESIRED

9000		Hydraulic Cylinder Kit for Chute Deflector	344.48
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1164 - 64 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In.
 Transport Width: 74.5 In.
 Working Height: 26 In.
 Length: 47.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In.
 Impeller Diameter: 24 In.
 Impeller Width: 9 In.
 Impeller Shaft Diameter: 1-3/8 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-281A
 Gear Box HP (Through Gears): 23 HP
 Gear Box HP (Straight Through): 60 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting (Number): 1700
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 1/4 In.
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded
 Cutting Edge Dimension: 3/8 In. x 2 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility:
 iMatch Compatible
 HP Requirements (Minimum-Maximum HP):
 20-50 HP
 Operating Weight: 590 lbs.
 Shipping Weight: 635 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 5 In.)
 Including Brackets, Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must Choose an
 Option - Manual or Hydraulic
 Manual, Worm Gear with Crank
 Hydraulic: Motor
 Including Flow Restrictors, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380DXF	SB1174 - 74 In. 3-Point Medium Snowblower - Canada	3,986.93
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	423.24

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	344.48
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1174 - 74 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 84 In.
 Transport Width: 85.5 In.
 Working Height: 34 In.
 Length: 55.5 In.
 Single/Dual Auger: Single
 Auger Diameter: 20 In.
 Auger Flighting Thickness: 3/8 In.
 Impeller Diameter: 27-1/2 In.
 Impeller Width: 10.5 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 38 Teeth
 Chain Idler: Manual Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 11 Gauge
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 3/16 In.
 Cutting Edge: Welded

Cutting Edge Dimension: 1/2 In. x 3 In.
 Chute Diameter: 12 In.
 Chute Base: Standard
 Chute Rotation: 215 Degrees
 Parking Stand: Standard
 Hitch Category: Category I/II
 Quick Hitch Compatibility:
 iMatch Compatible and
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 35-90 HP
 Operating Weight: 958 lbs.
 Shipping Weight: 1003 lbs.
 Approximate Set-Up Time: 60 Minutes
 Chute Deflector Adjustment (Standard):
 Manual
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Electric Actuator (8 In.)
 Including Hardware, Switch, and Electric Cable
 Chute Rotation (Standard): Must choose an
 Option - Manual or Hydraulic
 Chute Rotation Options:
 Manual, Worm Gear with Crank
 Hydraulic: Cylinder (2 In. x 8 In.),
 Including Bracket, Hoses, and Tips
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380EXF	SB1184 - 84 In. 3-Point Medium Snowblower - Canada	5,451.81
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	487.80

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	364.63
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1184 - 84 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - Canada Equipment for Base Machine

<p>Function: Snow Removal Working Width: 94 In. (2,387.6 mm) Transport Width: 95.5 In. (2,425.7 mm) Working Height: 34 In. (863.6 mm) Length: 55.5 In. (1,409.7 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.5 mm) Impeller Diameter: 27-1/2 In. (698.5 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1-9/16 In. (39.7 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 N-m Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 11 Gauge (3.18 mm) Impeller Blade Thickness: 3/8 In. (9.5 mm) Side Panel Bottom Thickness: 3/16 In. (4.8 mm) Cutting Edge: Welded</p>	<p>Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm) Chute Diameter: 12 In. (304.8 mm) Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 35-90 HP (26.1 kW - 67.1 kW) Operating Weight: 1,121 lbs. (508.5 kg) Shipping Weight: 1,166 lbs. (528.9 kg) Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A</p>
--	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

380FXF	SB1194 - 94 In. 3-Point Medium Snowblower - Canada	5,642.19
--------	--	----------

CHUTES

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	487.80

ATTACHMENTS - ORDER AS DESIRED

9000	Hydraulic Cylinder Kit for Chute Deflector	364.63
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	906.11

FRONTIER PRODUCTS

Snow Products

SB1194 - 94 In. 3-Point Medium Snowblower - Canada

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 74 In. (1,879.6 mm)
 Transport Width: 74.5 In. (1892.3 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 835 lbs. (378.7 kg)
 Shipping Weight: 875 lbs. (396.9 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

383AXF		SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	7,421.09
--------	--	--	----------

FRONTIER PRODUCTS

Snow Products

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 80 In. (2,032 mm)
 Transport Width: 80.5 In. (2,044.7 mm)
 Working Height: 30 In. (762 mm)
 Single/Dual Auger: Single
 Auger Diameter: 20 In. (508 mm)
 Auger Flighting Thickness: 3/8 In. (9.53 mm)
 Impeller Diameter: 26 In. (660.4 mm)
 Impeller Width: 10.5 In. (266.7 mm)
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)
 Number of Impeller Blades: 4
 Roller Chain: 60
 Drive Sprocket: 10 Teeth
 Driven Sprocket: 32 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP (41 kW)
 Gear Box HP (Straight Through): 105 HP (78.3 kW)
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 170 RPM
 PTO Manufacturer: Comer
 PTO Description: 50
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)
 Shearbolt Bolt Size and Grade (PTO):
 M10 8.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In. (4.8mm)
 Impeller Blade Thickness: 5/16 In. (7.9mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replacable
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category I & II
 Quick Hitch Compatibility:
 iMatch & Cat. II Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 30-80 HP (22.4-59.7kW)
 Operating Weight: 895 lbs. (406 kg)
 Shipping Weight: 935 lbs. (424.1 kg)
 Approximate Set-up Time: 60 Minutes
 Chute Deflector Adjustment (Standard): Hydraulic
 Cylinder Chute Rotation (Standard): Hydraulic
 Motor
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

383BXF		SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	7,596.84
--------	--	--	----------

FRONTIER PRODUCTS

Snow Products

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

THIS PAGE IS INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Snow Products

SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

<p>Function: Snow Removal Working Width: 98 In. Transport Width: 99 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Optional Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In. Side Panel Bottom Thickness: 5/8 In.</p>	<p>Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II/III Quick Hitch Compatibility: Quick Hitch Compatible HP Requirements (Minimum-Maximum HP): 90-180 HP Operating Weight: 2233 lbs. Shipping Weight: 2280 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard</p>
--	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381BXF	SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	13,751.84
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	615.49

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	326.80
9002	Cutting Edge - Tivar	697.44

FRONTIER PRODUCTS

Snow Products

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	676.92
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,553.44
9012		Serrated Main Auger	2,919.12
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,401.68
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	281.93
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	820.51
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 98 In.
 Transport Width: 99 In.
 Working Height: 44 In.
 Length: 65.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM Optional
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 3/4 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 5 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2160 lbs.
 Shipping Weight: 2205 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381AXF	SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	11,915.27
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	615.49

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	326.80
9002	Cutting Edge - Tivar	697.44

FRONTIER PRODUCTS

Snow Products

SB1308 - 8 Ft. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	676.92
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,553.44
9012		Serrated Main Auger	2,919.12
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,401.68
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	281.93
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	820.51
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 104 In.
 Transport Width: 105 In.
 Working Height: 44 In.
 Length: 67 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 24 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 31-1/2 In.
 Impeller Width: 14 In.
 Impeller Shaft Diameter: 2 In.
 Number of Impeller Blades: 6
 Roller Chain: 80
 Drive Sprocket: 12 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-279A
 Gear Box HP (Through Gears): 100 HP
 Gear Box HP (Straight Through): 185 HP
 Tractor RPM: 540/1000 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 190 RPM
 PTO Manufacturer: Comer
 PTO Description: 80
 PTO Clutch Setting (Number): 3000
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 5/16 In.
 Back Plate Thickness: 10 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 1/2 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 14-7/8 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II/III
 Quick Hitch Compatibility:
 Quick Hitch Compatible
 HP Requirements (Minimum-Maximum HP):
 90-180 HP
 Operating Weight: 2336 lbs.
 Shipping Weight: 2385 lbs.
 Approximate Set-Up Time: 100 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 15 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381CXF	SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	14,194.76
--------	--	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	615.49

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	350.90
9002	Cutting Edge - Tivar	728.21

FRONTIER PRODUCTS

Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	687.18
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,571.31
9012		Serrated Main Auger	3,076.92
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,401.68
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	281.93
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	820.51
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 62.5 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 3/16 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12 3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1670 lbs.
 Shipping Weight: 1715 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 Standard

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381EXF	SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	11,622.96
--------	---	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	671.84

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	284.11
9002	Cutting Edge - Tivar	684.16

FRONTIER PRODUCTS

Snow Products

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor
Chute Rotation and Single Auger - Canada**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	656.41
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,449.88
9012		Serrated Main Auger	2,820.51
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	717.95
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada Equipment for Base Machine

Function: Snow Removal
 Working Width: 88 In.
 Transport Width: 88.5 In.
 Working Height: 40 In.
 Length: 61 In.
 Single/Dual Auger: Single/Dual
 Auger Diameter: 22 In.
 Auger Flighting Thickness: 7/16 In.
 Impeller Diameter: 28-1/2 In.
 Impeller Width: 12 In.
 Impeller Shaft Diameter: 1-9/16 In.
 Number of Impeller Blades: 5
 Roller Chain: 80
 Drive Sprocket: 11 Teeth
 Driven Sprocket: 34 Teeth
 Chain Idler: Automatic Adjustment
 Gear Box Manufacturer: Comer
 Gear Box Description: Model T-27D
 Gear Box HP (Through Gears): 55 HP
 Gear Box HP (Straight Through): 105 HP
 Tractor RPM: 540 RPM
 Impeller RPM: 540 RPM
 Auger RPM: 175 RPM
 PTO Manufacturer: Comer
 PTO Description: 60
 PTO Clutch Setting (Number): 1900
 Shearbolt Bolt Size and Grade (PTO):
 M10 6.8 Metric
 Shearbolt Bolt Size and Grade (Auger):
 5/16 In. 5 SAE
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 1/4 In.
 Back Plate Thickness: 11 Gauge
 Impeller Housing Thickness: 1/4 In.
 Impeller Blade Thickness: 3/8 In.
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible
 Cutting Edge Dimension: 1/2 In. x 4 In.
 Chute Diameter: 12-3/4 In.
 Chute Base: Heavy Duty
 Chute Rotation: 270 Degrees
 Parking Stand: Standard
 Hitch Category: Category II
 Quick Hitch Compatibility:
 Quick Coupler Compatible
 HP Requirements (Minimum-Maximum HP):
 45-95 HP
 Operating Weight: 1552 lbs.
 Shipping Weight: 1597 lbs.
 Approximate Set-Up Time: 90 Minutes
 Chute Deflector Adjustment (Standard):
 Manual - Must Choose a Chute Option
 Chute Deflector Adjustment Options:
 Hydraulic Cylinder (2 In. x 8 In.)
 Including Hoses and Tips
 Chute Rotation (Standard):
 Hydraulic Motor Chute Rotation
 Including Hoses and Tips
 Chute Rotation Options: N/A
 Chute:
 Two Part, Includes Manual Deflector
 Three Part, Includes Cylinder
 (2 In. x 8 In.), Hoses and Tips
 Dual Auger: 14 In. Diameter Auger
 Rotating Drum (Including Hoses and Tips):
 N/A

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381DXF	SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	9,852.94
--------	---	----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	671.84

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	284.11
9002	Cutting Edge - Tivar	684.16

FRONTIER PRODUCTS

Snow Products

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation
and Single Auger - Canada**

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	656.41
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,449.88
9012		Serrated Main Auger	2,820.51
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	717.95
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

<p>Function: Snow Removal Working Width: 92 In. Transport Width: 93 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In. Side Panel Bottom Thickness: 5/8 In.</p>	<p>Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 75-125 HP Operating Weight: 2183 lbs. Shipping Weight: 2230 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard</p>
---	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381GXF		SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	13,384.12
--------	--	---	-----------

CHUTES

1000		2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010		3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	615.49

ATTACHMENTS - ORDER AS DESIRED

9000		Cutting Edge - CHT400 Steel	298.09
9002		Cutting Edge - Tivar	666.67

FRONTIER PRODUCTS

Snow Products

SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	666.67
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,470.59
9012		Serrated Main Auger	2,871.79
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,401.68
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	281.93
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	820.51
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Equipment for Base Machine

<p>Function: Snow Removal Working Width: 92 In. Transport Width: 93 In. Working Height: 44 In. Length: 65.5 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 1/4 In. Impeller Blade Thickness: 1/2 In. Side Panel Bottom Thickness: 3/4 In.</p>	<p>Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 5 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 75-125 HP Operating Weight: 2044 lbs. Shipping Weight: 2100 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): N/A</p>
--	---

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

381XF	SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada	11,045.36
-------	---	-----------

CHUTES

1000	2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	615.49

ATTACHMENTS - ORDER AS DESIRED

9000	Cutting Edge - CHT400 Steel	298.09
9002	Cutting Edge - Tivar	666.67

FRONTIER PRODUCTS

Snow Products

SB1392 - 92 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
ATTACHMENTS - ORDER AS DESIRED ...Continued...			
<i>Fully Plastic - Wear & Rust Resistant.</i>			
9003		Cutting Edge - Stainless Steel	666.67
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,470.59
9012		Serrated Main Auger	2,871.79
9020		Drift Cutters	385.18
9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	331.50
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,401.68
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	281.93
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	820.51
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	564.10

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

382BXF	SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada <i>Must only be used with HP2025 Hydraulic Power Unit.</i>	15,030.49
--------	---	-----------

HYDRAULIC POWER UNITS

1000	HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness to control the loader mounted implement.</i>	In Base Price
1095	Less Hydraulic Power Unit	-7,524.02

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i>	In Base Price
2095	Less Oil Cooler	-1,900.82

FRONTIER PRODUCTS

Snow Products

SB2164 - 64 In. Hydraulic, 300 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit- Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
CHUTES			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	708.86
ATTACHMENTS - ORDER AS DESIRED			
9020		Drift Cutters (SB21)	170.36
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i>	111.47

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada

Equipment for Base Machine

Function: Snow Removal
 Working Width: 64 In. (1,625.6 mm)
 Transport Width: 64 In. (1,625.6 mm)
 Working Height: 27 In. (685.8 mm)
 Single/Dual Auger: Single
 Auger Diameter: 15 In.
 Auger Flighting Thickness: 5/16 In. (8 mm)
 Impeller Diameter: 24 In. (609.6 mm)
 Impeller Width: 7 In. (177.8 mm)
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)
 Number of Impeller Blades: 4
 Auger Drive: Hydraulic
 Impeller Drive: Hydraulic
 Impeller RPM: 680 RPM
 Auger RPM: 200 RPM
 Skid Shoe: Adjustable
 Skid Shoe Material: Steel
 End Plate Thickness: 3/16 In. (4.8 mm)
 Back Plate Thickness: 11 Gauge (3.18 mm)
 Impeller Housing Thickness: 3/16 In. (4.8 mm)
 Impeller Blade Thickness: 1/4 In. (6.4 mm)
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)
 Cutting Edge: Replaceable
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)
 Chute Diameter: 8.25 In. (209.6 mm)
 Chute Base: Standard
 Chute Rotation: 270 Degrees
 Operating Weight: 760 lbs. (344.7 kg)
 Shipping Weight: 840 lbs. (381 kg)
 Approximate Set-Up Time: 120 Minutes
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder
 Chute Deflector Adjustment Options:
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder
 Chute: Two Part ONLY
 Dual Auger: N/A
 Rotating Drum (Including Hoses and Tips): N/A
 Function: Hydraulic Power Unit
 Pressure: 2700 psi
 Flow: 16 gpm
 Reservoir Capacity: 15 gal.
 System Capacity: 17 gal.
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch
 Hoses, Tips, and Brackets included
 Tractor RPM: 540 RPM
 PTO Manufacturer: Comer
 Parking Stand: Standard
 Hitch Category: Category I
 Quick Hitch Compatibility: iMatch Compatible
 Approximate Set-Up Time: 120 Minutes

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

382AXF	SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada <i>Must only be used with HP2134 Hydraulic Power Unit.</i>	15,811.48
--------	--	-----------

HYDRAULIC POWER UNITS

1010	HP2134 - Hydraulic Power Unit, 34 HP <i>Includes wiring harness to control the loader mounted implement.</i>	In Base Price
1095	Less Hydraulic Power Unit	-7,652.88

OIL COOLER

2000	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i>	In Base Price
2095	Less Oil Cooler	-1,900.82

FRONTIER PRODUCTS

Snow Products

SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower with Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - Canada

Continued

CODE	ATTACHMENT IDENTIFIER	DESCRIPTION	SUGGESTED LIST PRICE USD (\$)
CHUTES			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	708.86
ATTACHMENTS - ORDER AS DESIRED			
9020		Drift Cutters (SB21)	170.36
9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console. Not available with option Code 1095.</i>	111.47