

Jupiter Table

NORIX

SPECIFICATIONS



Model	Dimensions	Weight
CY3600	(36" Diameter x 29.3"H)	68 lbs
CY3636	(36"L x 36"W x 29.3"H)	80 lbs
CY4200	(42" Diameter x 29.3"H)	82 lbs
CY4242	(42"L x 42"W x 29.3"H)	99 lbs
CY4800	(48" Diameter x 29.3"H)	103 lbs

*Intended for indoor use only



DETAILS

Color

Base: Raven

Top: Kensington Maple, Asian Sun, Wild Cherry, Montana Walnut with coordinating edge. Titanium Evolve and Titanium Evolve Game Top with Black edge.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ballasting available (100 lbs).

Assembly

Refer to manufacturer's instructions for assembly.

Fabrication & Material

Base: Slightly textured, maintenance-free surface allows for easy cleaning. Rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading).

Top: Premium M3 Grade, 45 lb. density particle board table top core is sandwiched between 1/8" thick hardboard and faced with special 0.05" thick high pressure laminate for superior quality and long term durability. Molded edge is radiused for safety and comfort, pressure fused to the top, rendering it firmly attached and highly sanitary. Embedded T-nuts secure top to base with tight steel to steel connection for maximum long term reliability. Robust 1.5" thick edge profile. Made in the U.S.A.

Installation

Ballast weighting required to validate warranty. Recommended 100 pounds of sand ballast. Not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG
- Complies with Healthier Hospitals guidelines

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items

Performance Test Standards

Product tested to 1,000 lb static load

NORIX.COM

1800 W. Hawthorne Lane, Suite N, West Chicago, Illinois 60185
Phone: 630-231-1331 | Toll Free: 800-234-4900 | Email: furniture@norix.com
©2020 Norix Group, Inc.

Specifications subject to change without notice.
©2020 Norix Group, Inc. All Rights Reserved.
Printed in U.S.A. 1/20

SPECIFICATIONS



Model

C160

Weight

17 lbs

*Intended for indoor use only

Dimensions

Seat Height 17.5"

Seat Width 19"

Overall Height 31.5"

Depth 23"

Width 19"



DETAILS

Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ganging plates, Ballasting, Stainless Steel Bolt-down plate.

Assembly

None required

Fabrication & Material

One-piece, rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Anti-ligature design with no internal openings. Full perimeter floor support to facilitate ease of cleaning and to prevent concealment of contraband. Molded-in steel threaded inserts for optional ganging side-to-side or bolt-down applications. Made in the U.S.A.

Installation

Required for bolt-down plates, ganging plates and ballast. Recommended 50 pounds of ballast, 100 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

TESTING

Performance Test Standards:

- ANSI/BIFMA X5.1 2002 General Purpose Office Chairs
- Tested to 750 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- UL94 HB Test for Flammability of Plastic Materials

SPECIFICATIONS



Model

C140

Weight

30 lbs

*Intended for indoor use only

Dimensions

Seat Height	15.5"
Seat Width	21.8"
Overall Height	29.5"
Depth	25.3"
Width	26.8"
Arm Height	21.5"



DETAILS

Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Ganging plates, Ballasting, Stainless Steel plates for Bolt-down Kit

Assembly

None required

Fabrication & Material

One-piece, rotationally-molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ polymer is fully compounded for superior color consistency and durability. Anti-ligature design with no internal openings. Full perimeter floor support to facilitate ease of cleaning and to prevent concealment of contraband. Molded-in steel threaded inserts for optional ganging side-to-side, back-to-back or bolt-down applications. Made in the U.S.A.

Installation

Required for bolt-down plates, ganging plates and ballast. Recommended 50 lbs of sand or pea gravel ballast, 100 lbs maximum. Ballast not supplied by Norix.

Warranty

10 year limited replacement warranty.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

TESTING

Performance Test Standards:

- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards:

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture
- British Standard BS 7176: 2007, High Hazard Occupancy (BS EN 1012-1: 2006, BS EN 1012-2: 2006, BS 5852: 2006)

Integra Stacking Armless Chair

NORIX

SPECIFICATIONS



Model

C110

Weight

7.1 lbs

Dimensions

Seat Height 17.5"

Overall Height 32"

Seat Depth 17.2"

Width 17.6"

*Intended for indoor use only



DETAILS

Color

Canyon, Wild Berry, Meadow, Mojave, Pine Cone, River Rock, Lagoon, Graphite, Sea Spray

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

3 wheel dolly

Assembly

None required

Fabrication & Material

One-piece injection-molded, without steel or wood components. High impact grade copolymer polypropylene. Chemically resistant to acetone, alcohol, blood, vinegar, urine, feces, salt solution and chlorine solution.

Installation

None required

Warranty

10 year limited replacement warranty

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. For the deep-scrub cleaning of tougher stains, marks and debris, we recommend the use of Clorox® Clean-Up® Cleaner + Bleach or an equivalent cleaning solution.

TESTING

Performance Test Standards

ISO 14001:2015

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards:

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies.
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

NORIX.COM

1800 W. Hawthorne Lane, Suite N, West Chicago, Illinois 60185
Phone: 630-231-1331 | Toll Free: 800-234-4900 | Email: furniture@norix.com
©2020 Norix Group, Inc.

Specifications subject to change without notice.
©2020 Norix Group, Inc. All Rights Reserved.
Printed in U.S.A. 1/20